



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Intel Corporation
Intel SE440BX-2 (750 MHz Pentium III)

SPECfp2000 = 230
SPECfp_base2000 = 219

SPEC license #: 13 Tested by: Intel Corporation Test date: Mar-2000 Hardware Avail: Dec-1999 Software Avail: Feb-2000

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
168.wupwise	1600	598	268	577	277	
171.swim	3100	1159	268	1157	268	
172.mgrid	1800	973	185	973	185	
173.applu	2100	1166	180	1143	184	
177.mesa	1400	481	291	481	291	
178.galgel	2900	1289	225	1191	244	
179.art	2600	994	262	997	261	
183.quake	1300	633	206	491	265	
187.facerec	1900	1018	187	919	207	
188.amp	2200	876	251	876	251	
189.lucas	2000	865	231	861	232	
191.fma3d	2100	986	213	922	228	
200.sixtrack	1100	893	123	841	131	
301.apsi	2600	1045	249	1001	260	

Hardware

CPU: 750 MHz Pentium III processor
CPU MHz: 750
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 1 core/chip
CPU(s) orderable: 1
Parallel: No
Primary Cache: 16KBI + 16KBD on-die
Secondary Cache: 256KB(I+D) on-die ECC
L3 Cache: N/A
Other Cache: N/A
Memory: 256MB PC100 SDRAM
Disk Subsystem: IBM DJNA 371800 ATA-66
Other Hardware: Diamond Multimedia Viper 770 Ultra TNT2 AGP

Software

Operating System: Windows 2000 (Build 2195)
Compiler: Intel C and Fortran Compiler 4.5 for Windows 2000
Microsoft Visual C++ 6.0 C libraries, SmartHeap library
File System: FAT32
System State: Default

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning: -QaxK -Qipo_wp -O3 +FDO
Portability:
178.galgel: -FI -Fe$@ -link -stack:32000000
Peak tuning:
168.wupwise: -Qipo_wp -QxK +FDO
171.swim: -Qipo_wp -QaxK -O3 +FDO
172.mgrid: -Qipo_wp -QaxK -O3 +FDO
173.applu: -Qipo_wp -QxK +FDO
177.mesa: -Qipo_wp -QaxK -O3 +FDO shlW32M.lib
178.galgel: -Qipo_wp -QxK -O3 +FDO -Zi shlW32M.lib
179.art: -Qipo_wp -QxK +FDO shlW32M.lib
183.quake: -QxK -Qrcd -Ow -Qipo_wp +FDO shlW32M.lib
187.facerec: -Qipo_wp -QxK -O3 +FDO -Zi shlW32M.lib
188.amp: -Qipo_wp -QaxK -O3 +FDO shlW32M.lib
189.lucas: -Qipo_wp -QxK -O3 +FDO -Zi shlW32M.lib
191.fma3d: -QxK -O1 +FDO
```



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Intel Corporation
Intel SE440BX-2 (750 MHz Pentium III)

SPECfp2000 = 230

SPECfp_base2000 = 219

SPEC license #: 13 | Tested by: Intel Corporation | Test date: Mar-2000 | Hardware Avail: Dec-1999 | Software Avail: Feb-2000

Notes/Tuning Information (Continued)

200.sixtrack: -Qipo_wp -QxK +FDO

Tested systems can be used with Shin-G ATX case, Sparkle Inc., power supply

Product description located as of 03/2000:

http://developer.intel.com/design/motherbd/se2/se2_ds.htm

Motherboard is available through Intel OEM Distribution Channel. See

<http://channel.intel.com/> for more information

The system bus runs at 100 MHz