



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

IBM Corporation
IBM RS/6000 Model M80 (750 MHz)

SPECint_rate2000 = 20.3
SPECint_rate_base2000 = 18.7

SPEC license #: 11 | Tested by: IBM Corp. | Test date: Jul-2001 | Hardware Avail: Sep-2001 | Software Avail: Sep-2001

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	4	398	16.3	4	374	17.4
175.vpr	4	291	22.3	4	284	22.9
176.gcc	4	264	19.3	4	263	19.4
181.mcf	4	264	31.7	4	251	33.2
186.crafty	4	260	17.9	4	208	22.3
197.parser	4	593	14.1	4	536	15.6
252.eon	4	372	16.2	4	371	16.3
253.perlbnk	4	647	12.9	4	543	15.4
254.gap	4	392	13.0	4	382	13.4
255.vortex	4	529	16.7	4	434	20.3
256.bzip2	4	309	22.5	4	282	24.7
300.twolf	4	446	31.2	4	434	32.1

Hardware

CPU: RS64 IV
 CPU MHz: 750
 FPU: Integrated
 CPU(s) enabled: 4 cores, 4 chips, 1 core/chip
 CPU(s) orderable: 2,4,6,8
 Parallel: No
 Primary Cache: 128KBI+128KBD (on chip)
 Secondary Cache: 8MB unified (off chip)
 L3 Cache: None
 Other Cache: None
 Memory: 2GB
 Disk Subsystem: 1x9.1GB, 1x4.3GB Fast SCSI
 Other Hardware: None

Software

Operating System: AIX 5L V5.1
 Compiler: C: IBM VAC++ 5.0.2.0 invoked as 'cc' except where noted as 'xlc'
 C++: IBM VAC++ 5.0.2.0 invoked as 'xlc'
 File System: AIX/JFS
 System State: Multi-user

Notes/Tuning Information

Portability Flags:

```
gcc: -ma -qlanglvl=ansi -DHOST_WORDS_BIG_ENDIAN
crafty: -DAIX
eon: -DNEED_EXPLICIT_SPECIALIZATION
perlbnk: -DSPEC_CPU2000_AIX
gap: -DSYS_IS_BSD -DSYS_STRING_H -DSYS_HAS_TIME_PROTO -DSYS_HAS_MALLOC_PROTO
      -DSYS_HAS_CALLOC_PROTO
twolf: -DHAVE_SIGNED_CHAR
```

Base Flags:

```
C: -O4
C++: -qpdf1/pdf2 -O3 -qarch=ppc qtune=rs64b
```

Peak Flags:

```
164.gzip: CC=/usr/vac/bin/xlc -O5 -qarch=ppc, fdpr -v -R3
175.vpr: CC=/usr/vac/bin/xlc -O3 -qpdf1/pdf2 -qarch=rs64b -Q=500
        -L/usr/vac/lib -bnso -bI:/lib/syscalls.exp, fdpr -v -R3
176.gcc: -qpdf1/pdf2 -O3 -qarch=pwr3 -lhmu -L/usr/vac/lib, fdpr -v -R3
181.mcf: -O5 -lhmu -qipa=partition=large, fdpr -v -R3
186.crafty: -O4 -lhmu -q64, fdpr -v -R3
197.parser: -qpdf1/pdf2 CC=/usr/vac/bin/xlc -O4 -qarch=rs64b
        -L/usr/vac/lib -bnso -bI:/lib/syscalls.exp, fdpr -v -R3
```



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

IBM Corporation
IBM RS/6000 Model M80 (750 MHz)

SPECint_rate2000 = 20.3
SPECint_rate_base2000 = 18.7

SPEC license #: 11 | Tested by: IBM Corp. | Test date: Jul-2001 | Hardware Avail: Sep-2001 | Software Avail: Sep-2001

Notes/Tuning Information (Continued)

```
252.eon:      -qpdf1/pdf2 -O3 -qarch=ppc -qtune=rs64b -L/usr/vac/lib, fdpr -v -R3
253.perlbnk:  -qpdf1/pdf2 -O3 -qarch=rs64b -lhmu -qdatalocal -qunroll=8
              -L/usr/vac/lib, fdpr -v -R3
254.gap:      -O4 -qarch=rs64b, fdpr -v -R3
255.vortex:   -O5 -lhmu -qipa=partition=large, fdpr -v -R3
256.bzip2:    -O5 -lhmu, fdpr -v -R3
300.twolf:    CC=/usr/vac/bin/xlc -O5 -qpdf1/pdf2 -L/usr/vac/lib, fdpr -v -R3
fdpr: Feedback directed program restructuring tool
APAR IY 21957 was applied to AIX 5.1.0 to enable new hardware support.
/usr/spec2000 file system mounted with no JFS log file I/O.
```