



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Compaq Computer Corporation
AlphaStation XP1000 Model 6/667

SPECfp2000 = 532
SPECfp_base2000 = 452

SPEC license #: 2 | Tested by: Compaq NH | Test date: Sep-2001 | Hardware Avail: Aug-1999 | Software Avail: Aug-2001

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
168.wupwise	1600	375	426	320	500	
171.swim	3100	441	703	441	703	
172.mgrid	1800	551	327	417	432	
173.applu	2100	518	406	430	489	
177.mesa	1400	273	513	241	580	
178.galgel	2900	297	977	299	969	
179.art	2600	307	846	267	973	
183.earthquake	1300	581	224	280	464	
187.facerec	1900	327	581	323	589	
188.amp	2200	665	331	555	397	
189.lucas	2000	405	493	356	562	
191.fma3d	2100	519	405	432	486	
200.sixtrack	1100	416	264	366	300	
301.apsi	2600	676	385	646	402	

Hardware

CPU: Alpha 21264A
 CPU MHz: 667
 FPU: Integrated
 CPU(s) enabled: 1 core, 1 chip, 1 core/chip
 CPU(s) orderable: 1
 Parallel: No
 Primary Cache: 64KB(I)+64KB(D) on chip
 Secondary Cache: 4MB off chip
 L3 Cache: None
 Other Cache: None
 Memory: 512MB
 Disk Subsystem: 1x 8GB RZ2DC-KA
 Other Hardware: None

Software

Operating System: Compaq Tru64 UNIX V5.1 (Rev. 732)
 Compiler: Compaq C V6.4-215-46B7O
 Program Analysis Tools V2.0 BETA
 Spike V5.2 DTK (1.471.2.2 46B5P) BETA
 Compaq Fortran V5.4A-1472-46B2F
 Compaq Fortran 77 V5.4A-196-46B2F
 KAP Fortran V4.3 000607
 KAP Fortran 77 V4.1 980926
 KAP C V4.1 000607
 File System: AdvFS
 System State: Multi-user

Notes/Tuning Information

Baseline C: cc -arch ev6 -fast -O4 ONESTEP
 Fortran: f90 -arch ev6 -fast -O5 ONESTEP

Peak:

All use -g3 -arch ev6 -non_shared ONESTEP
 Individual benchmark tuning:
 168.wupwise: kf77 -fast -O4 -pipeline -unroll 2 +PFB
 171.swim: f90 -fast -O5
 172.mgrid: kf77 -O5 -transform_loops -tune ev6 -unroll 8
 173.applu: f90 -fast -O5 +PFB
 177.mesa: cc -fast -O4 +CFB +IFB
 -split_threshold .90 -noporder
 178.galgel: f90 -fast -O5
 179.art: kcc -fast -O4 -unroll 10 -ckapargs='-arl=4
 -ur=4' +PFB
 183.earthquake: cc -fast -xtaso_short -assume



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Compaq Computer Corporation
AlphaStation XP1000 Model 6/667

SPECfp2000 = 532
SPECfp_base2000 = 452

SPEC license #: 2 | Tested by: Compaq NH | Test date: Sep-2001 | Hardware Avail: Aug-1999 | Software Avail: Aug-2001

Notes/Tuning Information (Continued)

```

restricted_pointers -all -ldensemalloc -none +PFB
187.facerec: f90 -fast -O4 +PFB
188.ammp: cc -fast -O4 -xtaso_short -assume
restricted_pointers
189.lucas: kf90 -O5 -fkapargs='-ur=1' +PFB
191.fma3d: kf90 -O4 -transform_loops +PFB
200.sixtrack: f90 -fast -O5 -assume accuracy_sensitive
-notransform_loops +PFB
301.apsi: kf90 -O5 -transform_loops -unroll 8
-fkapargs='-ur=1' +PFB

```

Most benchmarks are built using one or more types of profile-driven feedback. The types used are designated by abbreviations in the notes:

+CFB: Code generation is optimized by the compiler, using feedback from a training run. These commands are done before the first compile (in phase "fdo_pre0"):

```

mkdir /tmp/pp
rm -f /tmp/pp/${baseexe}*

```

and these flags are added to the first and second compiles:

```

PASS1_CFLAGS = -prof_gen_noopt -prof_dir /tmp/pp
PASS2_CFLAGS = -prof_use -prof_dir /tmp/pp

```

(Peak builds use /tmp/pp above; base builds use /tmp/pb.)

+IFB: Icache usage is improved by the post-link-time optimizer Spike, using feedback from a training run. These commands are used (in phase "fdo_postN"):

```

mv ${baseexe} oldexe
spike oldexe -feedback oldexe -o ${baseexe}

```

+PFB: Prefetches are improved by the post-link-time optimizer Spike, using feedback from a training run. These commands are used (in phase "fdo_post_makeN"):

```

rm -f *Counts*
mv ${baseexe} oldexe
pixie -stats dstride oldexe 1>pixie.out 2>pixie.err
mv oldexe.pixie ${baseexe}

```

A training run is carried out (in phase "fdo_runN"), and then this command (in phase "fdo_postN"):

```

spike oldexe -fb oldexe -stride_prefetch -o ${baseexe}

```

When Spike is used for both Icache and Prefetch improvements, only one spike command is actually issued, with the Icache options followed by the Prefetch options.

Portability: galgel: -fixed

Process limits are set to maximum using csh "unlimit" command



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Compaq Computer Corporation
AlphaStation XP1000 Model 6/667

SPECfp2000 = 532

SPECfp_base2000 = 452

SPEC license #: 2 | Tested by: Compaq NH | Test date: Sep-2001 | Hardware Avail: Aug-1999 | Software Avail: Aug-2001

Notes/Tuning Information (Continued)

Spike, and the Program Analysis Tools, are part of the Developers' Tool Kit Supplement, <http://www.tru64unix.compaq.com/dtk/>. The features used in this SPEC submission will be available at the web site as a beta kit in August, 2001, and as a production release in October, 2001.