



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers PRIMEPOWER400 (700MHz)

SPECint2000 = 521
SPECint_base2000 = 448

SPEC license #: 22 Tested by: Fujitsu Limited Test date: Jun-2002 Hardware Avail: Sep-2002 Software Avail: May-2002

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
164.gzip	1400	345	406	300	467	
175.vpr	1400	338	414	313	447	
176.gcc	1100	366	301	235	469	
181.mcf	1800	359	501	359	501	
186.crafty	1000	227	441	174	575	
197.parser	1800	389	463	353	510	
252.eon	1300	244	533	220	591	
253.perlbnk	1800	356	506	313	575	
254.gap	1100	409	269	403	273	
255.vortex	1900	278	683	198	960	
256.bzip2	1500	319	470	288	520	
300.twolf	3000	547	548	500	600	

Hardware

CPU: SPARC64 GP
CPU MHz: 700
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 1 core/chip
CPU(s) orderable: 1 to 4
Parallel: None
Primary Cache: 128KBI+128KBD on chip
Secondary Cache: 8MB(I+D) off chip, per CPU
L3 Cache: None
Other Cache: None
Memory: 8192MB
Disk Subsystem: 1 x 36.4GB SCSI (10000rpm)
Other Hardware: Ethernet

Software

Operating System: Solaris 8 2/02 with patches 108434-07 and 108435-07.
Compiler: Fujitsu Parallelnavi 1.0.2 with patches 911403-01 and 911746-01, Sun ONE Studio 7 with patches 111704-01, 111705-01, 111706-01, 111708-01, 111709-01, 111715-01 and 111716-01, Sun Performance Library 7
File System: ufs
System State: single user

Notes/Tuning Information

Baseline (except 252.eon, for Parallelnavi 1.0.2): -Kfast_GP=3,largepage
fdo_pre0=rm -rf `pwd`/*.fbk
PASS1=-Kpg
PASS2=-Kpu=\$(EXEBASE).fbk
(252.eon, for Sun ONE Studio 7): -fast -xcrossfile -xtarget=ultra3
fdo_pre0=rm -rf `pwd`/../feedback.profile `pwd`/SunWS_cache
PASS1=-xprofile=collect:`pwd`/../feedback
PASS2=-xprofile=use:`pwd`/../feedback

Peak

(for Sun ONE Studio 7)
fdo_pre0=rm -rf `pwd`/../feedback.profile `pwd`/SunWS_cache
PASS1=-xprofile=collect:`pwd`/../feedback
PASS2=-xprofile=use:`pwd`/../feedback
164.gzip: -x05 -xtarget=ultra3 -xalias_level=std -W2,-whole -xcrossfile -W2,-Ainline -xprefetch -Wc,-Qgsched-trace_late=1,-Qgsched-spec_load=1 -l12amm
175.vpr: -fast -xarch=v8plusb -xalias_level=std -xcrossfile -xsfpcnst -xdepend -W2,-whole,-Mt600,-Mr4000 -Wc,-Qeps:enabled=1,-Qeps:do_spec_load=1,-Qeps:rp_filtering_margin=100 -xregs=syst -xprefetch=auto,latx:5.0 -lprism32 -lmopt -lm
176.gcc: -fast -xtarget=ultra3 -xcrossfile -W2,-whole -Wc,-Qgsched-trace_late=1,-Qgsched-T4 -l12amm



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers
PRIMEPOWER400 (700MHz)

SPECint2000 = 521
SPECint_base2000 = 448

SPEC license #: 22 | Tested by: Fujitsu Limited | Test date: Jun-2002 | Hardware Avail: Sep-2002 | Software Avail: May-2002

Notes/Tuning Information (Continued)

```

186.crafty: -fast -xtarget=ultra3 -xarch=v8plus -xF -xinline= -xcrossfile -Wc,-Qgsched-spec_load=1,-Qiselect-funcalign=64 -xalias_level=strong -xregs=syst
  -W2,-Ashort_ldst,-Aivel:duplicate_loops -xprefetch=auto,latx:5.0
197.parser: -fast -xarch=v8plusb -xdepend -xprefetch=no%auto -xcrossfile
  -xregs=syst -Wc,-Qgsched-trace_late=1,-Qgsched-T4 -xalias_level=strong
  -Wc,-Qipa:valueprediction -W2,-Ashort_ldst,-Mt5000 -Wc,-Qiselect-funcalign=32 -lprism32
252.eon: -fast -xtarget=ultra3 -xcrossfile -xalias_level=compatible -xsafe=mem
  -Qoption iropt -Mt2000,-xrestrict -Qoption cg -Qgsched-trace_spec_load=1,-Qgsched-trace_late=1
253.perlbnk: -xO5 -xtarget=ultra3 -xarch=v8plusb -xcrossfile -xalias_level=strong
  -xsafe=mem -Wc,-Qgsched-trace_late=1,-Qgsched-T4,-Qgsched-trace_spec_load=1 -Wc,-Qinline_memcpy=32 -Wc,-Qiselect-funcalign=32,-Qicache-chbab=1
  -Wc,-Qiselect-sw_pf_tbl_th=20 -W2,-Adata_access -xprefetch=auto,latx:5.0 -l12amm -dn
255.vortex: -fast -xtarget=ultra3 -xcrossfile -W2,-Aheap,-reroll=1,-Aunroll,-Msl,-Mt600,-Mr13000,-crit
  -Wc,-Qdepgraph-early_cross_call=1 -Wc,-Qiselect-funcalign=32
  -Wc,-Qpeep-Sh0 -xrestrict -xdepend -W2,-Amemopt -l12amm -lprism32
256.bzip2: -fast -xtarget=ultra3 -W2,-whole,-crit -xcrossfile -xalias_level=strong -Wc,-Qiselect-funcalign=32
  -xdepend -xregs=syst -xsfpcnst -Wc,-Qgsched-trace_spec_load=1 -xsafe=mem -l12amm -lprism32

```

(for Parallelnavi 1.0.2):

fdo_pre0=rm -rf `pwd`/*.fbk

PASS1=-Kpg

PASS2=-Kpu=\$(EXEBASE).fbk

181.mcf: basepeak=yes

254.gap: -Kfast_GP=3,popt,eval,cfunc,largepage,xi=10

300.twolf: -Kfast_GP=5,eval,GREG,popt,cfunc,staticclump,use_rodata,xi=10,largepage,bcopy,nounroll,prefetch=4

Portability:

176.gcc: -Dalloca=__builtin_alloca -DHOST_WORDS_BIG_ENDIAN

186.crafty: -DSUN

252.eon: -library=iostream

253.perlbnk: -DSPEC_CPU2000_SOLARIS

254.gap: -DSYS_IS_USG -DSYS_HAS_TIME_PROTO -DSYS_HAS_SIGNAL_PROTO -DSYS_HAS_CALLOC_PROTO

Note:

System Tunables: (for /etc/system)

consistent_coloring=1, tune_t_fsflushr=86400, autoup=86400,

shmsys:shminfo_shmmax=1477846784, shmsys:shminfo_shmmni=1024, shmsys:shminfo_shmseg=1024,shminfo_shmmin=1

(for /etc/opt/FJSVpnm/lpg.conf)

TSS=4G, SHMSEGSIZE=256M

Shell Environments:

LD_LIBRARY_PATH="/usr/lib:/opt/SUNWspro/lib/v8plusb:/opt/SUNWspro/prod/lib/v8plusb:/opt/FSUNf90/lib"

LD_LIBRARY_PATH_64="/usr/lib/64:/opt/SUNWspro/lib/v9:/opt/SUNWspro/prod/lib/v9"

PRISM_HEAP=268435456

PRISM_MODE=2

ONESTEP=yes was set for all baseline and peak benchmarks.

Feedback directed optimization was used for all baseline and peak benchmarks.

System board used with only one CPU present.