



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Fujitsu Limited
PRIMEPOWER800/1000/2000 (788MHz)

SPECint_rate2000 = 368
SPECint_rate_base2000 = 335

SPEC license #: 19 | Tested by: Fujitsu Limited | Test date: Aug-2002 | Hardware Avail: Aug-2002 | Software Avail: May-2002

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.zip	64	331	314	64	306	340
175.vpr	64	346	300	64	337	308
176.gcc	64	458	178	64	384	213
181.mcf	64	405	330	64	365	366
186.crafty	64	206	361	64	157	472
197.parser	64	358	373	64	348	384
252.eon	64	239	404	64	196	493
253.perlbnk	64	332	402	64	288	464
254.gap	64	455	179	64	448	182
255.vortex	64	256	551	64	256	551
256.bzip2	64	291	383	64	291	383
300.twolf	64	513	435	64	469	474

Hardware

CPU: SPARC64 GP
CPU MHz: 788
FPU: Integrated
CPU(s) enabled: 64 cores, 64 chips, 1 core/chip
CPU(s) orderable: 4 to 16/4 to 32/8 to 128
Parallel: None
Primary Cache: 128KBI+128KBD on chip
Secondary Cache: 8MB(I+D) off chip, per CPU
L3 Cache: None
Other Cache: None
Memory: 16GB
Disk Subsystem: 1 x 36GB, 1 x 18GB SCSI (10000rpm)
Other Hardware: Ethernet

Software

Operating System: Solaris 8 2/02 with patches 108434-07 and 108435-07.
Compiler: Fujitsu Parallelnavi 1.0.2
with patches 911403-01 and 911746-01.
Sun ONE Studio 7 with current patches (see notes)
Sun Performance Library 7

File System: ufs
System State: multi user

Notes/Tuning Information

Baseline (except 252.eon, for Parallelnavi 1.0.2): -Kfast_GP=3,largepage

fdo_pre0=rm -rf `pwd`/*.fbk

PASS1=-Kpg

PASS2=-Kpu=\$(EXEBASE).fbk

(252.eon, for Sun ONE Studio 7): -fast -xcrossfile

fdo_pre0=rm -rf `pwd`/../feedback.profile `pwd`/SunWS_cache

PASS1=-xprofile=collect:`pwd`/../feedback

PASS2=-xprofile=use:`pwd`/../feedback

Peak

(for Sun ONE Studio 7)

fdo_pre0=rm -rf `pwd`/../feedback.profile `pwd`/SunWS_cache

PASS1=-xprofile=collect:`pwd`/../feedback

PASS2=-xprofile=use:`pwd`/../feedback

164.zip: -xO5 -xtarget=ultra3 -xalias_level=std -W2,-whole -xcrossfile

-W2,-Ainline -xprefetch -Wc,-Qgsched-trace_late=1,-Qgsched-spec_load=1 -l12amm

176.gcc: -fast -xtarget=ultra3 -xcrossfile -W2,-whole -Wc,-Qgsched-trace_late=1,-Qgsched-T4 -l12amm

186.crafty: -fast -xtarget=ultra3 -xarch=v8plus -xP -xinline= -xcrossfile -Wc,-Qgsched-spec_load=1,-Qiselect-funcalign=64

-xalias_level=strong -xregs=syst -W2,-Ashort_ldst,-Aivel:duplicate_loops -xprefetch=auto,latx:5.0

252.eon: -fast -xtarget=ultra3 -xcrossfile -xalias_level=compatible -xsafe=mem -Qoption iropt

Standard Performance Evaluation Corporation

info@spec.org

http://www.spec.org



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Fujitsu Limited
PRIMEPOWER800/1000/2000 (788MHz)

SPECint_rate2000 = 368
SPECint_rate_base2000 = 335

SPEC license #: 19 | Tested by: Fujitsu Limited | Test date: Aug-2002 | Hardware Avail: Aug-2002 | Software Avail: May-2002

Notes/Tuning Information (Continued)

```
-Mt2000,-xrestrict -Qoption cg -Qgsched-trace_spec_load=1,-Qgsched-trace_late=1
253.perlbnk: -xO5 -xtarget=ultra3 -xarch=v8plusb -xcrossfile -xalias_level=strong -xsafe=mem
-Wc,-Qgsched-trace_late=1,-Qgsched-T4,-Qgsched-trace_spec_load=1 -Wc,-Qinline_memcpy=32
-Wc,-Qiselect-funcalign=32,-Qicache-chbab=1 -Wc,-Qiselect-sw_pf_tbl_th=20 -W2,-Adata_access -xprefetch=auto,latx:5.0 -l12amm -dn
```

(for Parallelnavi 1.0.2):

```
fdo_pre0=rm -rf `pwd`/*.fbk
```

```
PASS1=-Kpg
```

```
PASS2=-Kpu=$(EXEBASE).fbk
```

```
175.vpr: -Kfast_GP=4,staticclump,eval,preex,popt,switchopt,cond,GREG,nounroll,largepage,NOFLTLD=5,fconst,xi=30
```

```
181.mcf: -Kfast_GP=2,GREG,eval,preex,popt,unroll=2,prefetch=4,largepage,preload -x-
```

```
197.parser: -Kfast_GP=4,switchopt,cond,staticclump,use_rodata,largepage
```

```
254.gap: -Kfast_GP=3,popt,eval,cfunc,largepage,xi=10
```

```
255.vortex: -Kfast_GP=3,GREG,popt,staticclump,use_rodata,cond,cfunc,switchopt,largepage
```

```
256.bzip2: -Kfast_GP=3,largepage
```

```
300.twolf: -Kfast_GP=5,eval,GREG,popt,cfunc,staticclump,use_rodata,xi=10,largepage,bcopy,nounroll,prefetch=4
```

Portability:

```
176.gcc: -Dalloca=__builtin_alloca -DHOST_WORDS_BIG_ENDIAN
```

```
186.crafty: -DSUN
```

```
252.eon: -library=iostream
```

```
253.perlbnk: -DSPEC_CPU2000_SOLARIS
```

```
254.gap: -DSYS_IS_USG -DSYS_HAS_TIME_PROTO -DSYS_HAS_SIGNAL_PROTO -DSYS_HAS_CALLOC_PROTO
```

Note:

System Tunables: (for /etc/system)

```
consistent_coloring=1, tune_t_fsflushr=86400, autoup=86400,
```

```
shmsys:shminfo_shmmax=1477846784, shmsys:shminfo_shmni=1024, shmsys:shminfo_shmseg=1024,shminfo_shmmin=1
```

(for /etc/opt/FJSVpnm/lpg.conf)

```
TSS=32768M, SHMSEGSIZE=256M
```

Shell Environments:

```
LD_LIBRARY_PATH="/usr/lib:/opt/SUNWspro/lib/v8plusb:/opt/SUNWspro/prod/lib/v8plusb:/opt/FSUNf90/lib"
```

```
LD_LIBRARY_PATH_64="/usr/lib/64:/opt/SUNWspro/lib/v9:/opt/SUNWspro/prod/lib/v9"
```

```
PRISM_HEAP=268435456
```

```
PRISM_MODE=2
```

ONESTEP=yes was set for all baseline and peak benchmarks.

Feedback directed optimization was used for all baseline and peak benchmarks.

All patches of Sun ONE Studio 7 posted at URL <http://access1.sun.com/sundev/sls7-patches.html>

as of date 2002/6/4 were applied: 111704-01, 111705-01, 111706-01,

111708-01, 111709-01, 111715-01, 111716-01.