



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Intel Corporation

Intel D850EMV2 motherboard (2.53 GHz, Pentium 4 processor)

SPECfp2000 = 889

SPECfp_base2000 = 875

SPEC license #: 13 Tested by: Intel Corporation Test date: May-2002 Hardware Avail: May-2002 Software Avail: Apr-2002

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
168.wupwise	1600	141	1137	140	1144	
171.swim	3100	225	1379	222	1398	
172.mgrid	1800	220	820	217	829	
173.applu	2100	234	897	228	920	
177.mesa	1400	146	961	145	965	
178.galgel	2900	235	1233	232	1252	
179.art	2600	479	543	461	565	
183.quake	1300	129	1004	123	1053	
187.facerec	1900	170	1119	168	1132	
188.amp	2200	381	577	378	582	
189.lucas	2000	166	1206	166	1207	
191.fma3d	2100	237	884	237	887	
200.sixtrack	1100	240	457	233	472	
301.apsi	2600	393	661	393	661	

Hardware

CPU: Pentium 4 processor (2.53 GHz, 533 MHz bus)
 CPU MHz: 2533
 FPU: Integrated
 CPU(s) enabled: 1 core, 1 chip, 1 core/chip
 CPU(s) orderable: 1
 Parallel: No
 Primary Cache: 12k micro-ops I + 8KBD on chip
 Secondary Cache: 512KB(I+D) on chip
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 256 MB (2 128 MB PC800-40 RDRAM non-ECC modules)
 Disk Subsystem: IBM 120GXP 80 GB IC35L080AVVA07-0 ATA-100
 Other Hardware: None

Software

Operating System: Windows XP Professional(Build 2600)
 Compiler: Intel C++ Compiler 6.0 Build 020321Z
 Intel Fortran Compiler 6.0 Build 020321Z
 Microsoft Visual C++ 6.0 SP5(for libraries)
 File System: FAT32
 System State: Default

Notes/Tuning Information

```
+FDO: PASS1= -Qprof_gen PASS2=-Qprof_use
Base tuning: -Qipo -QxW -O3 +FDO
Portability:
178.galgel: -FI /F32000000
Peak tuning:
168.wupwise: -Qipo -QxW -O3 +FDO
171.swim: -Qipo -QxW -O3 +FDO
172.mgrid: -Qipo -QaxW -O3 +FDO
173.applu: -Qipo -QxW -O3 -Qscalar_rep- -Qauto +FDO
177.mesa: -Qipo -Oa -QxW -O3 +FDO
178.galgel: -Qipo -QxW -O3 +FDO
179.art: -Qipo -QxW -O3 -Oa +FDO
183.quake: -Qipo -QxW -Oa -Qrcd +FDO
187.facerec: -Qipo -QxW -O3 +FDO
188.amp: -Qipo -QxW -O3 -Oa +FDO
189.lucas: -Qipo -QxW -O3 +FDO
191.fma3d: -Qipo -QxW -O3 +FDO
```



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Intel Corporation

Intel D850EMV2 motherboard (2.53 GHz, Pentium 4 processor)

SPECfp2000 = 889

SPECfp_base2000 = 875

SPEC license #: 13 | Tested by: Intel Corporation | Test date: May-2002 | Hardware Avail: May-2002 | Software Avail: Apr-2002

Notes/Tuning Information (Continued)

200.sixtrack: -Qipo -QxW +FDO

301.apsi: -Qipo -QxW -O3 +FDO

Tested systems can be used with Shin-G ATX case, Delta Inc. power supply PS-300GB-1 B

Product description located as of 8/2002:

<http://developer.intel.com/design/motherbd/mv2/index.htm>

Motherboard ordering information is available at:

<http://program.intel.com/shared/products/boards/d850emv2/index.htm>

The system bus runs at 533 MHz