



# CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems  
Sun Blade 2500 (1.28GHz)

SPECfp\_rate2000 = 11.8

SPECfp\_rate\_base2000 = 10.2

SPEC license #: 6 | Tested by: Sun Microsystems, Santa Clara | Test date: Aug-2003 | Hardware Avail: Dec-2003 | Software Avail: May-2003

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	1	169	11.0	1	157	11.8
171.swim	1	337	10.7	1	160	22.5
172.mgrid	1	271	7.71	1	271	7.70
173.applu	1	279	8.73	1	225	10.8
177.mesa	1	199	8.18	1	185	8.77
178.galgel	1	206	16.4	1	183	18.4
179.art	1	33.8	89.3	1	31.2	96.8
183.quake	1	93.4	16.1	1	87.3	17.3
187.facerec	1	169	13.1	1	161	13.7
188.amp	1	482	5.30	1	484	5.27
189.lucas	1	523	4.44	1	289	8.03
191.fma3d	1	377	6.46	1	350	6.95
200.sixtrack	1	250	5.11	1	239	5.35
301.apsi	1	365	8.27	1	366	8.24

### Hardware

CPU: UltraSPARC IIIi  
 CPU MHz: 1280  
 FPU: Integrated  
 CPU(s) enabled: 1 core, 1 chip, 1 core/chip  
 CPU(s) orderable: 1-2  
 Parallel: No  
 Primary Cache: 32KBI+64KBD on chip  
 Secondary Cache: 1MB(I+D) on chip  
 L3 Cache: None  
 Other Cache: None  
 Memory: 4GB (4x1GB DIMM)  
 Disk Subsystem: 1x36GB 10K RPM SCSI  
 Other Hardware: None

### Software

Operating System: Solaris 8 HW 5/03  
 Compiler: Sun ONE Studio 8  
 Sun Performance Library 8  
 File System: ufs with ufs logging  
 System State: Multi-User

## Notes/Tuning Information

#### Compiler invocation:

C: cc  
 F90: f90  
 F77: f90

#### Floating point base flags:

C: -fast -xipo=2 -xalias\_level=std with ONESTEP=yes and feedback  
 F90: -fast -xipo=2 with ONESTEP=yes and feedback

#### Floating point peak flags:

ONESTEP=yes and feedback for all benchmarks, unless otherwise noted

168.wupwise: -fast -xipo=2 -Qoption iropt -Ainline:inc=800:cp=1  
 171.swim: -fast -xpad=common:384 -xprefetch=latx:1.6  
 -Qoption iropt -Atile:skewp:b6,-Ainline:cs=700  
 (no feedback)  
 172.mgrid: -fast -xipo=2



# CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems  
Sun Blade 2500 (1.28GHz)

SPECfp\_rate2000 = 11.8  
SPECfp\_rate\_base2000 = 10.2

SPEC license #: 6 | Tested by: Sun Microsystems, Santa Clara | Test date: Aug-2003 | Hardware Avail: Dec-2003 | Software Avail: May-2003

## Notes/Tuning Information (Continued)

```
173.applu: -fast -xipo=2
           -Qoption cg -Qlp=1-av=192-fa=1,-Qms_pipe+prefolim=7
           -Qoption iropt -Aujam:inner=g
177.mesa:  -fast -xipo=2 -xalias_level=strong -xrestrict
           -Wc,-Qms_pipe+unoovf
178.galgel: -fast -xipo=2 -Qoption iropt -Addint:sf=9 -xlic_lib=sunperf
           RM_SOURCES=lapak.f90
179.art:    -fast -xipo=2 -xalias_level=std -xprefetch=latx:1.5
183.quake: -fast -xipo=2 -xalias_level=strong -xprefetch_level=2
187.facerec: -fast -xipo=2 -xprefetch=latx:1.5
188.ampp:   -fast -xipo=2 -xalias_level=std -lmopt -lm
189.lucas:  -fast -xprefetch_level=3 -Qoption iropt -Apf:pdl=1
           -Qoption f90comp -array_pad_rows,1977
191.fma3d:  -fast -stackvar -xprefetch_level=3
           -Qoption iropt -Apf:pdl=1
200.sixtrack: -O -dalign -xchip=ultra3 -xarch=v8plusb -fsimple=2
301.apsi:    -fast -xipo=2
```

Feedback is done as follows, unless otherwise noted:

```
fdo_pre0: rm -rf ./feedback.profile ./SunWS_cache
PASS1:    -xprofile=collect:./feedback
PASS2:    -xprofile=use:./feedback
```

Portability:

```
178.galgel: -e -fixed
```

Shell Environments:

```
Stack size set to unlimited via "ulimit -s unlimited"
```

Kernel Parameters (/etc/system):

```
autoup=900
tune_t_fsflushr=1
```

System Settings:

```
2nd cpu physically removed from system
```