



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire V250 (1.28GHz)

SPECfp2000 = 1054

SPECfp_base2000 = 954

SPEC license #: 6 Tested by: Sun Microsystems, Santa Clara Test date: Sep-2003 Hardware Avail: Sep-2003 Software Avail: Aug-2003

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio
168.wupwise	1600	166	963	155	1033
171.swim	3100	318	975	172	1797
172.mgrid	1800	256	703	257	700
173.applu	2100	274	766	219	960
177.mesa	1400	199	705	185	757
178.galgel	2900	192	1512	167	1735
179.art	2600	33.5	7760	31.6	8228
183.earth	1300	87.1	1493	80.6	1613
187.facerec	1900	173	1099	156	1215
188.amp	2200	469	469	472	466
189.lucas	2000	228	877	242	825
191.fma3d	2100	373	563	347	606
200.sixtrack	1100	252	436	240	458
301.apsi	2600	350	743	350	744

Hardware

CPU: UltraSPARC IIIi
CPU MHz: 1280
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 1 core/chip
CPU(s) orderable: 1-2
Parallel: No
Primary Cache: 32KBI+64KBD on chip
Secondary Cache: 1MB(I+D) on chip
L3 Cache: None
Other Cache: None
Memory: 4GB 16-way interleaved
Disk Subsystem: 1 x 36GB SEAGATE ST336607LSUN36G
Other Hardware: None

Software

Operating System: Solaris 9 8/03
Compiler: Sun ONE Studio 8
Sun Performance Library 8
File System: ufs with ufs logging
System State: Multi-User

Notes/Tuning Information

Compiler invocation:

C: cc
CXX: CC
F90: f90
F77: f90

Floating point base flags:

C: -fast -xipo=2 -xalias_level=std with ONESTEP=yes and feedback
F90: -fast -xipo=2 with ONESTEP=yes and feedback

Floating point peak flags:

ONESTEP=yes and feedback for all benchmarks, unless otherwise noted

168.wupwise: -fast -xipo=2 -Qoption iropt -Ainline:inc=800:cp=1
171.swim: -fast -xpad=common:384 -xprefetch=latx:1.6
-Qoption iropt -Atile:skewp:b6,-Ainline:cs=700
(no feedback)



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire V250 (1.28GHz)

SPECfp2000 = 1054
SPECfp_base2000 = 954

SPEC license #: 6 | Tested by: Sun Microsystems, Santa Clara | Test date: Sep-2003 | Hardware Avail: Sep-2003 | Software Avail: Aug-2003

Notes/Tuning Information (Continued)

```

172.mgrid: -fast -xipo=2
173.applu: -fast -xipo=2
           -Qoption cg -Qlp=1-av=192-fa=1,-Qms_pipe+prefolim=7
           -Qoption iropt -Aujam:inner=g
177.mesa: -fast -xipo=2 -xalias_level=strong -xrestrict
           -Wc,-Qms_pipe+unoovf
178.galgel: -fast -xipo=2 -Qoption iropt -Addint:sf=9 -xlic_lib=sunperf
           RM_SOURCES=lapak.f90
179.art: -fast -xipo=2 -xalias_level=std -xprefetch=latx:1.5
183.equake: -fast -xipo=2 -xalias_level=strong -xprefetch_level=2
187.facerec: -fast -xipo=2 -xprefetch=latx:1.5
188.ammp: -fast -xipo=2 -xalias_level=std -lmopt -lm
189.lucas: -fast -xprefetch_level=3 -Qoption iropt -Apf:pdl=1
           -Qoption f90comp -array_pad_rows,1977
191.fma3d: -fast -stackvar -xprefetch_level=3
           -Qoption iropt -Apf:pdl=1
200.sixtrack: -O -dalign -xchip=ultra3 -xarch=v8plusb -fsimple=2
301.apsi: -fast -xipo=2

```

Feedback is done as follows, unless otherwise noted:

```

fdo_pre0: rm -rf ./feedback.profile ./SunWS_cache
PASS1: -xprofile=collect:./feedback
PASS2: -xprofile=use:./feedback

```

Portability:

178.galgel: -e -fixed

Shell Environments:

```

Stack size set to unlimited via "ulimit -s unlimited"
MPSSHEAP=512K
MPSSSTACK=512K
LD_PRELOAD=mpss.so.1

```

Kernel Parameters (/etc/system):

```

autoup=900
tune_t_fsflushr=1

```

System Settings:

2nd CPU physically removed from the system