



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Intel Corporation

Intel D875PBZ (AA-206) motherboard (3.2 GHz, Pentium 4 processor with Hyper-Threading Technology Extreme Edition)

SPECfp2000 = 1493

SPECfp_base2000 = 1474

SPEC license #: 13 Tested by: Intel Corporation Test date: Sep-2003 Hardware Avail: Nov-2003 Software Avail: Apr-2003

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
168.wupwise	1600	92.5	1729	91.9	1741	
171.swim	3100	162	1914	163	1905	
172.mgrid	1800	136	1322	136	1323	
173.applu	2100	161	1306	161	1308	
177.mesa	1400	106	1321	105	1333	
178.galgel	2900	111	2603	111	2607	
179.art	2600	113	2296	109	2376	
183.quake	1300	83.6	1555	78.5	1656	
187.facerec	1900	114	1666	108	1766	
188.ammmp	2200	175	1256	174	1265	
189.lucas	2000	123	1622	123	1623	
191.fma3d	2100	158	1328	158	1328	
200.sixtrack	1100	184	598	183	600	
301.apsi	2600	215	1210	215	1210	

Hardware

CPU: Intel Pentium 4 Processor with Hyper-Threading Technology Extreme Edition (3.2 GHz, 800 MHz bus)
CPU MHz: 3200
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 1 core/chip (Hyper-Threading Technology enabled)
CPU(s) orderable: 1
Parallel: No
Primary Cache: 12k micro-ops I + 8KBD on chip
Secondary Cache: 512KB(I+D) on chip
L3 Cache: 2MB(I+D) on chip
Other Cache: N/A
Memory: 1 GB(2 512MB PC3200 Samsung Double-sided CL3-3-3 DIMMs)
Disk Subsystem: Seagate ST3160023AS 160 GB Serial ATA (7200 RPM, 8MB cache)
Other Hardware: None

Software

Operating System: Windows XP Professional Service Pack 1a
Compiler: Intel C++ and Fortran Compiler 7.1 Build 20030224Z
Microsoft Visual Studio .Net 7.0(for libraries)
MicroQuill SmartHeap library V6.0
File System: NTFS
System State: Default

Notes/Tuning Information

```

ONESTEP=yes +FDO: PASS1= -Qprof_gen PASS2=-Qprof_use
Base tuning: -Qipo -QxW -O3 +FDO
Portability:
178.galgel: -FI /F32000000
Peak tuning:
168.wupwise: -Qipo -QxW -O3 +FDO
171.swim: -Qipo -QxW -O3 +FDO
172.mgrid: -Qipo -QaxW -O3 +FDO
173.applu: -Qipo -QxW -O3 -Qscalar_rep- -Qauto +FDO
177.mesa: -Qipo -QxW -O3 -Oa -Qscalar_rep- +FDO
178.galgel: -Qipo -QxW -O3 +FDO
179.art: -Oa -Qipo -Qunroll4 -Zp4
183.quake: -Qipo -QxW -Oa -Qrcd +FDO
187.facerec: -Qipo -QaxW -O3 -Qunroll1 -Qscalar_rep- +FDO
188.ammmp: -Oa -QxW
189.lucas: -Qipo -QxW -O3 -Qprefetch- +FDO
191.fma3d: basepeak=yes

```



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Intel Corporation

Intel D875PBZ (AA-206) motherboard (3.2 GHz, Pentium 4 processor with Hyper-Threading Technology Extreme Edition)

SPECfp2000 = 1493

SPECfp_base2000 = 1474

SPEC license #: 13 | Tested by: Intel Corporation | Test date: Sep-2003 | Hardware Avail: Nov-2003 | Software Avail: Apr-2003

Notes/Tuning Information (Continued)

200.sixtrack: -Qipo -QxW +FDO

301.apsi: -Qipo -QxW -O3 +FDO

Tested systems can be used with Shin-G ATX case, Delta Inc. power supply PS-300GB-1

Product description located as of 9/2003:

<http://developer.intel.com/design/motherbd/bz/index.htm>

Motherboard is available through Intel OEM Distribution Channel. See

http://www.intel.com/cd/channel/reseller/asm-na/eng/products/box_desktop_boards/p4_boards/p4_dsk_board_d875pbz/index.htm

The system bus runs at 800 MHz

shlw32M.lib is the SmartHeap library V6.0 from <http://www.microquill.com/smartheap/index.html>

An AGP video card is installed