



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

ION Computer Systems

SR2300WV2 (3.066GHz Xeon processor w. 512KB L2 cache)

SPECfp_rate2000 = 15.5

SPECfp_rate_base2000 = 15.5

SPEC license #: 2697 | Tested by: ION | Test date: Feb-2004 | Hardware Avail: Nov-2003 | Software Avail: Jan-2004

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	128	28.9	2	128	28.9
171.swim	2	448	16.1	2	448	16.1
172.mgrid	2	373	11.2	2	376	11.1
173.applu	2	358	13.6	2	358	13.6
177.mesa	2	101	32.0	2	101	32.0
178.galgel	2	306	22.0	2	305	22.0
179.art	2	882	6.84	2	879	6.86
183.quake	2	176	17.1	2	179	16.8
187.facerec	2	208	21.2	2	208	21.2
188.amp	2	510	10.0	2	510	10.0
189.lucas	2	336	13.8	2	336	13.8
191.fma3d	2	276	17.7	2	276	17.7
200.sixtrack	2	190	13.5	2	190	13.5
301.apsi	2	509	11.8	2	509	11.8

Hardware

CPU: Intel Xeon processor, 533MHz system bus
 CPU MHz: 3057
 FPU: Integrated
 CPU(s) enabled: 2 cores, 2 chips, 1 core/chip
 CPU(s) orderable: 1-2
 Parallel: No
 Primary Cache: 12K(I) micro-ops + 8KB(D) on chip
 Secondary Cache: 512KB(I+D) on chip
 L3 Cache: None
 Other Cache: None
 Memory: 2 GB (2x1GB 2-2-2 DIMMs)
 Disk Subsystem: 1x 80GB IDE
 Other Hardware: None

Software

Operating System: Red Hat Enterprise Linux ES release 3
 Compiler: Intel(R) Fortran Compiler for Linux 8.0 (Build 20031231Z)
 Intel(R) C++ Compiler for Linux 8.0 (Build 20031231Z)
 File System: ext2
 System State: Multi-user, 2.4.21 smp kernel

Notes/Tuning Information

HyperThreading disabled in BIOS

Baseline optimization flags:

C programs: PASS1= -xW -prof_gen PASS2= -xW -ipo -O3 -prof_use
 Fortran programs: PASS1= -xW -prof_gen PASS2= -xW -ipo -O3 -prof_use

FP Peak optimization flags:

168.wupwise: basepeak=yes
 171.swim: basepeak=yes
 172.mgrid: PASS1= -xN -prof_gen PASS2= -xN -ipo -O3 -prof_use
 173.applu: basepeak=yes
 177.mesa: basepeak=yes
 178.galgel: PASS1= -xN -prof_gen PASS2= -xN -ipo -O3 -prof_use
 179.art: PASS1= -xN -prof_gen PASS2= -xN -ipo -O3 -prof_use
 183.quake: PASS1= -xN -prof_gen PASS2= -xN -ipo -O3 -prof_use
 187.facerec: basepeak=yes
 188.amp: basepeak=yes



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

ION Computer Systems

SR2300WV2 (3.066GHz Xeon processor w. 512KB L2 cache)

SPECfp_rate2000 = 15.5

SPECfp_rate_base2000 = 15.5

SPEC license #: 2697 | Tested by: ION | Test date: Feb-2004 | Hardware Avail: Nov-2003 | Software Avail: Jan-2004

Notes/Tuning Information (Continued)

189.lucas: basepeak=yes
191.fma3d: basepeak=yes
200.sixtrack: basepeak=yes
301.apsi: basepeak=yes

FP Portability Flags:
178.galgel: -FI