



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

IBM Corporation
IBM eServer p5 595 (1900 MHz, 64 CPU)

SPECint_rate2000 = 1147
SPECint_rate_base2000 = 1063

SPEC license #: 11 | Tested by: IBM | Test date: Oct-2004 | Hardware Avail: Nov-2004 | Software Avail: Nov-2004

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	128	250	832	128	248	839
175.vpr	128	238	873	128	234	890
176.gcc	128	173	946	128	128	1279
181.mcf	128	193	1384	128	187	1431
186.crafty	128	168	884	128	125	1191
197.parser	128	245	1091	128	240	1111
252.eon	128	149	1296	128	131	1468
253.perlbnk	128	328	816	128	272	984
254.gap	128	148	1106	128	161	1017
255.vortex	128	190	1483	128	190	1482
256.bzip2	128	186	1195	128	184	1213
300.twolf	128	408	1092	128	410	1088

Hardware

CPU: POWER5
CPU MHz: 1900
FPU: Integrated
CPU(s) enabled: 64 cores, 32 chips, 2 cores/chip (SMT on)
CPU(s) orderable: 16,24,32,40,48,56,64
Parallel: No
Primary Cache: 64KBI+32KBD (on chip)/core
Secondary Cache: 1920KB unified (on chip)/chip
L3 Cache: 36MB unified (off-chip)/chip, 4 chips/MCM, 8 MCMs/SUT
Other Cache: None
Memory: 256 GB DDR1
Disk Subsystem: 3x36GB SCSI, 15K RPM
Other Hardware: None

Software

Operating System: AIX 5L V5.3
Compiler: XL C/C++ Enterprise Edition V7.0 for AIX
File System: AIX/JFS2
System State: Multi-user

Notes/Tuning Information

Tested by IBM

Portability Flags:

```
176.gcc: EXTRA_CFLAGS=-ma -DHOST_WORDS_BIG_ENDIAN
186.crafty: EXTRA_CFLAGS=-DAIX
252.eon: EXTRA_LDFLAGS=-I. -DNDEBUG
253.perlbnk: EXTRA_CFLAGS=-DSPEC_CPU2000_AIX
254.gap: EXTRA_CFLAGS=-DSYS_IS_BSD -DSYS_STRING_H -DSYS_HAS_TIME_PROTO -DSYS_HAS_MALLOC_PROTO
-DSYS_HAS_CALLOC_PROTO
300.twolf: EXTRA_CFLAGS=-DHAVE_SIGNED_CHAR
```

Base Optimization Flags:

```
C: -qpdf1/pdf2
-05 -blpdata -D_ILS_MACROS
C++: -qpdf1/pdf2
-05 -lhm -qalign=natural
```

Alternate Sources for Base & Peak:

Approved alternate-source file 252.eon.fmax_errno.src.alt.tar.gz was used with 252.eon for POSIX-compatibility.



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

IBM Corporation
IBM eServer p5 595 (1900 MHz, 64 CPU)

SPECint_rate2000 = 1147
SPECint_rate_base2000 = 1063

SPEC license #: 11 | Tested by: IBM | Test date: Oct-2004 | Hardware Avail: Nov-2004 | Software Avail: Nov-2004

Notes/Tuning Information (Continued)

Peak Optimization Flags:

```

164.gzip:      -qpdf1/pdf2
               -O5 -blpdata -D_ILS_MACROS -qfdpr
               fdpr -R3
175.vpr:      -qpdf1/pdf2
               -O5 -blpdata -qalign=natural -qhot=arraypad -Q
176.gcc:      -qpdf1/pdf2
               -O5
181.mcf:      -O5 -blpdata -qfdpr -D_ILS_MACROS
               fdpr -R3
186.crafty:   -qpdf1/pdf2
               -O4 -q64 -qfdpr -qarch=pwr3 -qtune=pwr3 -D_ILS_MACROS
               fdpr -R3
197.parser:   -qpdf1/pdf2
               -O5 -blpdata -D_ILS_MACROS -qfdpr
               fdpr -R3
252.eon:      -qpdf1/pdf2
               -O4 -qarch=pwr4 -qtune=pwr4 -qalign=natural -D_ILS_MACROS
253.perlbnk:  -qpdf1/pdf2
               -O5 -lhmu -qalign=natural
254.gap:      -qpdf1/pdf2
               -O5 -lhmu -qalign=natural -D_ILS_MACROS -blpdata
255.vortex:   -qpdf1/pdf2
               -O5 -lhmu -qalign=natural -D_ILS_MACROS -blpdata
256.bzip2:    -qpdf1/pdf2
               -O5 -blpdata -D_ILS_MACROS -qfdpr
               fdpr -R3
300.twolf:    -qpdf1/pdf2
               -O5 -blpdata -D_ILS_MACROS

```

SMT: Acronym for "Simultaneous Multi-Threading". A processor technology that allows the simultaneous execution of multiple thread contexts within a single processor core. (Enabled by default)

MCM: Acronym for "Multi-Chip Module" (four dual-core processor chips + four L3-cache chips)
This system contains 8 MCMs.

SUT: Acronym for "System Under Test"

C: IBM XL C for AIX invoked as xlc
C++: IBM XL C++ for AIX invoked as xlc

APAR IY60349 was applied to AIX to enable new hardware support.
ulimits set to unlimited.

Large page mode and memory affinity were set as follows:

```

vmo -r -o lpgg_regions=7000 -o lpgg_size=16777216 -o memory_affinity=1
chuser capabilities=CAP_BYPASS_RAC_VMM,CAP_PROPAGATE $USER
shutdown -r
export MEMORY_AFFINITY=MCM

```

The following config-file entry was used to assign each benchmark process to a core:

```
submit = schedule.128 \${SPECUSERNUM} $command
```

with the "schedule.128" function defined as follows:

```

#!/bin/ksh
index=$1
shift 1
# Strip off the residual arguments; the rest is the command.
if [[ $index -ge 64 ]]

```



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

IBM Corporation
IBM eServer p5 595 (1900 MHz, 64 CPU)

SPECint_rate2000 = 1147
SPECint_rate_base2000 = 1063

SPEC license #: 11 | Tested by: IBM | Test date: Oct-2004 | Hardware Avail: Nov-2004 | Software Avail: Nov-2004

Notes/Tuning Information (Continued)

```
then
    target=$((1+2*(index-64)))
else
    target=$((2*index))
fi
bindprocessor $$ $target      # Schedule this job to the corresponding core.
$*                          # Now run the command.
```

The "bindprocessor" AIX command binds a process to a CPU core.