



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

SuperMicro
X6DHT-G (3.6GHz, Intel Xeon)

SPECfp_rate2000 = 23.3
SPECfp_rate_base2000 = 22.4

SPEC license #01176 | Tested by: SuperMicro Inc., San Jose, CA | Test date: Nov-2004 | Hardware Avail: Nov-2004 | Software Avail: Dec-2003

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	110	33.9	2	88.8	41.8
171.swim	2	313	23.0	2	319	22.5
172.mgrid	2	209	20.0	2	207	20.2
173.applu	2	270	18.1	2	268	18.1
177.mesa	2	90.3	36.0	2	91.5	35.5
178.galgel	2	199	33.7	2	199	33.7
179.art	2	511	11.8	2	497	12.1
183.quake	2	133	22.7	2	103	29.3
187.facerec	2	142	31.0	2	143	30.7
188.amp	2	277	18.4	2	277	18.4
189.lucas	2	211	22.0	2	212	21.9
191.fma3d	2	219	22.3	2	219	22.3
200.sixtrack	2	188	13.6	2	178	14.4
301.apsi	2	257	23.4	2	254	23.7

Hardware

CPU: Intel Xeon (3.6GHz, 1MB L2, 800MHz bus)
CPU MHz: 3600
FPU: Integrated
CPU(s) enabled: 2 cores, 2 chips, 1 core/chip (HT Technology Enabled)
CPU(s) orderable: 1,2
Parallel: No
Primary Cache: 12K micro-ops I + 16KBD on chip
Secondary Cache: 1024KB(I+D) on chip
L3 Cache: N/A
Other Cache: N/A
Memory: 8x1GB DDR-333
Disk Subsystem: 1x250GB
Other Hardware:

Software

Operating System: Windows Server 2003 Standard (Build 3790)
Compiler: Intel C++ Compiler 8.0 Build 20031211Z
Intel Fortran Compiler 8.0 build 20040125Z
Microsoft Visual Studio .NET 7.0.9466 (for libraries)
MicroQuill Smartheap Library 7.0
File System: NTFS
System State: Default

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use (-QxP not used in PASS1 to enable cross-compilation)
Base tuning Base tuning: -QxP -fast -Qansi_alias +FDO
Portability flags:
 178.galgel: -FI /F32000000
Peak tuning:
168.wupwise: -QxP -fast -Qansi_alias +FDO ONESTEP=yes
171.swim: -QxP -fast -f77rtl +FDO ONESTEP=yes
172.mgrid: -QxP -fast -Qansi_alias +FDO ONESTEP=yes
173.applu: -QxP -fast -Qscalar_rep- -Qauto -f77rtl +FDO ONESTEP=yes
177.mesa: -QxP -fast +FDO ONESTEP=yes
178.galgel: -QxP -fast +FDO ONESTEP=yes
179.art: -fast -Oa -Qunroll4 -Zp4 ONESTEP=yes
183.quake: -QxP -fast -Oa -Qrcd +FDO shlw32M.lib ONESTEP=yes
187.facerec: -QaxN -fast -Qunroll1 -Qscalar_rep- -fpp +FDO ONESTEP=yes
188.amp: basepeak=1
189.lucas: -QaxN-fast
191.fma3d: basepeak=1
```



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

SuperMicro
X6DHT-G (3.6GHz, Intel Xeon)

SPECfp_rate2000 = 23.3

SPECfp_rate_base2000 = 22.4

SPEC license #01176 | Tested by: SuperMicro Inc., San Jose, CA | Test date: Nov-2004 | Hardware Avail: Nov-2004 | Software Avail: Dec-2003

Notes/Tuning Information (Continued)

200.sixtrack: -QxP -fast +FDO
301.apsi: -QxP -fast -f77rtl +FDO ONESTEP=yes