



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Acer Incorporated
Altos R510 (3.6 GHz Intel Xeon)

SPECint2000 = 1508
SPECint_base2000 = 1503

SPEC license #: 97 Tested by: Acer Incorporated Test date: Mar-2005 Hardware Avail: Mar-2005 Software Avail: Mar-2005

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
164.gzip	1400	117	1197	118	1183	
175.vpr	1400	156	898	151	927	
176.gcc	1100	60.5	1817	60.5	1817	
181.mcf	1800	168	1072	168	1072	
186.crafty	1000	75.0	1333	75.4	1326	
197.parser	1800	137	1315	137	1319	
252.eon	1300	57.4	2263	57.3	2271	
253.perlbnk	1800	88.8	2027	88.3	2039	
254.gap	1100	58.6	1877	58.6	1877	
255.vortex	1900	77.4	2455	77.4	2455	
256.bzip2	1500	148	1011	147	1017	
300.twolf	3000	177	1697	176	1707	

Hardware

CPU: Intel Xeon (3.6 GHz, 1MB L2, 800MHz system bus)
CPU MHz: 3600
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 1 core/chip(Hyper-Threading Technology disabled)
CPU(s) orderable: 1,2
Parallel: No
Primary Cache: 12KB(I) micro-ops + 16KB(D) on chip
Secondary Cache: 1024KB(I+D) on chip
L3 Cache: N/A
Other Cache: N/A
Memory: 6x512MB DDR-333 ECC SDRAM
Disk Subsystem: 1 x 80GB 7200RPM SATA HDD
Other Hardware:

Software

Operating System: Microsoft Windows Server 2003 Enterprise Edition (Build 3790)
Compiler: Intel C++ Compiler 8.1 Build 20041019Z
Microsoft Visual Studio .Net 2003(7.1.3091, for libraries)
SmartHeap Library Version 7.4 from <http://www.microquill.com/>
File System: NTFS
System State: Default

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning for C programs: -fast +FDO shlW32M.lib
Base tuning for C++ programs: -fast -Qcxx_features +FDO
Portability flags:
176.gcc: -Dalloca=_alloca /F10000000
186.crafty: -DNT_i386
252.eon: Approved stdcpp src.alt used
253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Peak tuning:
164.gzip: -fast -Qansi_alias -Oa +FDO
175.vpr: -fast -Qansi_alias +FDO
176.gcc: basepeak=yes
181.mcf: basepeak=yes
186.crafty: -fast -Qansi_alias -Oa +FDO
197.parser: -fast -Qansi_alias +FDO
252.eon: -fast +FDO
253.perlbnk: -fast -Qansi_alias +FDO shlW32M.lib
254.gap: basepeak=yes
255.vortex: basepeak=yes
```



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Acer Incorporated
Altos R510 (3.6 GHz Intel Xeon)

SPECint2000 =	1508
SPECint_base2000 =	1503

SPEC license #: 97	Tested by: Acer Incorporated	Test date: Mar-2005	Hardware Avail: Mar-2005	Software Avail: Mar-2005
--------------------	------------------------------	---------------------	--------------------------	--------------------------

Notes/Tuning Information (Continued)

256.bzip2: -fast -Oa -Qunroll1 +FDO
300.twolf: -fast -O3 +FDO shlw32M.lib
Enable hardware prefetching and adjacent cache line prefetch BIOS setting
Product description located as of Apr-2005:
<http://www.acer.com>