



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Supermicro
X6DVL-EG2 (3.6GHz, Intel Xeon)

SPECint2000 = 1515
SPECint_base2000 = 1507

SPEC license #01176 Tested by: Supermicro Test date: Apr-2005 Hardware Avail: Dec-2004 Software Avail: Aug-2004

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
164.gzip	1400	117	1198	118	1191	
175.vpr	1400	149	940	146	960	
176.gcc	1100	58.8	1870	58.8	1870	
181.mcf	1800	161	1115	161	1115	
186.crafty	1000	74.8	1337	75.1	1332	
197.parser	1800	135	1330	134	1339	
252.eon	1300	62.7	2072	60.5	2148	
253.perlbmk	1800	97.6	1845	97.5	1847	
254.gap	1100	59.6	1847	59.6	1847	
255.vortex	1900	72.9	2608	72.9	2608	
256.bzip2	1500	144	1042	144	1045	
300.twolf	3000	175	1711	174	1722	

Hardware

CPU: Intel Xeon processor (3.6 GHz, 800 MHz System bus)
CPU MHz: 3600
FPU: Integrated
CPU(s) enabled: 2 cores, 2 chips, 1 core/chip (Hyper-Threading Technology Enabled)
CPU(s) orderable: 1, 2
Parallel: No
Primary Cache: 12k micro-ops I + 16KBD on chip
Secondary Cache: 1024KB(I+D) on chip
L3 Cache: N/A
Other Cache: N/A
Memory: 4x1GB DDR2-400 REG ECC CL3
Disk Subsystem: 1x40GB IDE
Other Hardware:

Software

Operating System: Windows Server 2003 EE
Compiler: Intel C++ Compiler 8.1 Build 20040802Z
Microsoft Visual Studio .Net 2003(for libraries)
SmartHeap Library Version 6.0 from <http://www.microquill.com/>
File System: NTFS
System State: Default

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning for C programs: -fast +FDO shlw32M.lib
Base tuning for C++ programs: -fast -Qcxx_features +FDO
Portability flags:
176.gcc: -Dalloca=_alloca /F10000000
186.crafty: -DNT_i386
252.eon: Approved stdcpp src.alt used
253.perlbmk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Peak tuning:
164.gzip: -fast -Qansi_alias -Oa +FDO
175.vpr: -fast -Qansi_alias +FDO
176.gcc: basepeak=yes
181.mcf: basepeak=yes
186.crafty: -fast -Qansi_alias -Oa +FDO
197.parser: -fast -Qansi_alias +FDO
252.eon: -fast +FDO
253.perlbmk: -fast -Qansi_alias +FDO shlw32M.lib
254.gap: basepeak=yes
255.vortex: basepeak=yes
```



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Supermicro
X6DVL-EG2 (3.6GHz, Intel Xeon)

SPECint2000 =	1515
SPECint_base2000 =	1507

SPEC license #01176 | Tested by: Supermicro | Test date: Apr-2005 | Hardware Avail: Dec-2004 | Software Avail: Aug-2004

Notes/Tuning Information (Continued)

256.bzip2: -fast -Oa -Qunroll11 +FDO
300.twolf: -fast -O3 +FDO shlw32M.lib
Tested system can be used with a 420W (minimum) ATX power supply [8-pin (+12V) and 24-pin are required]
The system bus runs at 800 MHz