



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Advanced Micro Devices
TYAN S2895 Thunder K8WE, AMD Opteron (TM) 265

SPECfp_rate2000 = 26.5
SPECfp_rate_base2000 = 25.5

SPEC license #: 49 Tested by: AMD, Austin, TX Test date: Apr-2005 Hardware Avail: May-2005 Software Avail: Mar-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	84.3	44.1	2	84.3	44.1
171.swim	2	288	24.9	2	250	28.7
172.mgrid	2	187	22.3	2	187	22.3
173.applu	2	222	22.0	2	202	24.1
177.mesa	2	104	31.3	2	98.1	33.1
178.galgel	2	158	42.6	2	150	44.8
179.art	2	258	23.3	2	246	24.5
183.quake	2	123	24.5	2	123	24.5
187.facerec	2	146	30.3	2	145	30.4
188.amp	2	236	21.6	2	223	22.9
189.lucas	2	176	26.4	2	169	27.5
191.fma3d	2	216	22.6	2	206	23.7
200.sixtrack	2	198	12.9	2	198	12.9
301.apsi	2	252	23.9	2	252	23.9

Hardware

CPU: AMD Opteron (TM) 265
CPU MHz: 1800
FPU: Integrated
CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip
CPU(s) orderable: 1-2
Parallel: No
Primary Cache: 64KBI + 64KBD/core
Secondary Cache: 1024KB(I+D)/core
L3 Cache: N/A
Other Cache: N/A
Memory: 4x512 MB PC3200 CL2.5 ECC Reg
Disk Subsystem: SATA, Western Digital WD740GD, 10000 RPM
Other Hardware: None

Software

Operating System: Microsoft Windows Server 2003 Enterprise Edition SP1
Compiler: Intel C++ 8.0 build 20040714Z, Intel Fortran 8.1 build 20041019Z, PGI Fortran compiler 5.2-4 for Windows XP, AMD Core Math library Version 2.1 (ACML), Microsoft Visual Studio .NET 7.0.9466 (libraries), MicroQuill Smartheap Library 7.0
File System: NTFS
System State: Default

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
+ACML is linking with AMD Core Math Library V2.1
ONESTEP is set for all peak runs.
ifort is the Intel Fortran compiler, icl is the Intel C++ compiler and
pgf90 is the PGI Fortran compiler.
The Intel C++ 8.0 and the Intel Fortran 8.1 compilers are setup in the following order:
  "c:\program files\intel\fortran\compiler80\ia32\bin\ifortvars.bat"
  "c:\program files\intel\cpp\compiler80\ia32\bin\iclvars.bat"
To make sure that the correct libraries are selected, the following link option is
added for the peak runs where Intel Fortran 8.1 compiler is used:
  LDOPT = -Fe$@ -link -LIBPATH:"c:\program files\intel\fortran\compiler80\ia32\lib"
(denoted by +LIBPATH:INTEL8.1 in the optimization flags listed below)
Portability:
  178.galgel: -Mfixed
Baseline: C      : icl  -fast -arch:SSE2 -QaxW +FDO
Baseline: Fortran: pgf90 -fastsse -Mipa=fast,inlined
```



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Advanced Micro Devices
TYAN S2895 Thunder K8WE, AMD Opteron (TM) 265

SPECfp_rate2000 = 26.5
SPECfp_rate_base2000 = 25.5

SPEC license #: 49 | Tested by: AMD, Austin, TX | Test date: Apr-2005 | Hardware Avail: May-2005 | Software Avail: Mar-2005

Notes/Tuning Information (Continued)

```

Peak tuning:
168.wupwise:      pgf90 basepeak=yes
171.swim:         ifort -Qipo -O3 -QaxN -QxW +FDO -Qunroll10 +LIBPATH:INTEL8.1
172.mgrid:        pgf90 basepeak=yes
173.applu:         ifort -Qipo -O3 -QaxN -QxW +FDO -auto +LIBPATH:INTEL8.1
177.mesa:          icl -Qipo -arch:SSE2 +FDO -Qunroll11 -Qansi_alias
                  -Qoption,f,-ip_ninl_max_stats=1500,-ip_ninl_max_total_stats=4500
179.art:           icl -Qipo -Zp4 +FDO
183.equake:        icl basepeak=yes
178.galgel:        pgf90 -fastsse -Mipa=fast,safe RM_SOURCES=lapak.f90 -Munix +ACML
187.facerec:       ifort -Qipo -QxW +FDO -Qunroll13 +LIBPATH:INTEL8.1
                  -Qoption,f,-ip_ninl_max_stats=2500,-ip_ninl_max_total_stats=7000
188.ammp:          icl -Oa -arch:SSE2 -Zp4 -Qansi_alias
189.lucas:         ifort -Qipo -QxW -Qunroll11 +LIBPATH:INTEL8.1
191.fma3d:         ifort -Qipo -QaxN -QxW +FDO -Qansi-alias- +LIBPATH:INTEL8.1
200.sixtrack:      pgf90 basepeak=yes
301.apsi:          pgf90 basepeak=yes

```

Bios Rev 1.00.2895

The start /b /wait /affinity command is used to bind CPU(s) to processes.
The tested system can be assembled using the SSI EEB v3.5 footprint, an Antec True 550 EPS12V 550W power supply, and a PCI-e graphics card.