



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant BL45p (AMD Opteron (TM) 880)

SPECfp_rate2000 = 74.6
SPECfp_rate_base2000 = 68.7

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Aug-2005 Hardware Avail: Sep-2005 Software Avail: Apr-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	4	71.5	104	4	62.7	118
171.swim	4	239	60.2	4	237	60.6
172.mgrid	4	155	53.8	4	153	54.7
173.applu	4	131	74.3	4	119	81.6
177.mesa	4	74.4	87.3	4	70.3	92.4
178.galgel	4	120	112	4	113	119
179.art	4	136	88.7	4	92.5	130
183.equake	4	117	51.7	4	105	57.3
187.facerec	4	93.5	94.3	4	91.2	96.7
188.amp	4	162	63.1	4	150	68.2
189.lucas	4	156	59.6	4	155	59.8
191.fma3d	4	165	59.1	4	161	60.7
200.sixtrack	4	157	32.5	4	133	38.5
301.apsi	4	178	67.8	4	176	68.6

Hardware

CPU: AMD Opteron (TM) 880
 CPU MHz: 2400
 FPU: Integrated
 CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip
 CPU(s) orderable: 1,2,4
 Parallel: No
 Primary Cache: 64KBI + 64KBD (on chip) per core
 Secondary Cache: 1024KB(I+D) (on chip) per core
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 8x2048MB PC3200 CL3.0
 Disk Subsystem: 1x36.4GB 15K Ultra320 SCSI
 Other Hardware:

Software

Operating System: SuSE Linux Enterprise Server 9 (x86_64) SP 1
 SuSE kernel 2.6.5-7.139-smp
 Compiler: PathScale EKOPATH(TM) Compiler Suite, Release 2.1
 AMD Core Math Library 2.5.1
 File System: Linux/ext2
 System State: Multi-user run level 3

Notes/Tuning Information

```
+FDO: PASS1= -fb_create fbdata PASS2= -fb_opt fbdata
+ACML: Linked with AMD Core Math Library
Base tuning for C programs: -Ofast -WOPT:mem_opnds=on +FDO
Base tuning for FORTRAN programs: -Ofast -LNO:fusion=2 -OPT:fast_complex=on
Portability flags:
  178.galgel: -fixedform
Peak tuning:
  168.wupwise: -Ofast -LNO:prefetch Ahead=5:prefetch=3
              -OPT:unroll_times_max=8:unroll_size=128:IEEE NaN_Inf=off:ro=3
              -IPA:linear=on:plimit=50000:callee_limit=5000 -INLINE:aggressive=on
  171.swim: -Ofast -CG:local_fwd_sched=on -LNO:fusion=2 -m3dnow
  172.mgrid: -Ofast -CG:gcm=off -OPT:IEEE_a=3:unroll_size=200
              -LNO:fusion=2:fission=1:blocking=off:prefetch Ahead=2 -WOPT:mem_opnds=on:aggstr=0
  173.applu: -Ofast -CG:local_fwd_sched=on -OPT:ro=3 -TENV:X=3
              -LNO:fusion=2:fission=2:full_unroll_size=10000
  177.mesa: -O2 -ipa -OPT:Ofast -fno-math-errno -CG:local_fwd_sched=on
              -WOPT:mem_opnds=on +FDO
```



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant BL45p (AMD Opteron (TM) 880)

SPECfp_rate2000 = 74.6
SPECfp_rate_base2000 = 68.7

SPEC license #: 3 | Tested by: Hewlett-Packard Company | Test date: Aug-2005 | Hardware Avail: Sep-2005 | Software Avail: Apr-2005

Notes/Tuning Information (Continued)

```

178.galgel: -Ofast -OPT:fast_complex=on RM_SOURCES=lapak.f90 +ACML
179.art: -O3 -OPT:ro=2:div_split=on:alias=typed -fno-math-errno -m32 +FDO
183.quake: -Ofast -CG:load_exe=2 -WOPT:mem_opnds=on -m32 +FDO
187.facerec: -Ofast -OPT:treeheight=on:IEEE_NaN_Inf=off:ro=3 -CG:load_exe=0 -LNO:fusion=2
            -IPA:plimit=1500 +FDO
188.ammp: -O3 -OPT:alias=disjoint:unroll_times_max=8:Ofast:ro=3
            -fno-math-errno -TENV:X=4 +FDO
189.lucas: -Ofast -OPT:ro=3:fast_nint=off:unroll_size=256 -WOPT:mem_opnds=on +FDO
191.fma3d: -O2 -ipa -CG:load_exe=1 -OPT:Ofast:IEEE_arith=3:ro=3
            -WOPT:mem_opnds=on:retype_expr=on -IPA:pu_reorder=1 +FDO
200.sixtrack: -O3 -OPT:Ofast:Olimit=6000:early_intrinsics=on -fno-math-errno
            -CG:load_exe=1 +FDO
301.apsi: -Ofast -CG:load_exe=0 -LNO:prefetch=0:simd=2

```

BIOS Configuration Notes
Node Interleaving is Disabled

Other Configuration Notes
Taskset utility used to bind process to CPU(s)