



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY Econel 100, Intel Pentium 4 processor 630, 3GHz

SPECint2000 = 1485

SPECint_base2000 = 1485

SPEC license #: 22 Tested by: Fujitsu Siemens Computers Test date: Oct-2005 Hardware Avail: Oct-2005 Software Avail: Sep-2005

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
164.gzip	1400	139	1004	139	1004	
175.vpr	1400	135	1038	135	1038	
176.gcc	1100	61.8	1779	61.8	1779	
181.mcf	1800	95.7	1881	95.7	1881	
186.crafty	1000	90.2	1109	90.2	1109	
197.parser	1800	143	1261	143	1261	
252.eon	1300	73.3	1774	73.3	1774	
253.perlbnk	1800	100	1792	100	1792	
254.gap	1100	66.7	1650	66.7	1650	
255.vortex	1900	74.5	2552	74.5	2552	
256.bzip2	1500	130	1151	130	1151	
300.twolf	3000	197	1525	197	1525	

Hardware

CPU: Intel Pentium 4 processor 630, 3GHz, 800MHz system bus
CPU MHz: 3000
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 1 core/chip (Hyper-Threading Technology disabled)
CPU(s) orderable: 1
Parallel: No
Primary Cache: 12k micro-ops I + 16KBD on chip
Secondary Cache: 2 MB(I+D) on chip
L3 Cache: N/A
Other Cache: N/A
Memory: 4x2 GB DDR2-SDRAM PC2-4200
Disk Subsystem: Seagate ST3160023AS (SATA, 7.2krpm)
Other Hardware:

Software

Operating System: Windows Server 2003 Enterprise Edition + SP1
Compiler: Intel C++ Compiler 9.0
Build 20050722Z (for 32-bit applications),
Microsoft Visual Studio .Net 2003
7.1.3088 (for libraries),
SmartHeap Library Version 7.4
from <http://www.microquill.com>
File System: NTFS
System State: Default

Notes/Tuning Information

GENERAL

+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

Portability flags

176.gcc: -Dalloca=_alloca /F10000000
186.crafty: -DNT_i386
252.eon: Approved srcalt stdcpp is used
253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

Base tuning flags

for C programs: -fast +FDO shlw32m.lib
for C++ programs: -fast -Qcxx_features +FDO shlw32m.lib

Peak tuning flags

same as baseline (basepeak=yes set globally)

New 32-bit Windows tools used, approved in May-2005

The system bus runs at 800 MHz



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY Econel 100, Intel Pentium 4 processor 630, 3GHz

SPECint2000 = 1485

SPECint_base2000 = 1485

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Oct-2005 | Hardware Avail: Oct-2005 | Software Avail: Sep-2005

Notes/Tuning Information (Continued)

This result was measured with 32-bit binaries using the 32-bit version of the operating system.

For information about Fujitsu Siemens Computers in your country please see:
<http://www.fujitsu-siemens.com/countries>