



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers
PRIMERGY BX630, AMD Opteron (TM) 865

SPECint_rate2000 = 109
SPECint_rate_base2000 = 99.5

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Jan-2006 | Hardware Avail: Oct-2005 | Software Avail: Mar-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	8	146	89.2	8	146	89.2
175.vpr	8	158	82.1	8	153	84.8
176.gcc	8	88.5	115	8	88.4	116
181.mcf	8	302	55.4	8	247	67.6
186.crafty	8	85.8	108	8	78.2	119
197.parser	8	170	98.5	8	170	98.5
252.eon	8	93.5	129	8	67.4	179
253.perlbnk	8	158	105	8	144	116
254.gap	8	96.1	106	8	96.1	106
255.vortex	8	115	154	8	103	171
256.bzip2	8	172	81.2	8	168	83.1
300.twolf	8	265	105	8	209	133

Hardware

CPU: AMD Opteron (TM) 865 processor (1.80 GHz)
 CPU MHz: 1800
 FPU: Integrated
 CPU(s) enabled: 8 cores, 4 chips, 2 cores/chip
 CPU(s) orderable: 1,2,4
 Parallel: No
 Primary Cache: 64KBI + 64KBD on chip, per core
 Secondary Cache: 1024KB (I+D) on chip, per core
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 16x1024MB DDR-RAM PC3200R
 Disk Subsystem: Western Digital WD2500 (SATA, 7.2krpm)
 Other Hardware: None

Software

Operating System: Windows Server 2003 Enterprise Edition + SP1
 Compiler: Intel C++ 8.0
 Build 20040318Z (for 32-bit applications),
 Microsoft Visual Studio .Net 2003
 7.1.3088 (for libraries),
 SmartHeap Library Version 8.0
 from <http://www.microquill.com>
 File System: NTFS
 System State: Default

Notes/Tuning Information

GENERAL

+FDO: PASS1= -Qprof_gen PASS2= -Qprof_use

Portability flags

176.gcc: -Dalloca=_alloca /F10000000
 186.crafty: -DNT_i386
 253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
 254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

Base tuning flags

for C programs: -fast -arch:SSE2 -Oi- +FDO
 for C++ programs: -fast -GX -GR +FDO

Peak tuning flags

164.gzip: basepeak=yes
 175.vpr: -fast -arch:SSE2 -Qoption,c,-ip_ninl_max_stats=2000,
 -ip_ninl_max_total_stats=4500 +FDO ONESTEP=yes
 176.gcc: -fast -arch:SSE2 -Oi- -Qunroll3 +FDO shlw32M.lib
 181.mcf: -fast -QaxN +FDO shlw32M.lib
 186.crafty: -fast -arch:SSE2 +FDO ONESTEP=yes shlw32M.lib



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers
PRIMERGY BX630, AMD Opteron (TM) 865

SPECint_rate2000 = 109
SPECint_rate_base2000 = 99.5

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Jan-2006 | Hardware Avail: Oct-2005 | Software Avail: Mar-2005

Notes/Tuning Information (Continued)

```
197.parser: basepeak=yes
252.eon: -fast -arch:SSE2 -Qansi_alias -Qoption,c,-ip_ninl_max_stats=2000,
        -ip_ninl_max_total_stats=4500 +FDO ONESTEP=yes shlw32M.lib
253.perlbnk: -fast -arch:SSE2 -Oi- +FDO ONESTEP=yes shlw32M.lib
254.gap: basepeak=yes
255.vortex: -fast -arch:SSE -Oi- -Qoption,c,-ip_ninl_max_stats=2000,
           -ip_ninl_max_total_stats=4500 +FDO shlw32M.lib
256.bzip2: -fast -Qunroll2 shlw32M.lib
300.twolf: -fast -arch:SSE2 -Qansi_alias +FDO ONESTEP=yes shlw32M.lib
```

'start /b /wait /affinity' command is used to bind CPU(s) to processes

```
boot options: /NoExecute=alwaysoff
              /USEPMTIMER
BIOS settings: Memory Timing: 1T
              DRAM Bank Interleave=AUTO
```

This result was measured with 32-bit binaries using the 32-bit version of the operating system.

For information about Fujitsu Siemens Computers in your country please see:
<http://www.fujitsu-siemens.com/countries>