



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers
PRIMERGY TX150 S4, Intel Pentium D processor 830

SPECint_rate2000 = 31.1
SPECint_rate_base2000 = 31.1

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Jan-2006 | Hardware Avail: Jan-2006 | Software Avail: Oct-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.zip	2	142	22.8	2	142	22.8
175.vpr	2	163	19.9	2	163	19.9
176.gcc	2	66.2	38.6	2	66.2	38.6
181.mcf	2	176	23.8	2	176	23.8
186.crafy	2	89.0	26.1	2	89.0	26.1
197.parser	2	153	27.3	2	153	27.3
252.eon	2	68.3	44.2	2	68.3	44.2
253.perlbnk	2	100	41.7	2	100	41.7
254.gap	2	71.3	35.8	2	71.3	35.8
255.vortex	2	81.6	54.0	2	81.6	54.0
256.bzip2	2	155	22.4	2	155	22.4
300.twolf	2	204	34.1	2	204	34.1

Hardware

CPU: Intel Pentium D processor 830 3.0GHz, 2x1MB L2, 800MHz system bus
CPU MHz: 3000
FPU: Integrated
CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip
CPU(s) orderable: 1
Parallel: No
Primary Cache: 12k micro-ops I + 16KBD on chip, per core
Secondary Cache: 1024KB(I+D) on chip, per core
L3 Cache: N/A
Other Cache: N/A
Memory: 4x1024 MB DDRII-RAM PC2-4300
Disk Subsystem: Fujitsu MAS3735NC (SCSI, 15krpm)
Other Hardware: none

Software

Operating System: Windows Server 2003 Enterprise Edition + SP1
Compiler: Intel C++ Compiler 9.0
Build 20051020Z (for 32-bit applications),
Microsoft Visual Studio .Net 2003
7.1.3088 (for libraries),
SmartHeap Library Version 8.0
from <http://www.microquill.com>
File System: NTFS
System State: Default

Notes/Tuning Information

GENERAL

+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

Portability flags

176.gcc: -Dalloca=_alloca /F10000000
186.crafy: -DNT_i386
253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

Base tuning flags

for C programs: -fast +FDO shlw32M.lib
for C++ programs: -fast -Qcxx_features +FDO shlw32M.lib

Peak tuning flags

same as baseline (basepeak=true set globally)

The system bus runs at 800 MHz

This result was measured with 32-bit binaries using the 32-bit version of the operating system.



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers
PRIMERGY TX150 S4, Intel Pentium D processor 830

SPECint_rate2000 = 31.1
SPECint_rate_base2000 = 31.1

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Jan-2006 | Hardware Avail: Jan-2006 | Software Avail: Oct-2005

Notes/Tuning Information (Continued)

For information about Fujitsu Siemens Computers in your country please see:
<http://www.fujitsu-siemens.com/countries>