



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Limited
PRIMEPOWER1500 (2160MHz)

SPECfp_rate2000 = 314
SPECfp_rate_base2000 = 291

SPEC license #: 19 | Tested by: Fujitsu Limited | Test date: Feb-2006 | Hardware Avail: Jun-2005 | Software Avail: Nov-2005

8000	6000	4000	2000	Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
				168.wupwise	16	136	219	16	128	232
				171.swim	16	127	452	16	89.2	645
				172.mgrid	16	267	125	16	262	127
				173.applu	16	163	239	16	147	265
				177.mesa	16	126	206	16	104	250
				178.galgel	16	60.9	883	16	52.6	1023
				179.art	16	10.3	4697	16	10.3	4698
				183.quake	16	101	239	16	99.9	242
				187.facerec	16	103	343	16	102	345
				188.amp	16	173	236	16	147	278
				189.lucas	16	282	132	16	281	132
				191.fma3d	16	287	136	16	284	137
				200.sixtrack	16	138	148	16	138	148
				301.apsi	16	200	241	16	200	241

Hardware

CPU: SPARC64 V
CPU MHz: 2160
FPU: Integrated
CPU(s) enabled: 16 cores, 16 chips, 1 core/chip
CPU(s) orderable: 1 to 32 (increments of 1)
Parallel: None
Primary Cache: 128KBI + 128KBD on chip
Secondary Cache: 4MB(I+D) on chip
L3 Cache: None
Other Cache: None
Memory: 64GB (512MB x 128)
Disk Subsystem: 1 x 36.4GB SCSI (10000rpm)
Other Hardware: None

Software

Operating System: Solaris 10
Compiler: Studio 11

File System: ufs
System State: multi user

Notes/Tuning Information

```
FDO: (for Sun Studio 11)
fdo_pre0=rm -rf ./feedback.profile ./SunWS_cache
PASS1=-xprofile=collect:./feedback
PASS2=-xprofile=use:./feedback
```

```
Floating point base flags:
(using Fortran compiler of Sun Studio 11)
-fast -xtarget=ultra3cu -xipo=2 ONESTEP=yes FDO
(using C compiler of Sun Studio 11)
-fast -xtarget=ultra3 -xipo=2 ONESTEP=yes FDO
```

```
Floating point peak flags:
(using Fortran compiler of Sun Studio 11)
168.wupwise: -fast -xarch=v8plusb -xchip=ultra3cu -xcache=128/64/2:4096/64/4
-xipo=1 -Qoption iropt -Ainline:inc=800:cp=1 ONESTEP=yes FDO
171.swim: -fast -xarch=v8plusb -xchip=ultra3cu -xcache=128/64/2:4096/64/4
```



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Limited
PRIMEPOWER1500 (2160MHz)

SPECfp_rate2000 = 314
SPECfp_rate_base2000 = 291

SPEC license #: 19 | Tested by: Fujitsu Limited | Test date: Feb-2006 | Hardware Avail: Jun-2005 | Software Avail: Nov-2005

Notes/Tuning Information (Continued)

```

172.mgrid: -xpad=common:1700 -Qoption iropt -Ainline:cs=700,Atile:skewp:b10
           -fast -xarch=v8plusb -xchip=ultra3cu -xcache=128/64/2:4096/64/4
           -stackvar -xipo=2 -xpad=common:800 -xprefetch=latx:1.6
           ONESTEP=yes FDO
173.applu: -fast -xarch=v8plusb -xchip=ultra3cu -xcache=128/64/2:4096/64/4
           -stackvar -xipo=2 -Qoption cg -Qlp=1-av=192-t=4-fa=1-fl=0
           -Qoption iropt -Aujam:inner=g ONESTEP=yes FDO
178.galgel: -fast -xarch=v8plusb -xchip=ultra3cu -xcache=128/64/2:4096/64/4
           -xipo=2 -Qoption iropt -Addint:sf=9 -xlic_lib=sunperf
           RM_SOURCES=lapak.f90 ONESTEP=yes FDO
187.facerec: -fast -xarch=v8plusb -xchip=ultra3cu -xcache=128/64/2:4096/64/4
           -xprefetch=latx:1.6 ONESTEP=yes FDO
189.lucas: -fast -xarch=v8plusb -xchip=ultra3cu -xcache=128/64/2:4096/64/4
           -stackvar -xipo=2 ONESTEP=yes FDO
191.fma3d: -fast -xarch=v8plusb -xchip=ultra3cu -xcache=128/64/2:4096/64/4
           -xipo=2 ONESTEP=yes FDO
200.sixtrack: basepeak=yes
301.apsi: basepeak=yes

```

(using C compiler of Sun Studio 11)

```

177.mesa: -fast -xarch=v8plusb -xchip=ultra3cu -xcache=128/64/2:4096/64/4
          -xchip=ultra2 -xalias_level=strong -xipo=2 -xrestrict
          ONESTEP=yes FDO
179.art: -fast -xarch=v8plusb -xchip=ultra3cu -xcache=128/64/2:4096/64/4
          -xipo=2 ONESTEP=yes FDO
183.quake: -fast -xarch=v8plusb -xchip=ultra3cu -xcache=128/64/2:4096/64/4
            -xalias_level=strong -W2,-whole -Wc,-Qms_pipe-pref,
            -Qlp=1-av=512-t=6-fa=1-fl=1 ONESTEP=yes FDO
188.ammp: -fast -xalias_level=std -xipo=2 ONESTEP=yes FDO

```

Portability:

178.galgel: -fixed

System Tunables:

```

(for /etc/system)
  set consistent_coloring=1
  set tune_t_fsflushr=86400
  set autoup=86400
  set memscrub_period_sec=172800

```

Shell Environments:

```

Stack size set to unlimited via "ulimit -s unlimited"
MPSSHEAP=4M
MPSSSTACK=4M
LD_PRELOAD=mpss.so.1

```

Extended Interleave Mode enabled.

4 CPUs each on 4 system boards. Unused CPUs have physically removed.

Sun Studio 11, posted at URL <http://www.sun.com/software/products/studio/index.xml> was used for this submission.