



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

CAIRA TD300D

SPECfp_rate2000 = 28.7

SPECfp_rate_base2000 = 28.8

SPEC license #: 3195 | Tested by: CAIRA | Test date: Feb-2006 | Hardware Avail: Feb-2006 | Software Avail: Feb-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	4	170	43.7	4	170	43.7
171.swim	4	625	23.0	4	626	23.0
172.mgrid	4	437	19.1	4	439	19.0
173.applu	4	460	21.2	4	460	21.2
177.mesa	4	148	44.0	4	148	44.0
178.galgel	4	288	46.8	4	282	47.7
179.art	4	271	44.5	4	271	44.5
183.quake	4	301	20.0	4	320	18.8
187.facerec	4	267	33.0	4	267	33.0
188.amp	4	354	28.8	4	354	28.8
189.lucas	4	418	22.2	4	419	22.2
191.fma3d	4	393	24.8	4	393	24.8
200.sixtrack	4	249	20.5	4	249	20.5
301.apsi	4	350	34.5	4	350	34.5

Hardware

CPU: Intel Xeon (3.6 GHz, 2MB L2, 800MHz system bus)
CPU MHz: 3600
FPU: Integrated
CPU(s) enabled: 2 cores, 2 chips, 1 core/chip(Hyper-Threading Technology Enabled)
CPU(s) orderable: 1,2
Parallel: No
Primary Cache: 12KB(I) micro-ops + 16KB(D) on chip
Secondary Cache: 2048KB(I+D) on chip
L3 Cache: N/A
Other Cache: N/A
Memory: 4 x 1 GB ECC DDR2-400 SDRAM
Disk Subsystem: 1*73 GB U320 SCSI 15K RPM Hot Pluggable
Other Hardware:

Software

Operating System: Windows Server 2003 Enterprise x64 Edition (Service Pack 1)
Compiler: Intel(R) Fortran compiler version 9.0
Intel(R) C++ compiler version 9.0
Microsoft Visual Studio.Net 2003
File System: NTFS
System State: Default

Notes/Tuning Information

```
+FDO:      PASS1= -Qprof_gen  PASS2=-Qprof_use
Base tuning :      -fast +FDO
178.galgel: -FI /F10000000
168.wupwise: -fast -Qansi_alias +FDO
171.swim:    -fast -Qansi_alias +FDO
172.mgrid:  -fast -Qansi_alias +FDO
173.applu:  -fast -Qscalar_rep- -Qauto  +FDO
177.mesa:   basepeak=yes
178.galgel: -fast -Qansi_alias +FDO
179.art:    basepeak=yes
183.quake:  -QxP -Oa -Qrcd +FDO
187.facerec: -fast -Qunroll11 -Qscalar_rep- +FDO
188.amp:    -fast -Oa +FDO
189.lucas:  -fast -Qprefetch- +FDO
191.fma3d:  basepeak=yes
200.sixtrack: -Qipo -QxP +FDO
301.apsi:   -fast +FDO
```