



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Bull
Express5800-140He (2.66 GHz Xeon MP)

SPECfp2000 = 1148
SPECfp_base2000 = 1126

SPEC license #: 20 Tested by: Bull Test date: Mar-2006 Hardware Avail: Mar-2006 Software Avail: Mar-2006

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio
168.wupwise	1600	88.1	1816	87.8	1822
171.swim	3100	183	1694	183	1694
172.mgrid	1800	166	1087	166	1086
173.applu	2100	186	1128	191	1097
177.mesa	1400	126	1110	126	1109
178.galgel	2900	183	1588	183	1588
179.art	2600	141	1851	133	1951
183.quake	1300	97.7	1330	77.2	1684
187.facerec	1900	183	1038	183	1038
188.amp	2200	353	623	353	623
189.lucas	2000	178	1124	178	1124
191.fma3d	2100	205	1025	205	1025
200.sixtrack	1100	212	518	212	518
301.apsi	2600	310	838	310	838

Hardware

CPU: Intel Xeon Processor MP 7020 (2.66GHz, 2x1MB L2, 667MHz bus)
CPU MHz: 2660
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 2 cores/chip (Hyper-Threading Technology disabled)
CPU(s) orderable: 1 to 4
Parallel: No
Primary Cache: 12KB(I) micro-ops + 16KB(D) (on chip) per core
Secondary Cache: 1024KB(I+D) (on chip) per core
L3 Cache: N/A
Other Cache: N/A
Memory: 2GB (512MB DIMMx4, DDR2-400 SDRAM, CL3)
Disk Subsystem: 2x36GB SCSI U320 15000 rpm
Other Hardware:

Software

Operating System: Windows Server 2003 Enterprise Edition (32 bits) Service Pack 1
Compiler: Intel(R) C++ Compiler for 32-bit app., Version 9.0, - Build 20060222Z Package ID: W_CC_C_9.0.030
Intel(R) Fortran Compiler for 32-bit app., Version 9.0, - Build 20060222Z Package ID: W_FC_C_9.0.030
Microsoft Visual Studio .NET 2003 (for libraries)
MicroQuill SmartHeap Library 8.0 (shlW32M.lib)
File System: NTFS
System State: Default

Notes/Tuning Information

Portability flags:

178.galgel: -FI /F32000000

Feedback optimization:

+FDO: PASS1= -Qprof_gen PASS2= -Qprof_use

Baseline Tuning Flags:

for C programs:
-fast -Qansi_alias +FDO
for Fortran programs:
-fast -Qansi_alias +FDO

Peak Tuning Flags:

168.wupwise: -fast -Qansi_alias +FDO
171.swim: -fast +FDO ONESTEP=yes
172.mgrid: -fast +FDO
173.applu: -fast -Qscalar_rep- -Qauto +FDO ONESTEP=yes



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Bull
Express5800-140He (2.66 GHz Xeon MP)

SPECfp2000 = 1148
SPECfp_base2000 = 1126

SPEC license #: 20 | Tested by: Bull | Test date: Mar-2006 | Hardware Avail: Mar-2006 | Software Avail: Mar-2006

Notes/Tuning Information (Continued)

177.mesa:	-fast	+FDO	ONESTEP=yes
178.galgel:	-fast	+FDO	
179.art:	-fast	+FDO	shlw32M.lib
183.earthquake:	-fast	+FDO	ONESTEP=yes shlw32M.lib
187.facerec:	-fast	+FDO	ONESTEP=yes
188.ammp:	-fast	+FDO	
189.lucas:	-fast	+FDO	
191.fma3d:	-fast	+FDO	
200.sixtrack:	-fast	+FDO	
301.apsi:	-fast	+FDO	

Other Configuration Notes

/NUMPROC=1 flag was added to boot.ini to invoke uniprocessor environment

Express5800-140He and 140Rd4 are electronically equivalent
Measured on Express5800-140Rd4

For information about Bull please see:
<http://www.bull.com>