



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant DL580 G4 (3.0GHz, Intel Xeon processor 7041)

SPECint_rate2000 = 16.5
SPECint_rate_base2000 = 16.4

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: May-2006 Hardware Avail: May-2006 Software Avail: May-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	1	139	11.7	1	139	11.7
175.vpr	1	150	10.8	1	146	11.1
176.gcc	1	63.2	20.2	1	63.2	20.2
181.mcf	1	124	16.9	1	124	16.9
186.crafty	1	89.0	13.0	1	89.0	13.0
197.parser	1	149	14.0	1	148	14.1
252.eon	1	63.7	23.7	1	63.6	23.7
253.perlbnk	1	104	20.1	1	102	20.4
254.gap	1	70.9	18.0	1	69.8	18.3
255.vortex	1	80.7	27.3	1	80.9	27.3
256.bzip2	1	148	11.7	1	148	11.7
300.twolf	1	195	17.8	1	195	17.8

Hardware

CPU: Intel Xeon processor 7041 (3.0GHz, 2x2MB L2, 800MHz bus)
CPU MHz: 3000
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 2 cores/chip (Hyper-Threading Technology disabled)
CPU(s) orderable: 1,2,4
Parallel: No
Primary Cache: 12K micro-ops I + 16KBD (on chip) per core
Secondary Cache: 2048KB(I+D) (on chip) per core
L3 Cache: N/A
Other Cache: N/A
Memory: 8x2048MB PC2-3200 dual-rank
Disk Subsystem: 1x36GB SAS
Other Hardware:

Software

Operating System: Windows Server 2003 Enterprise SP1
Compiler: Intel C++ Compiler for 32-bit applications, (Version 9.1 Build 20060323Z)
Microsoft Visual Studio .NET 7.0.9466 (for libraries)
MicroQuill Smartheap Library 7.0
File System: NTFS
System State: Default

Notes/Tuning Information

+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

Base tuning for C programs: -fast +FDO ONESTEP=yes shlw32M.lib

Base tuning for C++ programs: -fast -Qcxx_features +FDO ONESTEP=yes

Portability flags:

176.gcc: -Dalloca=_alloca /F10000000

186.crafty: -DNT_i386

253.perlbnk: -DSPEC_CPU2000_NTOS -DPERL DLL /MT

254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

Peak tuning:

164.gzip: -fast +FDO ONESTEP=yes

175.vpr: -fast +FDO ONESTEP=yes

176.gcc: basepeak=1

181.mcf: -fast +FDO ONESTEP=yes shlw32M.lib

186.crafty: -fast -Oa +FDO ONESTEP=yes shlw32M.lib

197.parser: -fast +FDO ONESTEP=yes

252.eon: -fast +FDO

253.perlbnk: -fast -Oa +FDO ONESTEP=yes shlw32M.lib

254.gap: -fast +FDO ONESTEP=yes

255.vortex: -fast +FDO ONESTEP=yes shlw32M.lib



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant DL580 G4 (3.0GHz, Intel Xeon processor 7041)

SPECint_rate2000 = 16.5
SPECint_rate_base2000 = 16.4

SPEC license #: 3 | Tested by: Hewlett-Packard Company | Test date: May-2006 | Hardware Avail: May-2006 | Software Avail: May-2006

Notes/Tuning Information (Continued)

```
256.bzip2:    basepeak=1
300.twolf:    -fast                +FDO                shlw32M.lib
BIOS Configuration Notes
Hyper-Threading Technology disabled
Other Configuration Notes
/NUMPROC=1 flag was added to boot.ini to invoke uniprocessor environment.
```