



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Supermicro

Motherboard X7DB8 (3.00GHz, Intel Xeon 5160 processor)

SPECfp_rate2000 = 74.9

SPECfp_rate_base2000 = 75.1

SPEC license #01176 | Tested by: Supermicro | Test date: May-2006 | Hardware Avail: May-2006 | Software Avail: Mar-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	4	75.0	99.0	4	75.0	99.0
171.swim	4	297	48.4	4	297	48.4
172.mgrid	4	187	44.7	4	187	44.8
173.applu	4	203	48.1	4	203	48.1
177.mesa	4	52.9	123	4	52.9	123
178.galgel	4	59.9	225	4	60.0	224
179.art	4	63.2	191	4	63.2	191
183.quake	4	101	60.0	4	101	59.9
187.facerec	4	99.0	89.1	4	99.0	89.0
188.amp	4	148	69.0	4	151	67.7
189.lucas	4	191	48.5	4	192	48.5
191.fma3d	4	180	54.0	4	180	54.0
200.sixtrack	4	93.9	54.3	4	95.2	53.6
301.apsi	4	191	63.2	4	191	63.1

Hardware

CPU: Intel Xeon 5160 processor (3.00 GHz, 4MB L2 shared, 1333 MHz bus)
CPU MHz: 3000
FPU: Integrated
CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip
CPU(s) orderable: 1, 2
Parallel: No
Primary Cache: 32KBI + 32KBD on chip per core
Secondary Cache: 4MB(I+D) on chip shared
L3 Cache: N/A
Other Cache: N/A
Memory: 8x 2GB 667MHz CL5 DDR2 FB-DIMM
Disk Subsystem: 1 X WD 2500 250GB SATA
Other Hardware: N/A

Software

Operating System: Windows server 2003 Enterprise Edition 32-bits W/ SP1
Compiler: Intel C++ and Fortran Compiler 9.1 for 32-bit applications
Build 20060323Z Package ID: W_FC_P_9.1.020
Microsoft Visual Studio 2005 (for libraries)
SmartHeap Library Version 8.0 from <http://www.microquill.com/>
File System: NTFS
System State: Default

Notes/Tuning Information

```
+FDO: PASS1= -Qprof_gen PASS2=-Qprof_use
Base tuning for Fortran programs: -fast -Qansi_alias +FDO
Base tuning for C programs: -fast shlW32M.lib +FDO
Portability:
178.galgel: -FI /F32000000
Peak tuning:
168.wupwise: -fast -Qansi_alias +FDO
171.swim: -fast -Qansi_alias +FDO
172.mgrid: -fast -Qansi_alias +FDO
173.applu: basepeak=yes
177.mesa: basepeak=yes
178.galgel: -fast -Qansi_alias +FDO
179.art: basepeak=yes
183.quake: -QxP -Oa -Qrcd -Qipo +FDO shlW32M.lib
187.facerec: -fast -Qunroll1 -Qscalar_rep- +FDO
188.amp: -fast -Oa +FDO shlW32M.lib
189.lucas: -fast -Qprefetch- +FDO
```



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Supermicro

Motherboard X7DB8 (3.00GHz, Intel Xeon 5160 processor)

SPECfp_rate2000 = 74.9

SPECfp_rate_base2000 = 75.1

SPEC license #01176 | Tested by: Supermicro | Test date: May-2006 | Hardware Avail: May-2006 | Software Avail: Mar-2006

Notes/Tuning Information (Continued)

191.fma3d: basepeak=yes

200.sixtrack: -Qipo -QxP +FDO

301.apsi: -fast +FDO

Tested systems can be used with SC825S2-R700LPV case,

To ensure system stability, a 500W (minimum) ATX power supply

[4-pin (+12V), 8-pin (+12V) and 24-pin are required]

Product description located as of X7DA8:

<http://www.supermicro.com/products/motherboard/Xeon1333/5000P/X7DB8.cfm>

The system bus runs at 1333 MHz