



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Dell
PowerEdge 1955 (Intel Xeon processor 5140, 2.33GHz)

SPECfp2000 = **2310**
SPECfp_base2000 = **2310**

SPEC license #: 55 Tested by: Dell, Round Rock, TX Test date: Jun-2006 Hardware Avail: Jul-2006 Software Avail: Mar-2006

| Benchmark | Reference Time | Base Runtime | Base Ratio | Runtime | Ratio |
|--------------|----------------|--------------|------------|---------|-------|
| 168.wupwise | 1600 | 51.4 | 3112 | 51.4 | 3112 |
| 171.swim | 3100 | 117 | 2640 | 117 | 2640 |
| 172.mgrid | 1800 | 113 | 1590 | 113 | 1590 |
| 173.aplu | 2100 | 113 | 1867 | 113 | 1867 |
| 177.mesa | 1400 | 57.9 | 2418 | 57.9 | 2418 |
| 178.galgel | 2900 | 53.6 | 5415 | 53.6 | 5415 |
| 179.art | 2600 | 28.4 | 9142 | 28.4 | 9142 |
| 183.quake | 1300 | 53.6 | 2427 | 53.6 | 2427 |
| 187.facerec | 1900 | 77.6 | 2448 | 77.6 | 2448 |
| 188.amp | 2200 | 130 | 1688 | 130 | 1688 |
| 189.lucas | 2000 | 106 | 1891 | 106 | 1891 |
| 191.fma3d | 2100 | 121 | 1741 | 121 | 1741 |
| 200.sixtrack | 1100 | 123 | 891 | 123 | 891 |
| 301.apsi | 2600 | 181 | 1435 | 181 | 1435 |

Hardware

CPU: Intel Xeon processor 5140 (1333MHz system bus)
CPU MHz: 2333
FPU: Integrated
CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip
CPU(s) orderable: 1,2
Parallel: No
Primary Cache: 32KB(I) + 32KB(D) on chip, per core
Secondary Cache: 4096KB(I+D) on chip, shared
L3 Cache: N/A
Other Cache: N/A
Memory: 8 x 1GB 667MHz ECC CL5 DDR2 FB-DIMM
Disk Subsystem: 1 x 73GB SAS 10000 RPM
Other Hardware: None

Software

Operating System: Red Hat Enterprise Linux 4 Advanced Server Update 3 EM64T
Compiler: Intel C++ and Fortran Compiler 9.0 for EM64T Builds 20060120 and 20051201
File System: ext3
System State: Runlevel 3

Notes/Tuning Information

GENERAL

ONESTEP=yes for all benchmarks

+FDO implies feedback-directed optimization PASS1: -prof_gen PASS2: -prof_use

PORTABILITY FLAGS

-DSPEC_CPU2000_LP64 applied to all benchmarks

178.galgel: -FI for fixed-format Fortran

BASE TUNING

Baseline optimizations for C and Fortran: -fast +FDO

PEAK TUNING

basepeak=yes set for all benchmarks