



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

## Dell

Precision Workstation 690 (Intel Xeon processor 5120, 1.86 GHz)

SPECfp\_rate2000 = 32.8

SPECfp\_rate\_base2000 = 32.8

SPEC license #: 55 | Tested by: Dell, Inc., Round Rock, TX | Test date: Jun-2006 | Hardware Avail: Jun-2006 | Software Avail: May-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	78.9	47.1	2	78.9	47.1
171.swim	2	281	25.6	2	281	25.6
172.mgrid	2	198	21.1	2	198	21.1
173.applu	2	198	24.6	2	198	24.6
177.mesa	2	80.7	40.3	2	80.7	40.3
178.galgel	2	78.6	85.6	2	78.6	85.6
179.art	2	62.9	95.9	2	62.9	95.9
183.equake	2	95.7	31.5	2	95.7	31.5
187.facerec	2	112	39.3	2	112	39.3
188.amp	2	201	25.4	2	201	25.4
189.lucas	2	168	27.6	2	168	27.6
191.fma3d	2	208	23.4	2	208	23.4
200.sixtrack	2	150	17.1	2	150	17.1
301.apsi	2	265	22.7	2	265	22.7

### Hardware

CPU: Intel Xeon processor 5120 (1066 MHz system bus)  
 CPU MHz: 1866  
 FPU: Integrated  
 CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip  
 CPU(s) orderable: 1,2  
 Parallel: No  
 Primary Cache: 32KB(I) + 32KB(D) on chip, per core  
 Secondary Cache: 4096KB(I+D) on chip  
 L3 Cache: N/A  
 Other Cache: N/A  
 Memory: 8 x 512MB 533MHz ECC CL4 FB-DIMM DDR2 SDRAM  
 Disk Subsystem: 1 x 73GB SAS 10K RPM  
 Other Hardware:

### Software

Operating System: Windows XP Professional x64 Edition  
 Compiler: Intel C++ Compiler 9.1 for IA32(20060519Z)  
 Intel Fortran Compiler 9.1 for IA32(20060519Z)  
 Microsoft Visual Studio .NET 2003(7.1.3088)  
 MicroQuill SmartHeap Library 8.0  
 File System: NTFS  
 System State: Default

## Notes/Tuning Information

### GENERAL

ONESTEP=yes  
 +FDO: PASS1=-Qprof\_gen PASS2=-Qprof\_use

### PORTABILITY

178.galgel: -FI /F32000000

### BASE TUNING

FORTRAN: -fast -Qansi\_alias +FDO  
 177.mesa: -fast +FDO shlw32M.lib  
 179.art: -fast +FDO shlw32M.lib  
 183.equake: -fast +FDO shlw32M.lib  
 188.amp: -fast +FDO shlw32M.lib

### PEAK TUNING

basepeak=yes