



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Acer Incorporated

Acer Altos R720 (1.6 GHz Intel Xeon Processor 5110)

SPECfp_rate2000 = 31.5

SPECfp_rate_base2000 = 31.5

SPEC license #: 97 Tested by: Acer Incorporated Test date: Jun-2006 Hardware Avail: Jun-2006 Software Avail: Mar-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	71.5	51.9	2	71.5	51.9
171.swim	2	261	27.5	2	261	27.5
172.mgrid	2	181	23.0	2	181	23.0
173.applu	2	189	25.8	2	189	25.8
177.mesa	2	85.8	37.9	2	85.8	37.9
178.galgel	2	94.7	71.1	2	94.7	71.1
179.art	2	68.6	87.9	2	68.6	87.9
183.equake	2	121	24.9	2	121	24.9
187.facerec	2	120	36.7	2	120	36.7
188.amp	2	197	26.0	2	197	26.0
189.lucas	2	187	24.9	2	187	24.9
191.fma3d	2	203	24.1	2	203	24.1
200.sixtrack	2	182	14.0	2	182	14.0
301.apsi	2	251	24.0	2	251	24.0

Hardware

CPU: Intel Xeon Processor 5110 (1.6 GHz, 4MB L2, 1066MHz system bus)
CPU MHz: 1600
FPU: Integrated
CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip
CPU(s) orderable: 1,2
Parallel: No
Primary Cache: 32KB(I) + 32KB(D) on chip, per core
Secondary Cache: 4096KB(I+D) on chip, shared
L3 Cache: N/A
Other Cache: N/A
Memory: 8 x 2048MB ECC FB-DIMM DDR2-667
Disk Subsystem: 1 x 73GB 10000RPM SAS HDD
Other Hardware:

Software

Operating System: Red Hat Enterprise Linux 4 Advanced Server Update 3 EM64T
Compiler: Intel C++ 9.1 for EM64T build 20060323 and Fortran Compiler 9.1 for EM64T build 20060323
File System: ext3
System State: Runlevel 3

Notes/Tuning Information

GENERAL

ONESTEP=yes for all benchmarks
+FDO : PASS1= -prof_gen PASS2= -prof_use

PORTABILITY FLAGS

-DSPEC_CPU2000_LP64 applied to all benchmarks
178.galgel: -FI for fixed-format Fortran

BASE TUNING

Baseline optimizations for C and Fortran: -fast +FDO

PEAK TUNING

basepeak=yes set for all benchmarks