



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation

IBM System X 3400 (1.60 GHz Xeon 5110, 4MB L2 Cache)

SPECfp2000 = --

SPECfp_base2000 = 1650

SPEC license #: 11 | Tested by: IBM Corporation | Test date: Jul-2006 | Hardware Avail: Jul-2006 | Software Avail: Mar-2006

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio
168.wupwise	1600	66.5	2407		
171.swim	3100	144	2159		
172.mgrid	1800	170	1056		
173.applu	2100	165	1276		
177.mesa	1400	89.9	1558		
178.galgel	2900	74.3	3902		
179.art	2600	46.8	5552		
183.earth	1300	62.2	2090		
187.facerec	1900	118	1609		
188.amp	2200	187	1175		
189.lucas	2000	134	1489		
191.fma3d	2100	169	1239		
200.sixtrack	1100	172	641		
301.apsi	2600	258	1006		

Hardware

CPU: Intel Xeon processor 5110 (1.60 GHz, 1333 MHz bus)
 CPU MHz: 1600
 FPU: Integrated
 CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip
 CPU(s) orderable: 1, 2
 Parallel: No
 Primary Cache: 32KB(I) + 32KB(D) on chip (per core)
 Secondary Cache: 4096KB(I+D) on chip (per chip)
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 8 x 1024 MB ECC PC2-5300F
 Disk Subsystem: 80GB SATA 10K RPM
 Other Hardware:

Software

Operating System: Windows Server 2003 Enterprise Edition (32-bit)
 Compiler: Intel C++ and Fortran Compiler 9.1 for 32-bit applications
 Build 20060323Z
 Microsoft Visual Studio 2005(for libraries)
 SmartHeap Library Version 8.0 from <http://www.microquill.com/>
 File System: NTFS
 System State: Default

Notes/Tuning Information

```
+FDO: PASS1= -Qprof_gen PASS2=-Qprof_use
Base tuning for Fortran programs: -fast -Qansi_alias +FDO
Base tuning for C programs: -fast +FDO shlw32M.lib
Portability:
178.galgel: -FI /F32000000
```