



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation


Hewlett-Packard Company

ProLiant ML350 G5 (1.6 GHz, Intel Xeon processor 5110)

SPECfp_rate2000 = 56.4

SPECfp_rate_base2000 = 52.8

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Jul-2006 Hardware Avail: May-2006 Software Avail: May-2006



Hardware

CPU: Intel Xeon processor 5110 (1.6 GHz, 4 MB L2 shared, 1066 MHz bus)
 CPU MHz: 1600
 FPU: Integrated
 CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip
 CPU(s) orderable: 1,2 chips
 Parallel: No
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 4 MB I+D on chip per chip
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 8 GB (4x2048 MB PC2-5300F)
 Disk Subsystem: 1x36 GB 15 K SAS
 Other Hardware:

Software

Operating System: RedHat Enterprise Linux 4.0 Advanced Server for AMD64/EM64T, Update 3 Kernel 2.6.9-34.ELsmp
 Compiler: Intel C++ Compiler for EM64T-based applications, (Version 9.1 Build 20060323)
 Intel Fortran Compiler for EM64T-based applications, (Version 9.1 Build 20060323)
 PathScale EKOPath(TM) Compiler Suite, Release 2.4
 File System: ext2
 System State: multi-user run level 3

Notes/Tuning Information

+FDO: PASS1= -prof_gen PASS2=-prof_use (Intel Compiler)
 +FDO: PASS1= -fb_create fbdata PASS2=-fb_opt fbdata (PathScale Compiler)
 ifort is the Intel Fortran compiler, icc is the Intel C++ compiler; and pathf95 is PathScale Fortran compiler, pathcc is the PathScale C compiler.
 Base tuning for C programs: icc -fast -auto_ilp32 +FDO
 Base tuning for FORTRAN programs: ifort -fast +FDO
 Portability:
 -DSPEC_CPU2000_LP64 applied to all benchmarks
 178.galgel: -FI
 Peak tuning:
 168.wupwise: basepeak=1
 171.swim: pathf95 -Ofast -LNO:fusion=2:simd=0 -WOPT:val=0 -march=em64t
 172.mgrid: pathf95 -Ofast -CG:load_exe=0 -LNO:blocking=off:prefetch_ahead=5
 -OPT:ro=3:unroll_size=256 -WOPT:mem_opnds=on -march=em64t
 173.applu: pathf95 -O3 -ipa -CG:load_exe=0
 -LNO:fission=1:fusion=2:blocking=off:full_unroll_size=9000
 -OPT:IEEE_a=3:ro=3 -TENV:X=3 -march=em64t



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant ML350 G5 (1.6 GHz, Intel Xeon processor 5110)

SPECfp_rate2000 = 56.4
SPECfp_rate_base2000 = 52.8

SPEC license #: 3 | Tested by: Hewlett-Packard Company | Test date: Jul-2006 | Hardware Avail: May-2006 | Software Avail: May-2006

Notes/Tuning Information (Continued)

```
177.mesa: pathcc -O2 -ipa -OPT:Ofast -fno-math-errno -CG:local_fwd_sched=on
          -GRA:optimize_boundary=on -march=em64t +FDO
178.galgel: basepeak=1
179.art: basepeak=1
183.equake: icc -fast +FDO ONESTEP=yes -rcd -auto-ilp32
187.facerec: pathf95 -Ofast -IPA:plimit=1500 -LNO:fusion=2
            -OPT:IEEE_NaN_Inf=off:ro=3:unroll_size=0 -march=em64t +FDO
188.amm: basepeak=1
189.lucas: ifort -fast ONESTEP=yes
191.fma3d: basepeak=1
200.sixtrack: basepeak=1
301.apsi: pathf95 -Ofast -CG:load_exe=0 -LNO:opt=0:prefetch=1 -march=em64t
```

BIOS Configuration Notes
Power Regulator set to Static High