



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation

IBM System X 3250 (1.86 GHz Xeon 3040, 4MB L2 Cache)

SPECfp_rate2000 = --

SPECfp_rate_base2000 = 35.7

SPEC license #: 11 | Tested by: IBM Corporation | Test date: Oct-2006 | Hardware Avail: Nov-2006 | Software Avail: Mar-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	56.8	65.4			
171.swim	2	215	33.4			
172.mgrid	2	161	25.9			
173.applu	2	176	27.7			
177.mesa	2	76.1	42.7			
178.galgel	2	110	61.4			
179.art	2	92.2	65.5			
183.earthquake	2	67.7	44.5			
187.facerec	2	110	39.9			
188.amp	2	227	22.5			
189.lucas	2	137	33.9			
191.fma3d	2	165	29.5			
200.sixtrack	2	150	17.0			
301.apsi	2	204	29.6			

Hardware

CPU: Intel Xeon processor 3040 (1.86 GHz, 1066 MHz bus)
CPU MHz: 1866
FPU: Integrated
CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip
CPU(s) orderable: 1 chip
Parallel: No
Primary Cache: 32KB(I) + 32KB(D) on chip (per core)
Secondary Cache: 4096KB(I+D) on chip (per chip)
L3 Cache: N/A
Other Cache: N/A
Memory: 4 x 1024 MB ECC PC2-5300
Disk Subsystem: 73GB SAS 15K RPM
Other Hardware:

Software

Operating System: Windows Server 2003 Enterprise Edition (32-bit)
Compiler: Intel C++ and Fortran Compiler 9.1 for 32-bit applications
Build 20060323Z
Microsoft Visual Studio 2005(for libraries)
SmartHeap Library Version 8.0 from <http://www.microquill.com/>
File System: NTFS
System State: Default

Notes/Tuning Information

```
+FDO: PASS1= -Qprof_gen PASS2=-Qprof_use
Base tuning for Fortran programs: -fast -Qansi_alias +FDO
Base tuning for C programs: -fast +FDO shlW32M.lib
Portability:
178.galgel: -FI /F32000000
```