



SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Hewlett-Packard Company

SPECint®_rate2006 = 34.4

ProLiant DL380 G5
(1.86 GHz, Intel Xeon processor E5320)

SPECint_rate_base2006 = 33.3

CPU2006 license: 3


Test date: Feb-2007

Test sponsor: Hewlett-Packard Company

Hardware Availability: Nov-2006

Tested by: Hewlett-Packard Company

Software Availability: Nov-2006



Hardware

CPU Name: Intel Xeon E5320
 CPU Characteristics: 1.86 GHz, 2x4 MB L2 shared, 1066 MHz system bus
 CPU MHz: 1860
 FPU: Integrated
 CPU(s) enabled: 4 cores, 1 chip, 4 cores/chip
 CPU(s) orderable: 1,2 chips
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 8 MB I+D on chip per chip, 4 MB shared / 2 cores
 L3 Cache: None
 Other Cache: None
 Memory: 16 GB (8x2 GB PC2-5300F CL5)
 Disk Subsystem: 4x36 GB 10 K SAS
 Other Hardware: None

Software

Operating System: Windows Server 2003 Enterprise x64 Edition SP1
 Compiler: Intel C++ Compiler for 32-bit applications, Version 9.1, Build 20061103Z
 Package ID: W_CC_C_9.1.033
 Microsoft Visual Studio .NET 2003 (v7.1.3088, for libraries)
 Auto Parallel: No
 File System: NTFS
 System State: Default
 Base Pointers: 32-bit
 Peak Pointers: 32-bit
 Other Software: MicroQuill SmartHeap Library 8.0



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Hewlett-Packard Company

SPECint_rate2006 = 34.4

ProLiant DL380 G5
(1.86 GHz, Intel Xeon processor E5320)

SPECint_rate_base2006 = 33.3

CPU2006 license: 3

Test date: Feb-2007

Test sponsor: Hewlett-Packard Company

Hardware Availability: Nov-2006

Tested by: Hewlett-Packard Company

Software Availability: Nov-2006

Results Table

Benchmark	Base						Peak							
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	4	746	52.4	747	52.3	747	52.3	4	685	57.1	683	57.2	685	57.0
401.bzip2	4	1267	30.5	1263	30.6	1265	30.5	4	1242	31.1	1238	31.2	1240	31.1
403.gcc	4	1792	18.0	1802	17.9	1792	18.0	4	1791	18.0	1781	18.1	1786	18.0
429.mcf	4	1137	32.1	1138	32.1	1136	32.1	4	1137	32.1	1138	32.1	1136	32.1
445.gobmk	4	879	47.7	884	47.5	886	47.3	4	790	53.1	788	53.2	784	53.5
456.hammer	4	1197	31.2	1197	31.2	1198	31.2	4	1165	32.0	1165	32.0	1166	32.0
458.sjeng	4	1066	45.4	1066	45.4	1066	45.4	4	980	49.4	980	49.4	980	49.4
462.libquantum	4	5382	15.4	5380	15.4	5379	15.4	4	5371	15.4	5370	15.4	5372	15.4
464.h264ref	4	1167	75.9	1164	76.1	1165	76.0	4	1141	77.6	1141	77.6	1140	77.7
471.omnetpp	4	1095	22.8	1096	22.8	1095	22.8	4	1067	23.4	1067	23.4	1067	23.4
473.astar	4	1052	26.7	1052	26.7	1053	26.7	4	1056	26.6	1056	26.6	1056	26.6
483.xalancbmk	4	653	42.3	653	42.3	653	42.2	4	638	43.3	638	43.3	637	43.3

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Platform Notes

Power Regulator set to Static High Performance Mode in BIOS.
Adjacent Sector Prefetch Disabled in BIOS.

Base Compiler Invocation

C benchmarks:
icl -Qvc7.1 -Qc99
C++ benchmarks:
icl -Qvc7.1

Base Portability Flags

403.gcc: -DSPEC_CPU_WIN32
464.h264ref: -DSPEC_CPU_NO_INTTYPES -DWIN32

Base Optimization Flags

C benchmarks:
-fast /F512000000 shlw32m.lib -link /FORCE:MULTIPLE

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Hewlett-Packard Company

SPECint_rate2006 = 34.4

ProLiant DL380 G5
(1.86 GHz, Intel Xeon processor E5320)

SPECint_rate_base2006 = 33.3

CPU2006 license: 3

Test date: Feb-2007

Test sponsor: Hewlett-Packard Company

Hardware Availability: Nov-2006

Tested by: Hewlett-Packard Company

Software Availability: Nov-2006

Base Optimization Flags (Continued)

C++ benchmarks:

```
-fast -Qcxx_features /F512000000 shlw32m.lib
-link /FORCE:MULTIPLE
```

Base Other Flags

C benchmarks:

```
403.gcc: -Dalloca=_alloca
```

Peak Compiler Invocation

C benchmarks:

```
icl -Qvc7.1 -Qc99
```

C++ benchmarks:

```
icl -Qvc7.1
```

Peak Portability Flags

```
403.gcc: -DSPEC_CPU_WIN32
464.h264ref: -DSPEC_CPU_NO_INTTYPES -DWIN32
```

Peak Optimization Flags

C benchmarks:

```
400.perlbench: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast /F512000000
shlw32m.lib -link /FORCE:MULTIPLE
```

```
401.bzip2: Same as 400.perlbench
```

```
403.gcc: Same as 400.perlbench
```

```
429.mcf: basepeak = yes
```

```
445.gobmk: Same as 400.perlbench
```

```
456.hmmmer: Same as 400.perlbench
```

```
458.sjeng: Same as 400.perlbench
```

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Hewlett-Packard Company

SPECint_rate2006 = 34.4

ProLiant DL380 G5
(1.86 GHz, Intel Xeon processor E5320)

SPECint_rate_base2006 = 33.3

CPU2006 license: 3

Test date: Feb-2007

Test sponsor: Hewlett-Packard Company

Hardware Availability: Nov-2006

Tested by: Hewlett-Packard Company

Software Availability: Nov-2006

Peak Optimization Flags (Continued)

462.libquantum: Same as 400.perlbench

464.h264ref: Same as 400.perlbench

C++ benchmarks:

-Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qcxx_features
/F512000000 shlw32m.lib -link /FORCE:MULTIPLE

Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/hp-ic91-flags.20090715.02.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/hp-ic91-flags.20090715.02.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 10:50:27 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 20 March 2007.