



SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY RX200 S3, Intel Xeon processor 5150,
2.66 GHz

SPECint®_rate2006 = 54.8

SPECint_rate_base2006 = 52.2

CPU2006 license: 22


Test sponsor: Fujitsu Siemens Computers

Tested by: Fujitsu Siemens Computers

Test date: Apr-2007

Hardware Availability: Jul-2006

Software Availability: Feb-2007



Hardware

CPU Name: Intel Xeon 5150
 CPU Characteristics: 1333 MHz system bus
 CPU MHz: 2667
 FPU: Integrated
 CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip
 CPU(s) orderable: 1,2 chips
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 4 MB I+D on chip per chip
 L3 Cache: None
 Other Cache: None
 Memory: 8 GB (8x1 GB DDR2 PC2-5300F, 2 rank, CAS 5-5-5, with ECC)
 Disk Subsystem: SAS (73GB 15400 rpm)
 Other Hardware: None

Software

Operating System: 64-Bit SUSE LINUX Enterprise Server 10, Kernel 2.6.16.21-0.8-smp on an x86_64
 Compiler: Intel C++ Compiler for IA32/EM64T application, Version 9.1 - Build 20070215, Package-ID: l_cc_p_9.1.047
 Auto Parallel: No
 File System: ext2
 System State: Multiuser, Runlevel 3
 Base Pointers: 32-bit
 Peak Pointers: 32/64-bit
 Other Software: Smart Heap Library, Version 8.1



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY RX200 S3, Intel Xeon processor 5150,
2.66 GHz

SPECint_rate2006 = 54.8

SPECint_rate_base2006 = 52.2

CPU2006 license: 22

Test sponsor: Fujitsu Siemens Computers

Tested by: Fujitsu Siemens Computers

Test date: Apr-2007

Hardware Availability: Jul-2006

Software Availability: Feb-2007

Results Table

Benchmark	Base						Peak							
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	4	567	69.0	<u>563</u>	<u>69.4</u>	557	70.1	4	512	76.3	<u>514</u>	<u>76.1</u>	515	75.8
401.bzip2	4	920	42.0	<u>925</u>	<u>41.7</u>	929	41.5	4	876	44.1	<u>878</u>	<u>44.0</u>	880	43.8
403.gcc	4	627	51.3	<u>631</u>	<u>51.0</u>	632	50.9	4	627	51.3	<u>631</u>	<u>51.0</u>	632	50.9
429.mcf	4	<u>782</u>	<u>46.6</u>	783	46.6	781	46.7	4	800	45.6	802	45.5	<u>801</u>	<u>45.5</u>
445.gobmk	4	618	67.9	<u>618</u>	<u>67.9</u>	612	68.6	4	<u>572</u>	<u>73.3</u>	564	74.4	573	73.2
456.hmmer	4	<u>834</u>	<u>44.7</u>	834	44.7	834	44.8	4	699	53.4	696	53.6	<u>698</u>	<u>53.5</u>
458.sjeng	4	757	64.0	761	63.6	<u>760</u>	<u>63.7</u>	4	<u>698</u>	<u>69.3</u>	697	69.5	699	69.3
462.libquantum	4	2767	30.0	2779	29.8	<u>2767</u>	<u>30.0</u>	4	<u>2722</u>	<u>30.5</u>	2726	30.4	2710	30.6
464.h264ref	4	<u>825</u>	<u>107</u>	825	107	824	107	4	817	108	<u>816</u>	<u>109</u>	816	109
471.omnetpp	4	701	35.6	704	35.5	<u>702</u>	<u>35.6</u>	4	<u>650</u>	<u>38.5</u>	654	38.2	649	38.5
473.astar	4	703	40.0	703	39.9	<u>703</u>	<u>39.9</u>	4	<u>694</u>	<u>40.5</u>	694	40.4	694	40.5
483.xalancbmk	4	405	68.2	407	67.8	<u>406</u>	<u>67.9</u>	4	405	68.2	407	67.8	<u>406</u>	<u>67.9</u>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run
'/usr/bin/taskset' used to bind processes to CPUs

General Notes

The system bus runs at 1333 MHz

All binaries were built with 32-bit Intel compiler except:
401.bzip2, 456.hmmer and 462.libquantum in peak were built with
64-bit Intel compiler by changing the path for include and library files.

BIOS configuration:
Adjacent Sector Prefetch = Disable

For information about Fujitsu Siemens Computers in your country please see:
<http://www.fujitsu-siemens.com/countries>

Base Compiler Invocation

C benchmarks:
icc

C++ benchmarks:
icpc



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY RX200 S3, Intel Xeon processor 5150,
2.66 GHz

SPECint_rate2006 = 54.8

SPECint_rate_base2006 = 52.2

CPU2006 license: 22

Test sponsor: Fujitsu Siemens Computers

Tested by: Fujitsu Siemens Computers

Test date: Apr-2007

Hardware Availability: Jul-2006

Software Availability: Feb-2007

Base Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_X64
462.libquantum: -DSPEC_CPU_LINUX
483.xalancbmk: -DSPEC_CPU_LINUX

Base Optimization Flags

C benchmarks:

-fast

C++ benchmarks:

-xP -O3 -ipo -no-prec-div -L/opt/SmartHeap_8_1/lib -lsmartheap

Peak Compiler Invocation

C benchmarks (except as noted below):

icc

401.bzip2: /opt/intel/cce/9.1.047/bin/icc
-I/opt/intel/cce/9.1.047/include
-L/opt/intel/cce/9.1.047/lib

456.hmmer: /opt/intel/cce/9.1.047/bin/icc
-I/opt/intel/cce/9.1.047/include
-L/opt/intel/cce/9.1.047/lib

462.libquantum: /opt/intel/cce/9.1.047/bin/icc
-I/opt/intel/cce/9.1.047/include
-L/opt/intel/cce/9.1.047/lib

C++ benchmarks:

icpc

Peak Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_X64
401.bzip2: -DSPEC_CPU_LP64
456.hmmer: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX
483.xalancbmk: -DSPEC_CPU_LINUX



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY RX200 S3, Intel Xeon processor 5150,
2.66 GHz

SPECint_rate2006 = 54.8

SPECint_rate_base2006 = 52.2

CPU2006 license: 22

Test sponsor: Fujitsu Siemens Computers

Tested by: Fujitsu Siemens Computers

Test date: Apr-2007

Hardware Availability: Jul-2006

Software Availability: Feb-2007

Peak Optimization Flags

C benchmarks:

400.perlbench: -prof_gen(pass 1) -prof_use(pass 2) -fast

401.bzip2: -fast

403.gcc: basepeak = yes

429.mcf: -prof_gen(pass 1) -prof_use(pass 2) -fast
-L/opt/SmartHeap_8_1/lib -lsmartheap

445.gobmk: Same as 429.mcf

456.hmmer: Same as 400.perlbench

458.sjeng: Same as 429.mcf

462.libquantum: Same as 400.perlbench

464.h264ref: Same as 429.mcf

C++ benchmarks:

471.omnetpp: -prof_gen(pass 1) -prof_use(pass 2) -xP -O3 -ipo
-no-prec-div -L/opt/SmartHeap_8_1/lib -lsmartheap

473.astar: -prof_gen(pass 1) -prof_use(pass 2) -fast
-L/opt/SmartHeap_8_1/lib -lsmartheap

483.xalancbmk: basepeak = yes

The flags file that was used to format this result can be browsed at

http://www.spec.org/cpu2006/flags/CPU2006_flags.20090714.09.html

You can also download the XML flags source by saving the following link:

http://www.spec.org/cpu2006/flags/CPU2006_flags.20090714.09.xml

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 11:46:39 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 29 May 2007.