




SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Supermicro Motherboard X7DA8	SPECint®2006 = 16.2
	SPECint_base2006 = 15.5



Hardware		Software	
CPU Name:	Intel Xeon X5355	Operating System:	Windows Server 2003 Enterprise Edition W/ SP1
CPU Characteristics:	2.66GHz, 1333 MHz Bus	Compiler:	Intel C++ Compiler for IA32 version 9.1
CPU MHz:	2660		Build no 20070322Z
FPU:	Integrated		Microsoft Visual Studio .Net 2003 (for libraries)
CPU(s) enabled:	8 cores, 2 chips, 4 cores/chip	Auto Parallel:	No
CPU(s) orderable:	1, 2 chips	File System:	NTFS
Primary Cache:	32 KB I + 32 KB D on chip per core	System State:	Default
Secondary Cache:	8 MB I+D on chip per chip, 4 MB shared / 2 cores	Base Pointers:	32-bit
L3 Cache:	None	Peak Pointers:	32-bit
Other Cache:	None	Other Software:	SmartHeap Library Version 8.0
Memory:	16 GB (8 X 2GB ECC PC2-5300, CL5, FBDIMM)		
Disk Subsystem:	750GB IDE, 7200RPM		
Other Hardware:	None		



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Supermicro
Motherboard X7DA8

SPECint2006 = 16.2
SPECint_base2006 = 15.5

CPU2006 license: 001176

Test date: Apr-2007

Test sponsor: Supermicro

Hardware Availability: May-2007

Tested by: Supermicro

Software Availability: Apr-2007

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	513	19.1	511	19.1	512	19.1	460	21.2	460	21.2	463	21.1
401.bzip2	700	13.8	700	13.8	700	13.8	683	14.1	684	14.1	684	14.1
403.gcc	687	11.7	687	11.7	686	11.7	666	12.1	660	12.2	659	12.2
429.mcf	537	17.0	537	17.0	537	17.0	537	17.0	537	17.0	537	17.0
445.gobmk	589	17.8	590	17.8	589	17.8	539	19.5	538	19.5	539	19.5
456.hmmer	832	11.2	827	11.3	830	11.2	810	11.5	810	11.5	810	11.5
458.sjeng	735	16.5	737	16.4	733	16.5	691	17.5	690	17.5	691	17.5
462.libquantum	1454	14.2	1473	14.1	1450	14.3	1448	14.3	1456	14.2	1446	14.3
464.h264ref	796	27.8	793	27.9	793	27.9	774	28.6	774	28.6	774	28.6
471.omnetpp	549	11.4	561	11.1	552	11.3	506	12.4	499	12.5	506	12.4
473.astar	557	12.6	555	12.6	557	12.6	506	13.9	508	13.8	505	13.9
483.xalancbmk	349	19.7	350	19.7	349	19.8	354	19.5	355	19.4	355	19.5

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

General Notes

Tested systems can be used with SC816S-R700 case,
To ensure system stability, a 500W (minimum) ATX power supply [4-pin (+12V), 8-pin (+12V) and 24-pin are required]
Product description located as of <http://www.supermicro.com/products/motherboard/Xeon1333/5000X/X7DA8.cfm>
The system bus runs at 1333 MHz

Base Compiler Invocation

C benchmarks:

```
icl -Qvc7.1 -Qc99
```

C++ benchmarks:

```
icl -Qvc7.1
```

Base Portability Flags

403.gcc: -DSPEC_CPU_WIN32

464.h264ref: -DSPEC_CPU_NO_INTTYPES -DWIN32

Base Optimization Flags

C benchmarks:

```
-fast /F512000000 shlw32m.lib
```

```
-link /FORCE:MULTIPLE
```

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Supermicro
Motherboard X7DA8

SPECint2006 = 16.2
SPECint_base2006 = 15.5

CPU2006 license: 001176

Test sponsor: Supermicro

Tested by: Supermicro

Test date: Apr-2007

Hardware Availability: May-2007

Software Availability: Apr-2007

Base Optimization Flags (Continued)

C++ benchmarks:

```
-fast -Qcxx_features /F512000000 shlw32m.lib  
-link /FORCE:MULTIPLE
```

Base Other Flags

C benchmarks:

```
403.gcc: -Dalloca=_alloca
```

Peak Compiler Invocation

C benchmarks:

```
icl -Qvc7.1 -Qc99
```

C++ benchmarks:

```
icl -Qvc7.1
```

Peak Portability Flags

```
403.gcc: -DSPEC_CPU_WIN32  
464.h264ref: -DSPEC_CPU_NO_INTTYPES -DWIN32
```

Peak Optimization Flags

C benchmarks:

```
400.perlbench: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast /F512000000  
shlw32m.lib  
-link /FORCE:MULTIPLE
```

401.bzip2: Same as 400.perlbench

403.gcc: Same as 400.perlbench

429.mcf: basepeak = yes

445.gobmk: Same as 400.perlbench

456.hammer: Same as 400.perlbench

458.sjeng: Same as 400.perlbench

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Supermicro
Motherboard X7DA8

SPECint2006 = 16.2
SPECint_base2006 = 15.5

CPU2006 license: 001176

Test date: Apr-2007

Test sponsor: Supermicro

Hardware Availability: May-2007

Tested by: Supermicro

Software Availability: Apr-2007

Peak Optimization Flags (Continued)

462.libquantum: Same as 400.perlbench

464.h264ref: Same as 400.perlbench

C++ benchmarks:

471.omnetpp: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qcxx_features
/F512000000 shlw32m.lib -link /FORCE:MULTIPLE

473.astar: -Qprof_gen(pass 1) -Qprof_use(pass 2) -QxP -O2 -Qipo
-Qprec-div- -Qunroll4 -Ob2 -Qsfalign16 -Qcxx_features
/F512000000 shlw32m.lib -link /FORCE:MULTIPLE

483.xalancbmk: Same as 471.omnetpp

Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic91-ia32-flags.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic91-ia32-flags.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.1.
Report generated on Tue Jul 22 11:20:50 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 26 June 2007.