



# SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Fujitsu Siemens Computers

PRIMERGY RX300 S3, Intel Xeon processor X5365,  
3.0 GHz

**SPECint\_rate2006 = 107**

**SPECint\_rate\_base2006 = 98.9**

CPU2006 license: 22


**Test date:** Jul-2007

**Test sponsor:** Fujitsu Siemens Computers

**Hardware Availability:** Aug-2007

**Tested by:** Fujitsu Siemens Computers

**Software Availability:** Jun-2007



**SPECint\_rate\_base2006 = 98.9**

**SPECint\_rate2006 = 107**

### Hardware

CPU Name:	Intel Xeon X5365
CPU Characteristics:	1333 MHz system bus
CPU MHz:	3000
FPU:	Integrated
CPU(s) enabled:	8 cores, 2 chips, 4 cores/chip
CPU(s) orderable:	1,2 chips
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	8 MB I+D on chip per chip, 4 MB shared / 2 cores
L3 Cache:	None
Other Cache:	None
Memory:	8 GB (8x1 GB DDR2 PC2-5300F, 2 rank, CAS 5-5-5, with ECC)
Disk Subsystem:	Seagate ST3146854SS (SAS, 146GB, 15000rpm)
Other Hardware:	None

### Software

Operating System:	SUSE LINUX Enterprise Server 10 (x86_64), Kernel 2.6.16.21-0.8-smp
Compiler:	Intel C++ Compiler for IA32/EM64T application, Version 10.0 - Build 20070308, Package-ID: l_cc_p_10.0.023
Auto Parallel:	No
File System:	ext2
System State:	Multiuser, Runlevel 3
Base Pointers:	32-bit
Peak Pointers:	32/64-bit
Other Software:	Smart Heap Library, Version 8.1 binutils-2.17.tar.gz, Version 2.17



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Fujitsu Siemens Computers

PRIMERGY RX300 S3, Intel Xeon processor X5365,  
3.0 GHz

**SPECint\_rate2006 = 107**

**SPECint\_rate\_base2006 = 98.9**

CPU2006 license: 22

Test date: Jul-2007

Test sponsor: Fujitsu Siemens Computers

Hardware Availability: Aug-2007

Tested by: Fujitsu Siemens Computers

Software Availability: Jun-2007

## Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	8	534	146	<b>537</b>	<b>146</b>	541	145	8	457	171	468	167	<b>467</b>	<b>167</b>
401.bzip2	8	1003	77.0	<b>1008</b>	<b>76.6</b>	1009	76.5	8	<b>955</b>	<b>80.8</b>	954	80.9	956	80.8
403.gcc	8	750	85.9	753	85.5	<b>751</b>	<b>85.8</b>	8	750	85.9	753	85.5	<b>751</b>	<b>85.8</b>
429.mcf	8	1108	65.8	<b>1108</b>	<b>65.9</b>	1107	65.9	8	<b>1030</b>	<b>70.8</b>	1029	70.9	1030	70.8
445.gobmk	8	577	145	<b>579</b>	<b>145</b>	579	145	8	533	157	<b>533</b>	<b>157</b>	536	157
456.hammer	8	<b>640</b>	<b>117</b>	640	117	639	117	8	522	143	524	142	<b>522</b>	<b>143</b>
458.sjeng	8	715	135	720	135	<b>717</b>	<b>135</b>	8	<b>643</b>	<b>151</b>	642	151	643	150
462.libquantum	8	3373	49.1	<b>3374</b>	<b>49.1</b>	3374	49.1	8	2868	57.8	<b>2867</b>	<b>57.8</b>	2866	57.8
464.h264ref	8	756	234	<b>754</b>	<b>235</b>	754	235	8	715	248	<b>716</b>	<b>247</b>	717	247
471.omnetpp	8	<b>809</b>	<b>61.8</b>	811	61.7	808	61.8	8	783	63.9	780	64.1	<b>781</b>	<b>64.0</b>
473.astar	8	752	74.7	<b>748</b>	<b>75.1</b>	745	75.3	8	738	76.1	739	76.0	<b>738</b>	<b>76.1</b>
483.xalancbmk	8	<b>484</b>	<b>114</b>	483	114	485	114	8	<b>484</b>	<b>114</b>	483	114	485	114

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## General Notes

All binaries were built with 32-bit Intel compiler except:  
401.bzip2 and 456.hammer in peak were built with 64-bit Intel  
compiler by changing the path for include and library files.

BIOS configuration:

Hardware Prefetch = Disable, Adjacent Sector Prefetch = Disable

The PRIMERGY RX300 S3 and the PRIMERGY TX300 S3 are electronically equivalent.

For information about Fujitsu Siemens Computers please see:  
<http://www.fujitsu-siemens.com>

## Base Compiler Invocation

C benchmarks:

icc

C++ benchmarks:

icpc



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Fujitsu Siemens Computers

PRIMERGY RX300 S3, Intel Xeon processor X5365,  
3.0 GHz

**SPECint\_rate2006 = 107**

**SPECint\_rate\_base2006 = 98.9**

**CPU2006 license:** 22

**Test date:** Jul-2007

**Test sponsor:** Fujitsu Siemens Computers

**Hardware Availability:** Aug-2007

**Tested by:** Fujitsu Siemens Computers

**Software Availability:** Jun-2007

## Base Portability Flags

400.perlbench: -DSPEC\_CPU\_LINUX\_IA32  
462.libquantum: -DSPEC\_CPU\_LINUX  
483.xalancbmk: -DSPEC\_CPU\_LINUX

## Base Optimization Flags

C benchmarks:  
-fast

C++ benchmarks:  
-xT -O3 -ipo -no-prec-div -ansi-alias  
-L/opt/SmartHeap\_8\_1/lib -lsmartheap

## Base Other Flags

C benchmarks:

403.gcc: -Dalloca=\_alloca

## Peak Compiler Invocation

C benchmarks (except as noted below):  
icc

401.bzip2: /opt/intel/cce/10.0.023/bin/icc  
-I/opt/intel/cce/10.0.023/include  
-L/opt/intel/cce/10.0.023/lib

456.hmmr: /opt/intel/cce/10.0.023/bin/icc  
-I/opt/intel/cce/10.0.023/include  
-L/opt/intel/cce/10.0.023/lib

C++ benchmarks:  
icpc

## Peak Portability Flags

400.perlbench: -DSPEC\_CPU\_LINUX\_IA32  
401.bzip2: -DSPEC\_CPU\_LP64  
456.hmmr: -DSPEC\_CPU\_LP64  
462.libquantum: -DSPEC\_CPU\_LINUX

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Fujitsu Siemens Computers

PRIMERGY RX300 S3, Intel Xeon processor X5365,  
3.0 GHz

**SPECint\_rate2006 = 107**

**SPECint\_rate\_base2006 = 98.9**

**CPU2006 license:** 22

**Test date:** Jul-2007

**Test sponsor:** Fujitsu Siemens Computers

**Hardware Availability:** Aug-2007

**Tested by:** Fujitsu Siemens Computers

**Software Availability:** Jun-2007

## Peak Portability Flags (Continued)

483.xalancbmk: -DSPEC\_CPU\_LINUX

## Peak Optimization Flags

C benchmarks:

400.perlbench: -prof\_gen(pass 1) -prof\_use(pass 2) -fast

401.bzip2: -fast

403.gcc: basepeak = yes

429.mcf: -prof\_gen(pass 1) -prof\_use(pass 2) -fast -prefetch  
-L/opt/SmartHeap\_8\_1/lib -lsmartheap

445.gobmk: Same as 400.perlbench

456.hmmr: -prof\_gen(pass 1) -prof\_use(pass 2) -fast -unroll12

458.sjeng: -prof\_gen(pass 1) -prof\_use(pass 2) -fast -unroll14

462.libquantum: -prof\_gen(pass 1) -prof\_use(pass 2) -fast -prefetch  
-opt-streaming-stores always

464.h264ref: -prof\_gen(pass 1) -prof\_use(pass 2) -fast -unroll2  
-ansi-alias

C++ benchmarks:

471.omnetpp: -prof\_gen(pass 1) -prof\_use(pass 2) -fast -ansi-alias  
-L/opt/SmartHeap\_8\_1/lib -lsmartheap

473.astar: Same as 471.omnetpp

483.xalancbmk: basepeak = yes

## Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=\_alloca

The flags file that was used to format this result can be browsed at

[http://www.spec.org/cpu2006/flags/FSC\\_Intel\\_flags.html](http://www.spec.org/cpu2006/flags/FSC_Intel_flags.html)



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Fujitsu Siemens Computers

PRIMERGY RX300 S3, Intel Xeon processor X5365,  
3.0 GHz

**SPECint\_rate2006 = 107**

**SPECint\_rate\_base2006 = 98.9**

**CPU2006 license:** 22

**Test date:** Jul-2007

**Test sponsor:** Fujitsu Siemens Computers

**Hardware Availability:** Aug-2007

**Tested by:** Fujitsu Siemens Computers

**Software Availability:** Jun-2007

You can also download the XML flags source by saving the following link:

[http://www.spec.org/cpu2006/flags/FSC\\_Intel\\_flags.xml](http://www.spec.org/cpu2006/flags/FSC_Intel_flags.xml)

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.0.

Report generated on Tue Jul 22 13:24:24 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 24 July 2007.