



# SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Hewlett-Packard Company

SPECint®\_rate2006 = 52.4

ProLiant DL385 G5  
(2.3 GHz AMD Opteron 2356)

SPECint\_rate\_base2006 = 45.7

CPU2006 license: 3


Test date: Mar-2008

Test sponsor: Hewlett-Packard Company

Hardware Availability: Mar-2008

Tested by: Hewlett-Packard Company

Software Availability: May-2008



### Hardware

CPU Name: AMD Opteron 2356  
 CPU Characteristics:  
 CPU MHz: 2300  
 FPU: Integrated  
 CPU(s) enabled: 4 cores, 1 chip, 4 cores/chip  
 CPU(s) orderable: 1,2 chips  
 Primary Cache: 64 KB I + 64 KB D on chip per core  
 Secondary Cache: 512 KB I+D on chip per core  
 L3 Cache: 2 MB I+D on chip per chip  
 Other Cache: None  
 Memory: 16 GB (4x4 GB, PC2-5300P CL5)  
 Disk Subsystem: 2x72 GB 15 K SAS  
 Other Hardware: None

### Software

Operating System: SUSE Linux Enterprise Server 10 (x86\_64) SP1, Kernel 2.6.16.46-0.12-smp  
 Compiler: PGI Server Complete Version 7.2, PathScale Compiler Suite, Release Pre-3.2 Beta  
 Auto Parallel: No  
 File System: ext2  
 System State: Run level 3 (multi-user)  
 Base Pointers: 32/64-bit  
 Peak Pointers: 32/64-bit  
 Other Software: SmartHeap 8.1 32-bit Library for Linux, binutils-2.18.50



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Hewlett-Packard Company

SPECint\_rate2006 = 52.4

ProLiant DL385 G5  
(2.3 GHz AMD Opteron 2356)

SPECint\_rate\_base2006 = 45.7

CPU2006 license: 3

Test date: Mar-2008

Test sponsor: Hewlett-Packard Company

Hardware Availability: Mar-2008

Tested by: Hewlett-Packard Company

Software Availability: May-2008

## Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	4	809	48.3	803	48.7	<b>804</b>	<b>48.6</b>	4	<b>615</b>	<b>63.6</b>	616	63.5	614	63.6
401.bzip2	4	1092	35.3	1088	35.5	<b>1090</b>	<b>35.4</b>	4	<b>1049</b>	<b>36.8</b>	1048	36.8	1050	36.8
403.gcc	4	946	34.1	<b>940</b>	<b>34.3</b>	936	34.4	4	<b>824</b>	<b>39.1</b>	823	39.1	824	39.1
429.mcf	4	<b>1066</b>	<b>34.2</b>	1066	34.2	1066	34.2	4	751	48.6	<b>752</b>	<b>48.5</b>	752	48.5
445.gobmk	4	<b>890</b>	<b>47.2</b>	890	47.2	890	47.1	4	714	58.8	<b>714</b>	<b>58.8</b>	714	58.8
456.hammer	4	616	60.6	624	59.8	<b>616</b>	<b>60.6</b>	4	<b>420</b>	<b>88.9</b>	420	88.9	421	88.7
458.sjeng	4	984	49.2	<b>985</b>	<b>49.2</b>	986	49.1	4	902	53.7	900	53.7	<b>902</b>	<b>53.7</b>
462.libquantum	4	<b>1125</b>	<b>73.7</b>	1126	73.6	1124	73.8	4	1123	73.8	<b>1120</b>	<b>74.0</b>	1120	74.0
464.h264ref	4	<b>1159</b>	<b>76.4</b>	1179	75.1	1156	76.6	4	1143	77.4	<b>1142</b>	<b>77.5</b>	1136	78.0
471.omnetpp	4	748	33.4	<b>748</b>	<b>33.4</b>	748	33.4	4	748	33.4	<b>748</b>	<b>33.4</b>	748	33.4
473.astar	4	835	33.6	834	33.7	<b>835</b>	<b>33.6</b>	4	820	34.2	819	34.3	<b>820</b>	<b>34.2</b>
483.xalancbmk	4	594	46.5	593	46.5	<b>593</b>	<b>46.5</b>	4	<b>531</b>	<b>52.0</b>	531	52.0	531	52.0

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Operating System Notes

Environment stack size set to 'unlimited'  
Max locked memory set to 2097152  
PGI\_HUGE\_PAGES set to 896.  
Total number of huge pages available is 3584.

## Platform Notes

BIOS configuration:  
Power Regulator set to Static High Performance Mode

## Base Compiler Invocation

C benchmarks:  
pgcc  
  
C++ benchmarks:  
pgcpp

## Base Portability Flags

400.perlbench: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_LINUX\_X64  
401.bzip2: -DSPEC\_CPU\_LP64

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Hewlett-Packard Company

SPECint\_rate2006 = 52.4

ProLiant DL385 G5  
(2.3 GHz AMD Opteron 2356)

SPECint\_rate\_base2006 = 45.7

CPU2006 license: 3

Test date: Mar-2008

Test sponsor: Hewlett-Packard Company

Hardware Availability: Mar-2008

Tested by: Hewlett-Packard Company

Software Availability: May-2008

## Base Portability Flags (Continued)

```

403.gcc: -DSPEC_CPU_LP64
429.mcf: -DSPEC_CPU_LP64
445.gobmk: -DSPEC_CPU_LP64
456.hmmer: -DSPEC_CPU_LP64
458.sjeng: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX
464.h264ref: -DSPEC_CPU_LP64
483.xalancbmk: -DSPEC_CPU_LINUX

```

## Base Optimization Flags

C benchmarks:

```

-fast -Mipa=jobs:4 -Mipa=fast -Mipa=inline -Mfprelaxed
-Msmartalloc=huge:150 -tp barcelona-64 -Bstatic_pgi

```

C++ benchmarks:

```

-fastsse -Mipa=jobs:4 -Mipa=fast -Mipa=inline -Mfprelaxed
-Msmartalloc=huge:150 --zc_eh -tp barcelona -Bstatic_pgi

```

## Base Other Flags

C benchmarks:

-w

C++ benchmarks:

-w

## Peak Compiler Invocation

C benchmarks (except as noted below):

pgcc

400.perlbench: pathcc

403.gcc: pathcc

445.gobmk: pathcc

C++ benchmarks (except as noted below):

pathCC

471.omnetpp: pgcpp



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Hewlett-Packard Company

SPECint\_rate2006 = 52.4

ProLiant DL385 G5  
(2.3 GHz AMD Opteron 2356)

SPECint\_rate\_base2006 = 45.7

CPU2006 license: 3

Test date: Mar-2008

Test sponsor: Hewlett-Packard Company

Hardware Availability: Mar-2008

Tested by: Hewlett-Packard Company

Software Availability: May-2008

## Peak Portability Flags

400.perlbench: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_LINUX\_X64  
 401.bzip2: -DSPEC\_CPU\_LP64  
 445.gobmk: -DSPEC\_CPU\_LP64  
 456.hmmer: -DSPEC\_CPU\_LP64  
 458.sjeng: -DSPEC\_CPU\_LP64  
 462.libquantum: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_LINUX  
 464.h264ref: -DSPEC\_CPU\_LP64  
 483.xalanbmk: -DSPEC\_CPU\_LINUX

## Peak Optimization Flags

C benchmarks:

400.perlbench: -march=barcelona -fb\_create fbdata(pass 1)  
 -fb\_opt fbdata(pass 2) -Ofast -IPA:plimit=20000 -LNO:opt=0  
 -WOPT:if\_conv=0 -CG:local\_sched\_alg=1

401.bzip2: -Mpfi(pass 1) -Mpfo(pass 2) -fast -O4  
 -Msmartalloc=huge:150 -Mnounroll -tp barcelona-64  
 -Bstatic\_pgi

403.gcc: -march=barcelona -fb\_create fbdata(pass 1)  
 -fb\_opt fbdata(pass 2) -m32 -O3 -OPT:Ofast  
 -OPT:malloc\_alg=1

429.mcf: -fastsse -Mipa=jobs:4 -Mipa=fast -Mipa=inline:1  
 -Msmartalloc=huge:150 -tp barcelona -Bstatic\_pgi

445.gobmk: -march=barcelona -fb\_create fbdata(pass 1)  
 -fb\_opt fbdata(pass 2) -O3 -OPT:alias=restrict  
 -LNO:prefetch=1 -LNO:ignore\_feedback=off -CG:p2align=on

456.hmmer: -fastsse -Munroll=n:8 -Msmartalloc=huge:150 -Mfprelaxed  
 -Mvect=partial -Msafeptr -Mipa=jobs:4 -Mipa=const  
 -Mipa=ptr -Mipa=arg -Mipa=inline -tp barcelona-64  
 -Bstatic\_pgi

458.sjeng: -Mpfi(pass 1) -Mipa=jobs:4(pass 2) -Mipa=fast(pass 2)  
 -Mipa=inline:1(pass 2) -Mipa=noarg(pass 2) -Mpfo(pass 2)  
 -fastsse -Msmartalloc=huge:150 -Mfprelaxed  
 -tp barcelona-64 -Bstatic\_pgi

462.libquantum: -fastsse -Mfprelaxed -Msmartalloc=huge:150 -Munroll=m:8  
 -Mipa=jobs:4 -Mipa=fast -Mipa=inline -Mipa=noarg  
 -tp barcelona-64 -Bstatic\_pgi

464.h264ref: -Mpfi=indirect(pass 1) -Mipa=jobs:4(pass 2)  
 -Mipa=fast(pass 2) -Mipa=inline(pass 2)  
 -Mpfo=indirect(pass 2) -fastsse -Msmartalloc=huge:150

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Hewlett-Packard Company**

**SPECint\_rate2006 = 52.4**

ProLiant DL385 G5  
(2.3 GHz AMD Opteron 2356)

**SPECint\_rate\_base2006 = 45.7**

**CPU2006 license:** 3

**Test date:** Mar-2008

**Test sponsor:** Hewlett-Packard Company

**Hardware Availability:** Mar-2008

**Tested by:** Hewlett-Packard Company

**Software Availability:** May-2008

## Peak Optimization Flags (Continued)

464.h264ref (continued):

`-Mfprelaxed -tp barcelona-64 -Bstatic_pgi`

C++ benchmarks:

471.omnetpp: basepeak = yes

473.astar: `-march=barcelona -Ofast -TENV:frame_pointer=off  
-WOPT:if_conv=0 -GRA:optimize_boundary=on -IPA:plimit=525  
-m32 -lsmartheap`

483.xalancbmk: `-march=barcelona -Ofast -m32 -OPT:unroll_times_max=8  
-CG:push_pop_int_saved_regs=off -CG:ptr_load_use=0  
-lsmartheap`

## Peak Other Flags

C benchmarks (except as noted below):

`-w`

400.perlbench: No flags used

403.gcc: No flags used

445.gobmk: No flags used

C++ benchmarks (except as noted below):

`-L/root/work/cpu2006/amd123GH.libs/32`

471.omnetpp: `-w`

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/hp-PGI72-PS32-flags.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/hp-PGI72-PS32-flags.xml>



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Hewlett-Packard Company

ProLiant DL385 G5  
(2.3 GHz AMD Opteron 2356)

SPECint\_rate2006 = 52.4

SPECint\_rate\_base2006 = 45.7

**CPU2006 license:** 3  
**Test sponsor:** Hewlett-Packard Company  
**Tested by:** Hewlett-Packard Company

**Test date:** Mar-2008  
**Hardware Availability:** Mar-2008  
**Software Availability:** May-2008

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.0.  
Report generated on Tue Jul 22 18:34:03 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 15 April 2008.