



SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Hewlett-Packard Company

SPECint®_rate2006 = 132

ProLiant BL2x220c G5
(3.00 GHz, Intel Xeon E5450)

SPECint_rate_base2006 = 106

CPU2006 license: 3


Test date: May-2008

Test sponsor: Hewlett-Packard Company

Hardware Availability: May-2008

Tested by: Hewlett-Packard Company

Software Availability: Nov-2007



Hardware

CPU Name: Intel Xeon E5450
 CPU Characteristics: 3.00 GHz, 2x6 MB L2 shared, 1333 MHz system bus
 CPU MHz: 3000
 FPU: Integrated
 CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip
 CPU(s) orderable: 2,3,4 chips
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 12 MB I+D on chip per chip, 6 MB shared / 2 cores
 L3 Cache: None
 Other Cache: None
 Memory: 16 GB (4x4 GB PC2-5300P CL5)
 Disk Subsystem: 1x120 GB 5.4 K RPM 2.5" SFF SATA
 Other Hardware: None

Software

Operating System: SUSE Linux Enterprise Server 10 (x86_64) SP1, Kernel 2.6.16.46-0.12-smp
 Compiler: Intel C++ Compiler 10.1 for Linux Build 20070913 Package ID: l_cc_p_10.1.008
 Auto Parallel: Yes
 File System: ext2
 System State: Run level 3 (multi-user)
 Base Pointers: 32-bit
 Peak Pointers: 32/64-bit
 Other Software: MicroQuill SmartHeap Library 8.1 binutils-2.17.50



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Hewlett-Packard Company

SPECint_rate2006 = 132

ProLiant BL2x220c G5
(3.00 GHz, Intel Xeon E5450)

SPECint_rate_base2006 = 106

CPU2006 license: 3

Test date: May-2008

Test sponsor: Hewlett-Packard Company

Hardware Availability: May-2008

Tested by: Hewlett-Packard Company

Software Availability: Nov-2007

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	8	527	148	<u>524</u>	<u>149</u>	523	149	8	433	180	<u>434</u>	<u>180</u>	436	179
401.bzip2	8	<u>716</u>	<u>108</u>	715	108	717	108	8	680	113	677	114	<u>678</u>	<u>114</u>
403.gcc	8	680	94.7	<u>682</u>	<u>94.4</u>	683	94.3	8	678	94.9	<u>680</u>	<u>94.7</u>	681	94.6
429.mcf	8	<u>935</u>	<u>78.0</u>	935	78.0	937	77.8	8	944	77.3	<u>945</u>	<u>77.2</u>	948	77.0
445.gobmk	8	<u>567</u>	<u>148</u>	568	148	565	148	8	525	160	521	161	<u>524</u>	<u>160</u>
456.hammer	8	<u>597</u>	<u>125</u>	597	125	596	125	8	353	211	<u>354</u>	<u>211</u>	354	211
458.sjeng	8	690	140	691	140	<u>690</u>	<u>140</u>	8	618	157	<u>621</u>	<u>156</u>	621	156
462.libquantum	8	3581	46.3	3576	46.3	<u>3577</u>	<u>46.3</u>	1	89.9	230	91.1	227	<u>90.6</u>	<u>229</u>
464.h264ref	8	707	251	<u>707</u>	<u>250</u>	707	250	8	<u>678</u>	<u>261</u>	678	261	680	260
471.omnetpp	8	838	59.7	836	59.8	<u>836</u>	<u>59.8</u>	8	824	60.7	<u>823</u>	<u>60.7</u>	823	60.7
473.astar	8	745	75.4	730	77.0	<u>738</u>	<u>76.1</u>	8	695	80.8	696	80.7	<u>695</u>	<u>80.8</u>
483.xalancbmk	8	<u>443</u>	<u>125</u>	445	124	443	125	8	<u>443</u>	<u>125</u>	445	124	443	125

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

```
'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run
OMP_NUM_THREADS set to number of cores
KMP_AFFINITY set to physical,0
KMP_STACKSIZE set to 64M
```

Platform Notes

BIOS configuration:
Power Regulator set to Static High Performance Mode
Adjacent Sector Prefetch Disabled

General Notes

The ProLiant BL2x220c G5 is comprised of two independent server nodes in a single chassis. Only one of the server nodes was used for this benchmark; the other server node was idle during the benchmark. The active server node contained all of the CPUs and memory described in this disclosure.

Base Compiler Invocation

C benchmarks:
icc

C++ benchmarks:
icpc



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Hewlett-Packard Company

SPECint_rate2006 = 132

ProLiant BL2x220c G5
(3.00 GHz, Intel Xeon E5450)

SPECint_rate_base2006 = 106

CPU2006 license: 3

Test date: May-2008

Test sponsor: Hewlett-Packard Company

Hardware Availability: May-2008

Tested by: Hewlett-Packard Company

Software Availability: Nov-2007

Base Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32
462.libquantum: -DSPEC_CPU_LINUX
483.xalancbmk: -DSPEC_CPU_LINUX

Base Optimization Flags

C benchmarks:
-fast -inline-calloc -opt-malloc-options=3

C++ benchmarks:
-xT -ipo -O3 -no-prec-div -Wl,-z,muldefs
-L/cpu2006/SmartHeap_8.1/lib -lsmartheap

Base Other Flags

C benchmarks:
403.gcc: -Dalloca=_alloca

Peak Compiler Invocation

C benchmarks (except as noted below):
icc

401.bzip2: /opt/intel/cce/10.1.008/bin/icc
-L/opt/intel/cce/10.1.008/lib
-I/opt/intel/cce/10.1.008/include

456.hmmmer: /opt/intel/cce/10.1.008/bin/icc
-L/opt/intel/cce/10.1.008/lib
-I/opt/intel/cce/10.1.008/include

C++ benchmarks:
icpc

Peak Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32
401.bzip2: -DSPEC_CPU_LP64
456.hmmmer: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LINUX

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Hewlett-Packard Company

SPECint_rate2006 = 132

ProLiant BL2x220c G5
(3.00 GHz, Intel Xeon E5450)

SPECint_rate_base2006 = 106

CPU2006 license: 3

Test date: May-2008

Test sponsor: Hewlett-Packard Company

Hardware Availability: May-2008

Tested by: Hewlett-Packard Company

Software Availability: Nov-2007

Peak Portability Flags (Continued)

483.xalancbmk: -DSPEC_CPU_LINUX

Peak Optimization Flags

C benchmarks:

400.perlbench: -prof-gen(pass 1) -prof-use(pass 2) -fast -ansi-alias
-prefetch

401.bzip2: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch

403.gcc: -fast -inline-calloc -opt-malloc-options=3

429.mcf: -fast -prefetch

445.gobmk: -prof-gen(pass 1) -prof-use(pass 2) -xT -O2 -ipo
-no-prec-div -ansi-alias

456.hmmer: -fast -unroll2 -ansi-alias -opt-multi-version-aggressive

458.sjeng: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4

462.libquantum: -fast -unroll4 -Ob0 -prefetch
-opt-streaming-stores always -vec-guard-write
-opt-malloc-options=3 -parallel -par-runtime-control

464.h264ref: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
-ansi-alias

C++ benchmarks:

471.omnetpp: -prof-gen(pass 1) -prof-use(pass 2) -xT -O3 -ipo
-no-prec-div -ansi-alias -opt-ra-region-strategy=block
-Wl,-z,muldefs -L/cpu2006/SmartHeap_8.1/lib -lsmartheap

473.astar: -prof-gen(pass 1) -prof-use(pass 2) -xT -O3 -ipo
-no-prec-div -ansi-alias -opt-ra-region-strategy=routine
-Wl,-z,muldefs -L/cpu2006/SmartHeap_8.1/lib -lsmartheap

483.xalancbmk: basepeak = yes

Peak Other Flags

C benchmarks:

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Hewlett-Packard Company

SPECint_rate2006 = 132

ProLiant BL2x220c G5
(3.00 GHz, Intel Xeon E5450)

SPECint_rate_base2006 = 106

CPU2006 license: 3
Test sponsor: Hewlett-Packard Company
Tested by: Hewlett-Packard Company

Test date: May-2008
Hardware Availability: May-2008
Software Availability: Nov-2007

Peak Other Flags (Continued)

403.gcc: -Dalloca=_alloca

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/HP-Intel-ic10.1-linux-int-flags.20090714.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/HP-Intel-ic10.1-linux-int-flags.20090714.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 17:37:45 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 25 June 2008.