



# SPEC<sup>®</sup> CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## NEC Corporation

Express5800/B120a-d  
(Intel Xeon E5502)

SPECint<sup>®</sup>\_rate2006 = 36.1

SPECint\_rate\_base2006 = 33.6

CPU2006 license: 9006


Test sponsor: NEC Corporation

Tested by: NEC Corporation

Test date: Aug-2009

Hardware Availability: Jun-2009

Software Availability: Feb-2009



### Hardware

CPU Name: Intel Xeon E5502  
 CPU Characteristics: 1867  
 CPU MHz: 1867  
 FPU: Integrated  
 CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip  
 CPU(s) orderable: 1,2 chips  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 256 KB I+D on chip per core  
 L3 Cache: 4 MB I+D on chip per chip  
 Other Cache: None  
 Memory: 24 GB (6 X 4 GB PC3-8500R running at 800 MHz)  
 Disk Subsystem: 1x73.2 GB SAS, 10000 RPM  
 Other Hardware: None

### Software

Operating System: SUSE Linux Enterprise Server 10 (x86\_64) SP2 with patch Linux kernel 20090119, Kernel 2.6.16.60-0.34-smp  
 Compiler: Intel C++ Compiler Professional 11.0 for Linux Build 20090131 Package ID: l\_cproc\_p\_11.0.081  
 Auto Parallel: No  
 File System: ReiserFS  
 System State: Run level 3 (multi-user)  
 Base Pointers: 32-bit  
 Peak Pointers: 32/64-bit  
 Other Software: MicroQuill SmartHeap Library 8.1 Binutils 2.18.50.0.7.20080502



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## NEC Corporation

Express5800/B120a-d  
(Intel Xeon E5502)

SPECint\_rate2006 = 36.1

SPECint\_rate\_base2006 = 33.6

CPU2006 license: 9006

Test sponsor: NEC Corporation

Tested by: NEC Corporation

Test date: Aug-2009

Hardware Availability: Jun-2009

Software Availability: Feb-2009

## Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	2	693	28.2	<b>688</b>	<b>28.4</b>	687	28.4	2	589	33.2	<b>590</b>	<b>33.1</b>	591	33.1
401.bzip2	2	<b>997</b>	<b>19.4</b>	995	19.4	999	19.3	2	<b>951</b>	<b>20.3</b>	956	20.2	949	20.3
403.gcc	2	504	31.9	<b>505</b>	<b>31.9</b>	505	31.9	2	504	31.9	<b>505</b>	<b>31.9</b>	505	31.9
429.mcf	2	<b>357</b>	<b>51.0</b>	356	51.2	359	50.8	2	<b>357</b>	<b>51.0</b>	356	51.2	359	50.8
445.gobmk	2	<b>766</b>	<b>27.4</b>	768	27.3	766	27.4	2	712	29.5	<b>713</b>	<b>29.4</b>	713	29.4
456.hammer	2	<b>709</b>	<b>26.3</b>	709	26.3	709	26.3	2	521	35.8	<b>521</b>	<b>35.8</b>	521	35.8
458.sjeng	2	849	28.5	<b>850</b>	<b>28.5</b>	850	28.5	2	789	30.7	<b>789</b>	<b>30.7</b>	790	30.6
462.libquantum	2	316	131	317	131	<b>316</b>	<b>131</b>	2	315	132	<b>314</b>	<b>132</b>	313	132
464.h264ref	2	1028	43.1	<b>1028</b>	<b>43.1</b>	1031	42.9	2	970	45.6	<b>970</b>	<b>45.6</b>	971	45.6
471.omnetpp	2	468	26.7	<b>469</b>	<b>26.7</b>	470	26.6	2	468	26.7	<b>469</b>	<b>26.7</b>	470	26.6
473.astar	2	728	19.3	730	19.2	<b>730</b>	<b>19.2</b>	2	<b>638</b>	<b>22.0</b>	639	22.0	636	22.1
483.xalancbmk	2	353	39.1	<b>353</b>	<b>39.1</b>	353	39.1	2	353	39.1	<b>353</b>	<b>39.1</b>	353	39.1

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Submit Notes

The config file option 'submit' was used.  
numactl was used to bind copies to the cores

## Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run

## Platform Notes

Default BIOS settings were used.

## Base Compiler Invocation

C benchmarks:  
icc

C++ benchmarks:  
icpc

## Base Portability Flags

400.perlbench: -DSPEC\_CPU\_LINUX\_IA32

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**NEC Corporation**

**SPECint\_rate2006 = 36.1**

Express5800/B120a-d  
(Intel Xeon E5502)

**SPECint\_rate\_base2006 = 33.6**

**CPU2006 license:** 9006

**Test date:** Aug-2009

**Test sponsor:** NEC Corporation

**Hardware Availability:** Jun-2009

**Tested by:** NEC Corporation

**Software Availability:** Feb-2009

## Base Portability Flags (Continued)

462.libquantum: -DSPEC\_CPU\_LINUX  
483.xalancbmk: -DSPEC\_CPU\_LINUX

## Base Optimization Flags

C benchmarks:

-xSSE4.2 -ipo -O3 -no-prec-div -static -inline-calloc  
-opt-malloc-options=3 -opt-prefetch

C++ benchmarks:

-xSSE4.2 -ipo -O3 -no-prec-div -opt-prefetch -Wl,-z,muldefs  
-L/opt/SmartHeap\_8.1/lib -lsmartheap

## Base Other Flags

C benchmarks:

403.gcc: -Dalloca=\_alloca

## Peak Compiler Invocation

C benchmarks (except as noted below):

icc

401.bzip2: /opt/intel/Compiler/11.0/081/bin/intel64/icc

456.hmmer: /opt/intel/Compiler/11.0/081/bin/intel64/icc

458.sjeng: /opt/intel/Compiler/11.0/081/bin/intel64/icc

C++ benchmarks (except as noted below):

icpc

473.astar: /opt/intel/Compiler/11.0/081/bin/intel64/icpc

## Peak Portability Flags

400.perlbench: -DSPEC\_CPU\_LINUX\_IA32  
401.bzip2: -DSPEC\_CPU\_LP64  
456.hmmer: -DSPEC\_CPU\_LP64  
458.sjeng: -DSPEC\_CPU\_LP64

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**NEC Corporation**

Express5800/B120a-d  
(Intel Xeon E5502)

**SPECint\_rate2006 = 36.1**

**SPECint\_rate\_base2006 = 33.6**

**CPU2006 license:** 9006

**Test sponsor:** NEC Corporation

**Tested by:** NEC Corporation

**Test date:** Aug-2009

**Hardware Availability:** Jun-2009

**Software Availability:** Feb-2009

## Peak Portability Flags (Continued)

462.libquantum: -DSPEC\_CPU\_LINUX  
473.astar: -DSPEC\_CPU\_LP64  
483.xalancbmk: -DSPEC\_CPU\_LINUX

## Peak Optimization Flags

C benchmarks:

400.perlbench: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -static(pass 2)  
-prof-use(pass 2) -ansi-alias -opt-prefetch

401.bzip2: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -static(pass 2)  
-prof-use(pass 2) -opt-prefetch -ansi-alias -auto-ilp32

403.gcc: basepeak = yes

429.mcf: basepeak = yes

445.gobmk: -xSSE4.2(pass 2) -prof-gen(pass 1) -prof-use(pass 2) -O2  
-ipo -no-prec-div -ansi-alias

456.hmmer: -xSSE4.2 -ipo -O3 -no-prec-div -static -unroll2  
-ansi-alias -auto-ilp32

458.sjeng: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -static(pass 2)  
-prof-use(pass 2) -unroll4 -auto-ilp32

462.libquantum: -xSSE4.2 -ipo -O3 -no-prec-div -static  
-opt-malloc-options=3 -opt-prefetch

464.h264ref: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -static(pass 2)  
-prof-use(pass 2) -unroll2 -ansi-alias

C++ benchmarks:

471.omnetpp: basepeak = yes

473.astar: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)  
-ansi-alias -opt-ra-region-strategy=routine -auto-ilp32  
-Wl,-z,muldefs -L/opt/SmartHeap\_8.1/lib64 -lsmartheap64

483.xalancbmk: basepeak = yes



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**NEC Corporation**

Express5800/B120a-d  
(Intel Xeon E5502)

**SPECint\_rate2006 = 36.1**

**SPECint\_rate\_base2006 = 33.6**

**CPU2006 license:** 9006

**Test sponsor:** NEC Corporation

**Tested by:** NEC Corporation

**Test date:** Aug-2009

**Hardware Availability:** Jun-2009

**Software Availability:** Feb-2009

## Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=\_alloca

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic11.0-int-linux64-revG.html>

<http://www.spec.org/cpu2006/flags/NEC-Intel-Linux-Settings-flags-revE.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic11.0-int-linux64-revG.xml>

<http://www.spec.org/cpu2006/flags/NEC-Intel-Linux-Settings-flags-revE.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.1.

Report generated on Wed Jul 23 02:09:56 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 1 September 2009.