



SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

E4 Computer Engineering S.p.A.
E-Rack Twin E7116

SPECint®_rate2006 = 221
SPECint_rate_base2006 = 208

CPU2006 license: 3106


Test sponsor: E4 Computer Engineering S.p.A.

Tested by: E4 Computer Engineering S.p.A.

Test date: Mar-2011

Hardware Availability: Mar-2010

Software Availability: Jan-2009



Hardware

CPU Name: Intel Xeon E5620
 CPU Characteristics: Intel Turbo Boost Technology up to 2.67 GHz
 CPU MHz: 2400
 FPU: Integrated
 CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip, 2 threads/core
 CPU(s) orderable: 1,2 chips
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 256 KB I+D on chip per core
 L3 Cache: 12 MB I+D on chip per chip
 Other Cache: None
 Memory: 24 GB (6 x 4 GB 2Rx4 PC3-10600R-9, ECC, running at 1066 MHz)
 Disk Subsystem: 1 x 250GB SATA II Western Digital WD2502ABYS-01B7A0, 7200 rpm
 Other Hardware: None

Software

Operating System: openSUSE 11.1 (x86_64)
 Kernel 2.6.27.s7-9-default
 Compiler: Intel C++ Professional Compiler for IA32 and Intel 64, Version 11.1
 Build 20091130 Package ID: l_cproc_p_11.1.064
 Auto Parallel: No
 File System: ext3
 System State: Run level 3 (multi-user)
 Base Pointers: 32-bit
 Peak Pointers: 32/64-bit
 Other Software: Microquill SmartHeap V8.1



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

E4 Computer Engineering S.p.A.
E-Rack Twin E7116

SPECint_rate2006 = 221
SPECint_rate_base2006 = 208

CPU2006 license: 3106

Test sponsor: E4 Computer Engineering S.p.A.

Tested by: E4 Computer Engineering S.p.A.

Test date: Mar-2011

Hardware Availability: Mar-2010

Software Availability: Jan-2009

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	16	913	171	908	172	<u>909</u>	<u>172</u>	16	779	201	766	204	<u>769</u>	<u>203</u>
401.bzip2	16	1170	132	1160	133	<u>1162</u>	<u>133</u>	16	1105	140	1097	141	<u>1099</u>	<u>141</u>
403.gcc	16	764	169	757	170	<u>759</u>	<u>170</u>	16	<u>759</u>	<u>170</u>	765	168	753	171
429.mcf	16	606	241	<u>607</u>	<u>240</u>	608	240	8	<u>292</u>	<u>250</u>	292	250	299	244
445.gobmk	16	<u>852</u>	<u>197</u>	854	197	851	197	16	<u>784</u>	<u>214</u>	784	214	782	215
456.hammer	16	554	269	<u>554</u>	<u>269</u>	552	270	8	<u>255</u>	<u>292</u>	255	293	256	292
458.sjeng	16	<u>1060</u>	<u>183</u>	1062	182	1059	183	16	966	201	<u>969</u>	<u>200</u>	969	200
462.libquantum	16	527	629	526	630	<u>526</u>	<u>630</u>	16	525	631	<u>524</u>	<u>633</u>	523	634
464.h264ref	16	1365	259	<u>1374</u>	<u>258</u>	1403	252	16	1331	266	1375	257	<u>1351</u>	<u>262</u>
471.omnetpp	16	641	156	<u>642</u>	<u>156</u>	642	156	16	<u>578</u>	<u>173</u>	579	173	578	173
473.astar	16	873	129	870	129	<u>872</u>	<u>129</u>	16	<u>771</u>	<u>146</u>	772	146	770	146
483.xalancbmk	16	<u>503</u>	<u>219</u>	503	219	503	219	16	<u>503</u>	<u>219</u>	503	219	503	219

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

The config file option 'submit' was used.
numactl was used to bind copies to the cores

Operating System Notes

'ulimit -s unlimited' was used to set the stack size to unlimited prior to run

Platform Notes

Fan speed set to Full Speed in BIOS Setup.

Base Compiler Invocation

C benchmarks:
icc -m32

C++ benchmarks:
icpc -m32

Base Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

E4 Computer Engineering S.p.A.
E-Rack Twin E7116

SPECint_rate2006 = 221
SPECint_rate_base2006 = 208

CPU2006 license: 3106

Test sponsor: E4 Computer Engineering S.p.A.

Tested by: E4 Computer Engineering S.p.A.

Test date: Mar-2011

Hardware Availability: Mar-2010

Software Availability: Jan-2009

Base Portability Flags (Continued)

462.libquantum: -DSPEC_CPU_LINUX
483.xalancbmk: -DSPEC_CPU_LINUX

Base Optimization Flags

C benchmarks:

-xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch

C++ benchmarks:

-xSSE4.2 -ipo -O3 -no-prec-div -opt-prefetch -Wl,-z,muldefs
-L/opt/tools/smartHEAP/SmartHeap_8.1/lib -lsmartheap

Base Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

Peak Compiler Invocation

C benchmarks (except as noted below):

icc -m32

401.bzip2: icc -m64

456.hmmer: icc -m64

458.sjeng: icc -m64

462.libquantum: icc -m64

C++ benchmarks (except as noted below):

icpc -m32

473.astar: icpc -m64

Peak Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32

401.bzip2: -DSPEC_CPU_LP64

456.hmmer: -DSPEC_CPU_LP64

Continued on next page

Standard Performance Evaluation Corporation

info@spec.org

http://www.spec.org/



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

E4 Computer Engineering S.p.A.
E-Rack Twin E7116

SPECint_rate2006 = 221
SPECint_rate_base2006 = 208

CPU2006 license: 3106

Test sponsor: E4 Computer Engineering S.p.A.

Tested by: E4 Computer Engineering S.p.A.

Test date: Mar-2011

Hardware Availability: Mar-2010

Software Availability: Jan-2009

Peak Portability Flags (Continued)

458.sjeng: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX
473.astar: -DSPEC_CPU_LP64
483.xalancbmk: -DSPEC_CPU_LINUX

Peak Optimization Flags

C benchmarks:

400.perlbench: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
-O3(pass 2) -no-prec-div(pass 2) -static(pass 2)
-prof-use(pass 2) -ansi-alias
401.bzip2: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
-O3(pass 2) -no-prec-div(pass 2) -static(pass 2)
-prof-use(pass 2) -opt-prefetch -ansi-alias -auto-ilp32
403.gcc: -xSSE4.2 -ipo -O3 -no-prec-div -static
429.mcf: -xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch
445.gobmk: -xSSE4.2(pass 2) -prof-gen(pass 1) -prof-use(pass 2) -O2
-ipo -no-prec-div -ansi-alias
456.hmmmer: -xSSE4.2 -ipo -O3 -no-prec-div -static -unroll2
-ansi-alias -auto-ilp32
458.sjeng: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
-O3(pass 2) -no-prec-div(pass 2) -static(pass 2)
-prof-use(pass 2) -unroll4 -auto-ilp32
462.libquantum: -xSSE4.2 -ipo -O3 -no-prec-div -static -auto-ilp32
-opt-prefetch
464.h264ref: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
-O3(pass 2) -no-prec-div(pass 2) -static(pass 2)
-prof-use(pass 2) -unroll2 -ansi-alias

C++ benchmarks:

471.omnetpp: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)
-ansi-alias -opt-ra-region-strategy=block -Wl,-z,muldefs
-L/opt/tools/smartHEAP/SmartHeap_8.1/lib -lsmartheap
473.astar: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)
-ansi-alias -opt-ra-region-strategy=routine -Wl,-z,muldefs
-L/opt/tools/smartHEAP/SmartHeap_8/lib -lsmartheap64

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

E4 Computer Engineering S.p.A.
E-Rack Twin E7116

SPECint_rate2006 = 221
SPECint_rate_base2006 = 208

CPU2006 license: 3106

Test sponsor: E4 Computer Engineering S.p.A.

Tested by: E4 Computer Engineering S.p.A.

Test date: Mar-2011

Hardware Availability: Mar-2010

Software Availability: Jan-2009

Peak Optimization Flags (Continued)

483.xalancbmk: basepeak = yes

Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

The flags file that was used to format this result can be browsed at

http://www.spec.org/cpu2006/flags/flag_cint_rate_mar2011.html

You can also download the XML flags source by saving the following link:

http://www.spec.org/cpu2006/flags/flag_cint_rate_mar2011.xml

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.1.

Report generated on Wed Jul 23 19:11:14 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 12 April 2011.