



SPEC[®] CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated
(Test Sponsor: Acer Incorporation)

SPECfp[®]_rate2006 = 123

Acer AT310 F2 (Xeon E3-1280)

SPECfp_rate_base2006 = 119

CPU2006 license: 97


Test sponsor: Acer Incorporation

Tested by: Acer Incorporation

Test date: Dec-2011

Hardware Availability: Jan-2012

Software Availability: Dec-2011



Hardware

CPU Name: Intel Xeon E3-1280
 CPU Characteristics: Intel Turbo Boost Technology up to 3.90 GHz
 CPU MHz: 3500
 FPU: Integrated
 CPU(s) enabled: 4 cores, 1 chip, 4 cores/chip, 2 threads/core
 CPU(s) orderable: 1 chip
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 256 KB I+D on chip per core

Continued on next page

Software

Operating System: Red Hat Enterprise Linux Server release 6.1
 Kernel 2.6.32-131.0.15.el6.x86_64-default
 Compiler: C/C++: Version 12.1.0.225 of Intel C++ Studio XE for Linux;
 Fortran: Version 12.1.0.225 of Intel Fortran Studio XE for Linux
 Auto Parallel: No
 File System: ext3
 System State: Run level 3 (multi-user)

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated
(Test Sponsor: Acer Incorporation)

SPECfp_rate2006 = 123

Acer AT310 F2 (Xeon E3-1280)

SPECfp_rate_base2006 = 119

CPU2006 license: 97
Test sponsor: Acer Incorporation
Tested by: Acer Incorporation

Test date: Dec-2011
Hardware Availability: Jan-2012
Software Availability: Dec-2011

L3 Cache: 8 MB I+D on chip per chip
Other Cache: None
Memory: 8 GB (2 x 4 GB 2Rx8 PC3-10600E-9,ECC)
Disk Subsystem: 1 x 500 GB SATA, 7200 RPM
Other Hardware: None

Base Pointers: 32/64-bit
Peak Pointers: 32/64-bit
Other Software: Microquill SmartHeap V9.01

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	8	1184	91.8	1180	92.2	<u>1181</u>	<u>92.1</u>	4	<u>568</u>	<u>95.8</u>	567	95.8	571	95.3
416.gamess	8	<u>1010</u>	<u>155</u>	1006	156	1018	154	8	<u>980</u>	<u>160</u>	977	160	1121	140
433.milc	8	787	93.3	<u>787</u>	<u>93.3</u>	787	93.3	8	786	93.5	<u>786</u>	<u>93.4</u>	787	93.4
434.zeusmp	8	515	141	521	140	<u>519</u>	<u>140</u>	8	515	141	521	140	<u>519</u>	<u>140</u>
435.gromacs	8	452	126	453	126	<u>453</u>	<u>126</u>	8	452	126	<u>453</u>	<u>126</u>	494	116
436.cactusADM	8	669	143	667	143	<u>668</u>	<u>143</u>	8	669	143	667	143	<u>668</u>	<u>143</u>
437.leslie3d	8	<u>1239</u>	<u>60.7</u>	1240	60.7	1238	60.7	4	578	65.1	<u>578</u>	<u>65.1</u>	578	65.1
444.namd	8	518	124	<u>525</u>	<u>122</u>	529	121	8	516	124	<u>513</u>	<u>125</u>	512	125
447.dealII	8	<u>362</u>	<u>253</u>	360	254	373	245	8	<u>362</u>	<u>253</u>	360	254	373	245
450.soplex	8	1055	63.2	1053	63.4	<u>1053</u>	<u>63.3</u>	4	<u>423</u>	<u>78.8</u>	424	78.7	423	78.9
453.povray	8	200	213	<u>199</u>	<u>214</u>	199	214	8	172	247	171	249	<u>171</u>	<u>249</u>
454.calculix	8	336	197	<u>335</u>	<u>197</u>	334	198	8	326	202	336	196	<u>334</u>	<u>198</u>
459.GemsFDTD	8	1429	59.4	1428	59.4	<u>1429</u>	<u>59.4</u>	4	<u>740</u>	<u>57.4</u>	739	57.4	740	57.3
465.tonto	8	586	134	575	137	<u>581</u>	<u>136</u>	8	<u>559</u>	<u>141</u>	558	141	561	140
470.lbm	8	904	122	<u>905</u>	<u>122</u>	905	122	8	904	122	<u>905</u>	<u>122</u>	905	122
481.wrf	8	<u>808</u>	<u>111</u>	809	110	808	111	8	<u>799</u>	<u>112</u>	801	112	798	112
482.sphinx3	8	<u>1525</u>	<u>102</u>	1525	102	1527	102	8	<u>1470</u>	<u>106</u>	1485	105	1468	106

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

numactl was used to bind copies to the cores
The config file option 'submit' was used.

Operating System Notes

Large pages were disabled for this run.

General Notes

Binaries compiled on RHEL5.5



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated
(Test Sponsor: Acer Incorporation)

SPECfp_rate2006 = 123

Acer AT310 F2 (Xeon E3-1280)

SPECfp_rate_base2006 = 119

CPU2006 license: 97

Test date: Dec-2011

Test sponsor: Acer Incorporation

Hardware Availability: Jan-2012

Tested by: Acer Incorporation

Software Availability: Dec-2011

Base Compiler Invocation

C benchmarks:

icc -m64

C++ benchmarks:

icpc -m64

Fortran benchmarks:

ifort -m64

Benchmarks using both Fortran and C:

icc -m64 ifort -m64

Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64
 416.gamess: -DSPEC_CPU_LP64
 433.milc: -DSPEC_CPU_LP64
 434.zeusmp: -DSPEC_CPU_LP64
 435.gromacs: -DSPEC_CPU_LP64 -nofor_main
 436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
 437.leslie3d: -DSPEC_CPU_LP64
 444.namd: -DSPEC_CPU_LP64
 447.dealII: -DSPEC_CPU_LP64
 450.soplex: -DSPEC_CPU_LP64
 453.povray: -DSPEC_CPU_LP64
 454.calculix: -DSPEC_CPU_LP64 -nofor_main
 459.GemsFDTD: -DSPEC_CPU_LP64
 465.tonto: -DSPEC_CPU_LP64
 470.lbm: -DSPEC_CPU_LP64
 481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
 482.sphinx3: -DSPEC_CPU_LP64

Base Optimization Flags

C benchmarks:

-xAVX -ipo -O3 -no-prec-div -static -opt-prefetch -auto-p32
-ansi-alias

C++ benchmarks:

-xAVX -ipo -O3 -no-prec-div -static -opt-prefetch -auto-p32
-ansi-alias

Fortran benchmarks:

-xAVX -ipo -O3 -no-prec-div -static -opt-prefetch

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated
(Test Sponsor: Acer Incorporation)

SPECfp_rate2006 = 123

Acer AT310 F2 (Xeon E3-1280)

SPECfp_rate_base2006 = 119

CPU2006 license: 97
Test sponsor: Acer Incorporation
Tested by: Acer Incorporation

Test date: Dec-2011
Hardware Availability: Jan-2012
Software Availability: Dec-2011

Base Optimization Flags (Continued)

Benchmarks using both Fortran and C:

-xAVX -ipo -O3 -no-prec-div -static -opt-prefetch -auto-p32
-ansi-alias

Peak Compiler Invocation

C benchmarks (except as noted below):

icc -m64

482.sphinx3: icc -m32

C++ benchmarks (except as noted below):

icpc -m64

450.soplex: icpc -m32

Fortran benchmarks:

ifort -m64

Benchmarks using both Fortran and C:

icc -m64 ifort -m64

Peak Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX

Peak Optimization Flags

C benchmarks:

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated
(Test Sponsor: Acer Incorporation)

SPECfp_rate2006 = 123

Acer AT310 F2 (Xeon E3-1280)

SPECfp_rate_base2006 = 119

CPU2006 license: 97
Test sponsor: Acer Incorporation
Tested by: Acer Incorporation

Test date: Dec-2011
Hardware Availability: Jan-2012
Software Availability: Dec-2011

Peak Optimization Flags (Continued)

433.milc: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -prof-use(pass 2) -static -auto-ilp32

470.lbm: basepeak = yes

482.sphinx3: -xAVX -ipo -O3 -no-prec-div -unroll2

C++ benchmarks:

444.namd: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -prof-use(pass 2) -fno-alias
-auto-ilp32

447.dealIII: basepeak = yes

450.soplex: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -prof-use(pass 2) -opt-malloc-options=3

453.povray: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -prof-use(pass 2) -unroll4 -ansi-alias

Fortran benchmarks:

410.bwaves: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -prof-use(pass 2) -static

416.gamess: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -prof-use(pass 2) -unroll2
-inline-level=0 -scalar-rep- -static

434.zeusmp: basepeak = yes

437.leslie3d: -xAVX -ipo -O3 -no-prec-div -static -opt-prefetch

459.GemsFDTD: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -prof-use(pass 2) -opt-malloc-options=3

465.tonto: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -prof-use(pass 2) -unroll4 -auto
-inline-calloc -opt-malloc-options=3

Benchmarks using both Fortran and C:

435.gromacs: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -prof-use(pass 2) -opt-prefetch
-static -auto-ilp32

436.cactusADM: basepeak = yes

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated
(Test Sponsor: Acer Incorporation)

SPECfp_rate2006 = 123

Acer AT310 F2 (Xeon E3-1280)

SPECfp_rate_base2006 = 119

CPU2006 license: 97

Test sponsor: Acer Incorporation

Tested by: Acer Incorporation

Test date: Dec-2011

Hardware Availability: Jan-2012

Software Availability: Dec-2011

Peak Optimization Flags (Continued)

454.calculix: -xAVX -ipo -O3 -no-prec-div -static -auto-ilp32

481.wrf: Same as 454.calculix

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic12.1-official-linux64.20111122.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic12.1-official-linux64.20111122.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.2.
Report generated on Thu Jul 24 01:59:03 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 21 February 2012.