



SPEC® CPU2017 Integer Speed Result

Copyright 2017-2018 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

Integrity Superdome X

(384 core, 2.20 GHz, Intel Xeon E7-8890 v4)

SPECspeed2017_int_base = 5.31

SPECspeed2017_int_peak = 5.86

CPU2017 License: 3


Test Date: Dec-2016

Test Sponsor: HPE

Hardware Availability: Jun-2016

Tested by: HPE

Software Availability: Sep-2016



Hardware

CPU Name: Intel Xeon E7-8890 v4
 Max MHz.: 3400
 Nominal: 2200
 Enabled: 384 cores, 16 chips, 2 threads/core
 Orderable: 2 to 16 chips
 Cache L1: 32 KB I + 32 KB D on chip per core
 L2: 256 KB I+D on chip per core
 L3: 60 MB I+D on chip per chip
 Other: None
 Memory: 4 TB (128 x 32 GB 2Rx4 PC4-2400T-L, running at 1600)
 Storage: 8 x C8S59A, 900 GB 10 K RPM SAS
 Other: None

Software

OS: SUSE Linux Enterprise Server 12 (x86_64) SP1 3.12.53-60.30-default
 Compiler: C/C++: Version 17.0.0.098 of Intel C/C++ Compiler for Linux;
 Fortran: Version 17.0.0.098 of Intel Fortran Compiler for Linux
 Parallel: No
 Firmware: HP Bundle: 008.004.084 SFW: 043.025.000 08/16/2016
 File System: xfs
 System State: Run level 5 (multi-user, w/GUI)
 Base Pointers: 64-bit
 Peak Pointers: 32/64-bit
 Other: Microquill SmartHeap V10.2



SPEC CPU2017 Integer Speed Result

Copyright 2017-2018 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

Integrity Superdome X

(384 core, 2.20 GHz, Intel Xeon E7-8890 v4)

SPECspeed2017_int_base = 5.31

SPECspeed2017_int_peak = 5.86

CPU2017 License: 3

Test Date: Dec-2016

Test Sponsor: HPE

Hardware Availability: Jun-2016

Tested by: HPE

Software Availability: Sep-2016

Results Table

Benchmark	Base								Peak							
	Threads	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Threads	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
600.perlbench_s	384	365	4.86	358	4.96	357	4.98	384	298	5.95	295	6.02	295	6.01		
602.gcc_s	384	553	7.20	546	7.29	546	7.29	384	540	7.37	535	7.45	534	7.45		
605.mcf_s	384	866	5.45	866	5.45	898	5.26	384	708	6.67	700	6.75	699	6.75		
620.omnetpp_s	384	276	5.90	271	6.03	289	5.65	384	251	6.50	247	6.61	246	6.64		
623.xalancbmk_s	384	189	7.50	188	7.52	187	7.57	384	179	7.91	179	7.93	180	7.87		
625.x264_s	384	283	6.24	282	6.25	283	6.23	384	271	6.51	272	6.49	270	6.52		
631.deepsjeng_s	384	407	3.52	408	3.52	407	3.52	384	343	4.18	343	4.18	343	4.18		
641.leela_s	384	469	3.64	469	3.63	469	3.63	384	438	3.90	439	3.88	440	3.88		
648.exchange2_s	384	329	8.93	329	8.93	329	8.93	384	299	9.83	299	9.82	300	9.82		
657.xz_s	384	2165	2.86	2161	2.86	2164	2.86	384	2119	2.92	2120	2.92	2112	2.93		

SPECspeed2017_int_base = 5.31

SPECspeed2017_int_peak = 5.86

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

Stack size set to unlimited using "ulimit -s unlimited"
intel_idle.max_cstate=3 appended in kernel command line
Power profile set with:

cpupower -c all frequency-set -g performance

Setting the value of perf-bias:

cpupower set -b 0

Tuned profile set with:

tuned-adm profile throughput-performance

Transparent Huge Pages enabled by default

General Notes

Environment variables set by runcpu before the start of the run:

KMP_AFFINITY = "granularity=fine,scatter"

LD_LIBRARY_PATH = "/spec/cpu2017-rc4/lib/ia32:/spec/cpu2017-rc4/lib/intel64:/spec/cpu2017-rc4/sh10.2"

OMP_STACKSIZE = "192M"

Binaries compiled on a system with 1x Intel Core i7-4790K CPU + 32GB RAM
memory using Redhat Enterprise Linux 7.2

Platform Notes

Firmware settings:

Memory RAS Configuration set to Maximum Performance

Sysinfo program /spec/cpu2017-rc4/Docs/sysinfo

Rev: r5007 of 2016-11-15 fc8dc82f217779bedfed4d694d580ba9

(Continued on next page)



SPEC CPU2017 Integer Speed Result

Copyright 2017-2018 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

Integrity Superdome X

(384 core, 2.20 GHz, Intel Xeon E7-8890 v4)

SPECspeed2017_int_base = 5.31

SPECspeed2017_int_peak = 5.86

CPU2017 License: 3

Test Date: Dec-2016

Test Sponsor: HPE

Hardware Availability: Jun-2016

Tested by: HPE

Software Availability: Sep-2016

Platform Notes (Continued)

running on hawk049os1 Thu Dec 8 12:29:47 2016

This section contains SUT (System Under Test) info as seen by some common utilities.

For more information on this section, see
<http://www.spec.org/cpu2017/Docs/config.html#sysinfo>

From /proc/cpuinfo

```
model name : Intel(R) Xeon(R) CPU E7-8890 v4 @ 2.20GHz
 16 "physical id"s (chips)
 768 "processors"
cores, siblings (Caution: counting these is hw and system dependent. The
following excerpts from /proc/cpuinfo might not be reliable. Use with
caution.)
cpu cores : 24
siblings : 48
physical 0: cores 0 1 2 3 4 5 8 9 10 11 12 13 16 17 18 19 20 21 24 25 26
27 28 29
physical 1: cores 0 1 2 3 4 5 8 9 10 11 12 13 16 17 18 19 20 21 24 25 26
27 28 29
physical 2: cores 0 1 2 3 4 5 8 9 10 11 12 13 16 17 18 19 20 21 24 25 26
27 28 29
physical 3: cores 0 1 2 3 4 5 8 9 10 11 12 13 16 17 18 19 20 21 24 25 26
27 28 29
physical 4: cores 0 1 2 3 4 5 8 9 10 11 12 13 16 17 18 19 20 21 24 25 26
27 28 29
physical 5: cores 0 1 2 3 4 5 8 9 10 11 12 13 16 17 18 19 20 21 24 25 26
27 28 29
physical 6: cores 0 1 2 3 4 5 8 9 10 11 12 13 16 17 18 19 20 21 24 25 26
27 28 29
physical 7: cores 0 1 2 3 4 5 8 9 10 11 12 13 16 17 18 19 20 21 24 25 26
27 28 29
physical 8: cores 0 1 2 3 4 5 8 9 10 11 12 13 16 17 18 19 20 21 24 25 26
27 28 29
physical 9: cores 0 1 2 3 4 5 8 9 10 11 12 13 16 17 18 19 20 21 24 25 26
27 28 29
physical 10: cores 0 1 2 3 4 5 8 9 10 11 12 13 16 17 18 19 20 21 24 25 26
27 28 29
physical 11: cores 0 1 2 3 4 5 8 9 10 11 12 13 16 17 18 19 20 21 24 25 26
27 28 29
physical 12: cores 0 1 2 3 4 5 8 9 10 11 12 13 16 17 18 19 20 21 24 25 26
27 28 29
physical 13: cores 0 1 2 3 4 5 8 9 10 11 12 13 16 17 18 19 20 21 24 25 26
27 28 29
physical 14: cores 0 1 2 3 4 5 8 9 10 11 12 13 16 17 18 19 20 21 24 25 26
27 28 29
physical 15: cores 0 1 2 3 4 5 8 9 10 11 12 13 16 17 18 19 20 21 24 25 26
```

(Continued on next page)



SPEC CPU2017 Integer Speed Result

Copyright 2017-2018 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

Integrity Superdome X

(384 core, 2.20 GHz, Intel Xeon E7-8890 v4)

SPECspeed2017_int_base = 5.31

SPECspeed2017_int_peak = 5.86

CPU2017 License: 3

Test Sponsor: HPE

Tested by: HPE

Test Date: Dec-2016

Hardware Availability: Jun-2016

Software Availability: Sep-2016

Platform Notes (Continued)

```
27 28 29  
cache size : 61440 KB
```

```
The view from numactl --hardware follows.  WARNING: a numactl 'node' might or  
might not correspond to a physical chip.  
available: 16 nodes (0-15)  
node 0 cpus: 0 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 384  
385 386 387 388 389 390 391 392 393 394 395 396 397 398 399 400 401 402 403  
404 405 406 407  
node 0 size: 258296 MB  
node 0 free: 225316 MB  
node 1 cpus: 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45  
46 47 408 409 410 411 412 413 414 415 416 417 418 419 420 421 422 423 424 425  
426 427 428 429 430 431  
node 1 size: 258554 MB  
node 1 free: 231983 MB  
node 2 cpus: 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69  
70 71 432 433 434 435 436 437 438 439 440 441 442 443 444 445 446 447 448 449  
450 451 452 453 454 455  
node 2 size: 258554 MB  
node 2 free: 232225 MB  
node 3 cpus: 72 73 74 75 76 77 78 79 80 81 82 83 84 85 86 87 88 89 90 91 92 93  
94 95 456 457 458 459 460 461 462 463 464 465 466 467 468 469 470 471 472 473  
474 475 476 477 478 479  
node 3 size: 258554 MB  
node 3 free: 232046 MB  
node 4 cpus: 96 97 98 99 100 101 102 103 104 105 106 107 108 109 110 111 112  
113 114 115 116 117 118 119 480 481 482 483 484 485 486 487 488 489 490 491  
492 493 494 495 496 497 498 499 500 501 502 503  
node 4 size: 258554 MB  
node 4 free: 232220 MB  
node 5 cpus: 120 121 122 123 124 125 126 127 128 129 130 131 132 133 134 135  
136 137 138 139 140 141 142 143 504 505 506 507 508 509 510 511 512 513 514  
515 516 517 518 519 520 521 522 523 524 525 526 527  
node 5 size: 258554 MB  
node 5 free: 232080 MB  
node 6 cpus: 144 145 146 147 148 149 150 151 152 153 154 155 156 157 158 159  
160 161 162 163 164 165 166 167 528 529 530 531 532 533 534 535 536 537 538  
539 540 541 542 543 544 545 546 547 548 549 550 551  
node 6 size: 258554 MB  
node 6 free: 232151 MB  
node 7 cpus: 168 169 170 171 172 173 174 175 176 177 178 179 180 181 182 183  
184 185 186 187 188 189 190 191 552 553 554 555 556 557 558 559 560 561 562  
563 564 565 566 567 568 569 570 571 572 573 574 575  
node 7 size: 258554 MB  
node 7 free: 232256 MB  
node 8 cpus: 192 193 194 195 196 197 198 199 200 201 202 203 204 205 206 207
```

(Continued on next page)



SPEC CPU2017 Integer Speed Result

Copyright 2017-2018 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

Integrity Superdome X

(384 core, 2.20 GHz, Intel Xeon E7-8890 v4)

SPECspeed2017_int_base = 5.31

SPECspeed2017_int_peak = 5.86

CPU2017 License: 3

Test Date: Dec-2016

Test Sponsor: HPE

Hardware Availability: Jun-2016

Tested by: HPE

Software Availability: Sep-2016

Platform Notes (Continued)

```
208 209 210 211 212 213 214 215 576 577 578 579 580 581 582 583 584 585 586  
587 588 589 590 591 592 593 594 595 596 597 598 599  
node 8 size: 258554 MB  
node 8 free: 232241 MB  
node 9 cpus: 216 217 218 219 220 221 222 223 224 225 226 227 228 229 230 231  
232 233 234 235 236 237 238 239 600 601 602 603 604 605 606 607 608 609 610  
611 612 613 614 615 616 617 618 619 620 621 622 623  
node 9 size: 258554 MB  
node 9 free: 232215 MB  
node 10 cpus: 240 241 242 243 244 245 246 247 248 249 250 251 252 253 254 255  
256 257 258 259 260 261 262 263 624 625 626 627 628 629 630 631 632 633 634  
635 636 637 638 639 640 641 642 643 644 645 646 647  
node 10 size: 258554 MB  
node 10 free: 232247 MB  
node 11 cpus: 264 265 266 267 268 269 270 271 272 273 274 275 276 277 278 279  
280 281 282 283 284 285 286 287 648 649 650 651 652 653 654 655 656 657 658  
659 660 661 662 663 664 665 666 667 668 669 670 671  
node 11 size: 258554 MB  
node 11 free: 232235 MB  
node 12 cpus: 288 289 290 291 292 293 294 295 296 297 298 299 300 301 302 303  
304 305 306 307 308 309 310 311 672 673 674 675 676 677 678 679 680 681 682  
683 684 685 686 687 688 689 690 691 692 693 694 695  
node 12 size: 258554 MB  
node 12 free: 232243 MB  
node 13 cpus: 312 313 314 315 316 317 318 319 320 321 322 323 324 325 326 327  
328 329 330 331 332 333 334 335 696 697 698 699 700 701 702 703 704 705 706  
707 708 709 710 711 712 713 714 715 716 717 718 719  
node 13 size: 258554 MB  
node 13 free: 232258 MB  
node 14 cpus: 336 337 338 339 340 341 342 343 344 345 346 347 348 349 350 351  
352 353 354 355 356 357 358 359 720 721 722 723 724 725 726 727 728 729 730  
731 732 733 734 735 736 737 738 739 740 741 742 743  
node 14 size: 258554 MB  
node 14 free: 232239 MB  
node 15 cpus: 360 361 362 363 364 365 366 367 368 369 370 371 372 373 374 375  
376 377 378 379 380 381 382 383 744 745 746 747 748 749 750 751 752 753 754  
755 756 757 758 759 760 761 762 763 764 765 766 767  
node 15 size: 258549 MB  
node 15 free: 232181 MB  
node distances:  
node 0 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15  
0: 10 16 30 30 30 30 30 30 30 30 30 30 30 30 30 30  
1: 16 10 30 30 30 30 30 30 30 30 30 30 30 30 30 30  
2: 30 30 10 16 30 30 30 30 30 30 30 30 30 30 30 30  
3: 30 30 16 10 30 30 30 30 30 30 30 30 30 30 30 30  
4: 30 30 30 30 10 16 30 30 30 30 30 30 30 30 30 30  
5: 30 30 30 30 16 10 30 30 30 30 30 30 30 30 30 30
```

(Continued on next page)



SPEC CPU2017 Integer Speed Result

Copyright 2017-2018 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

Integrity Superdome X

(384 core, 2.20 GHz, Intel Xeon E7-8890 v4)

SPECspeed2017_int_base = 5.31

SPECspeed2017_int_peak = 5.86

CPU2017 License: 3

Test Date: Dec-2016

Test Sponsor: HPE

Hardware Availability: Jun-2016

Tested by: HPE

Software Availability: Sep-2016

Platform Notes (Continued)

```

6: 30 30 30 30 30 30 10 16 30 30 30 30 30 30 30 30 30 30 30 30 30
7: 30 30 30 30 30 30 16 10 30 30 30 30 30 30 30 30 30 30 30 30 30
8: 30 30 30 30 30 30 30 30 10 16 30 30 30 30 30 30 30 30 30 30 30
9: 30 30 30 30 30 30 30 30 16 10 30 30 30 30 30 30 30 30 30 30 30
10: 30 30 30 30 30 30 30 30 30 30 10 16 30 30 30 30 30 30 30 30 30
11: 30 30 30 30 30 30 30 30 30 30 16 10 30 30 30 30 30 30 30 30 30
12: 30 30 30 30 30 30 30 30 30 30 30 30 10 16 30 30 30 30 30 30 30
13: 30 30 30 30 30 30 30 30 30 30 30 30 16 10 30 30 30 30 30 30 30
14: 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 10 16
15: 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 16 10

```

From /proc/meminfo

```

MemTotal:        4235891396 kB
HugePages_Total:      0
Hugepagesize:       2048 kB

```

```
/usr/bin/lsb_release -d
SUSE Linux Enterprise Server 12 SP1
```

From /etc/*release* /etc/*version*

```

SuSE-release:
SUSE Linux Enterprise Server 12 (x86_64)
VERSION = 12
PATCHLEVEL = 1
# This file is deprecated and will be removed in a future service pack or
release.
# Please check /etc/os-release for details about this release.
os-release:
NAME="SLES"
VERSION="12-SP1"
VERSION_ID="12.1"
PRETTY_NAME="SUSE Linux Enterprise Server 12 SP1"
ID="sles"
ANSI_COLOR="0;32"
CPE_NAME="cpe:/o:suse:sles:12:sp1"
```

uname -a:

```
Linux hawk049os1 3.12.53-60.30-default #1 SMP Wed Feb 10 14:41:46 UTC 2016
(e57129f) x86_64 x86_64 x86_64 GNU/Linux
```

run-level 5 Dec 5 15:39

SPEC is set to: /spec/cpu2017-rc4

Filesystem	Type	Size	Used	Avail
Use% Mounted on				
/dev/mapper/3600c0ff0001e1834e672ee5701000000-part1	xfs	1.9T	832G	1.1T
44% /spec				

(Continued on next page)



SPEC CPU2017 Integer Speed Result

Copyright 2017-2018 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

Integrity Superdome X

(384 core, 2.20 GHz, Intel Xeon E7-8890 v4)

SPECspeed2017_int_base = 5.31

SPECspeed2017_int_peak = 5.86

CPU2017 License: 3

Test Sponsor: HPE

Tested by: HPE

Test Date: Dec-2016

Hardware Availability: Jun-2016

Software Availability: Sep-2016

Platform Notes (Continued)

Additional information from dmidecode follows. **WARNING:** Use caution when you interpret this section. The 'dmidecode' program reads system data which is "intended to allow hardware to be accurately determined", but the intent may not be met, as there are frequent changes to hardware, firmware, and the "DMTF SMBIOS" standard.

BIOS HP Bundle: 008.004.084 SFW: 043.025.000 08/16/2016

Memory:

128x HP HMA84GL7MFR4N-UH 32 GB 2 rank 1067 MHz, configured at 1600 MHz
256x not defined not defined

(End of data from sysinfo program)

Regarding the sysinfo display about the memory installed, the correct amount of memory is 4 TB and the dmidecode description should have one line reading as:
128x HP HMA84GL7MFR4N-UH 32 GB 2 rank 1067 MHz, configured at 1600 MHz

Compiler Version Notes

=====

CC 600.perlbench_s(base, peak) 602.gcc_s(base, peak) 605.mcf_s(base, peak)
625.x264_s(base, peak) 657.xz_s(base, peak)

=====

icc (ICC) 17.0.0 20160721
Copyright (C) 1985-2016 Intel Corporation. All rights reserved.

=====

CXXC 620.omnetpp_s(base, peak) 623.xalancbmk_s(base, peak)
631.deepsjeng_s(base, peak) 641.leela_s(base, peak)

=====

icpc (ICC) 17.0.0 20160721
Copyright (C) 1985-2016 Intel Corporation. All rights reserved.

=====

FC 648.exchange2_s(base, peak)

ifort (IFORT) 17.0.0 20160721
Copyright (C) 1985-2016 Intel Corporation. All rights reserved.

Base Compiler Invocation

C benchmarks:

icc -m64 -std=c11

(Continued on next page)



SPEC CPU2017 Integer Speed Result

Copyright 2017-2018 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

Integrity Superdome X

(384 core, 2.20 GHz, Intel Xeon E7-8890 v4)

SPECspeed2017_int_base = 5.31

SPECspeed2017_int_peak = 5.86

CPU2017 License: 3

Test Sponsor: HPE

Tested by: HPE

Test Date: Dec-2016

Hardware Availability: Jun-2016

Software Availability: Sep-2016

Base Compiler Invocation (Continued)

C++ benchmarks:

`icpc -m64`

Fortran benchmarks:

`ifort -m64`

Base Portability Flags

600.perlbench_s: -DSPEC_LP64 -DSPEC_LINUX_X64

602.gcc_s: -DSPEC_LP64

605.mcf_s: -DSPEC_LP64

620.omnetpp_s: -DSPEC_LP64

623.xalancbmk_s: -DSPEC_LP64 -DSPEC_LINUX

625.x264_s: -DSPEC_LP64

631.deepsjeng_s: -DSPEC_LP64

641.leela_s: -DSPEC_LP64

648.exchange2_s: -DSPEC_LP64

657.xz_s: -DSPEC_LP64

Base Optimization Flags

C benchmarks:

`-qopt-prefetch -qopt-mem-layout-trans=3 -DSPEC_SUPPRESS_OPENMP`

C++ benchmarks:

`-Wl,-z,muldefs -qopt-prefetch -qopt-mem-layout-trans=3
-DSPEC_SUPPRESS_OPENMP -L/sh10.2 -lsmartheap64`

Fortran benchmarks:

`-DSPEC_SUPPRESS_OPENMP -qopt-prefetch -qopt-mem-layout-trans=3
-nostandard-realloc-lhs`

Peak Compiler Invocation

C benchmarks:

`icc -m64 -std=c11`

(Continued on next page)



SPEC CPU2017 Integer Speed Result

Copyright 2017-2018 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

Integrity Superdome X

(384 core, 2.20 GHz, Intel Xeon E7-8890 v4)

SPECspeed2017_int_base = 5.31

SPECspeed2017_int_peak = 5.86

CPU2017 License: 3

Test Sponsor: HPE

Tested by: HPE

Test Date: Dec-2016

Hardware Availability: Jun-2016

Software Availability: Sep-2016

Peak Compiler Invocation (Continued)

C++ benchmarks:

icpc -m64

Fortran benchmarks:

ifort -m64

Peak Portability Flags

Same as Base Portability Flags

Peak Optimization Flags

C benchmarks:

600.perlbench_s: -prof-gen(pass 1) -prof-use(pass 2) -O2 -xCORE-AVX2
-auto-p32 -ipo -qopt-prefetch -O3 -no-prec-div
-qopt-mem-layout-trans=3 -DSPEC_SUPPRESS_OPENMP

602.gcc_s: Same as 600.perlbench_s

605.mcf_s: -prof-gen(pass 1) -prof-use(pass 2) -ipo -xCORE-AVX2 -O3
-no-prec-div -qopt-prefetch -qopt-mem-layout-trans=3
-DSPEC_SUPPRESS_OPENMP

625.x264_s: Same as 600.perlbench_s

657.xz_s: Same as 600.perlbench_s

C++ benchmarks:

620.omnetpp_s: -Wl,-z,muldefs -prof-gen(pass 1) -prof-use(pass 2) -ipo
-xCORE-AVX2 -O3 -no-prec-div -auto-p32 -qopt-prefetch
-qopt-mem-layout-trans=3 -DSPEC_SUPPRESS_OPENMP
-L/sh10.2 -lsmartheap64

623.xalancbmk_s: Same as 620.omnetpp_s

631.deepsjeng_s: -Wl,-z,muldefs -prof-gen(pass 1) -prof-use(pass 2) -ipo
-xCORE-AVX2 -O3 -no-prec-div -qopt-prefetch
-qopt-mem-layout-trans=3 -DSPEC_SUPPRESS_OPENMP
-L/sh10.2 -lsmartheap64

(Continued on next page)



SPEC CPU2017 Integer Speed Result

Copyright 2017-2018 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

Integrity Superdome X

(384 core, 2.20 GHz, Intel Xeon E7-8890 v4)

SPECspeed2017_int_base = 5.31

SPECspeed2017_int_peak = 5.86

CPU2017 License: 3

Test Sponsor: HPE

Tested by: HPE

Test Date: Dec-2016

Hardware Availability: Jun-2016

Software Availability: Sep-2016

Peak Optimization Flags (Continued)

641.leela_s: Same as 620.omnetpp_s

Fortran benchmarks:

```
-prof-gen(pass 1) -prof-use(pass 2) -DSPEC_SUPPRESS_OPENMP -ipo  
-xCORE-AVX2 -O3 -no-prec-div -qopt-prefetch -qopt-mem-layout-trans=3  
-nostandard-realloc-lhs
```

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2017/flags/Intel-ic17.0-official-linux64-revD.html>

<http://www.spec.org/cpu2017/flags/HP-Platform-Flags-Intel-V1.2-Integrity-revC.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2017/flags/Intel-ic17.0-official-linux64-revD.xml>

<http://www.spec.org/cpu2017/flags/HP-Platform-Flags-Intel-V1.2-Integrity-revC.xml>

SPEC is a registered trademark of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester. For other inquiries, please contact info@spec.org.

Tested with SPEC CPU2017 v0.904.0 on 2016-12-08 14:29:47-0500.

Report generated on 2018-10-31 12:38:49 by CPU2017 PDF formatter v6067.

Originally published on 2017-06-19.