



SPEChpc™ 2021 Tiny Result

Copyright 2021-2024 Standard Performance Evaluation Corporation

Intel

SPEChpc 2021_tny_base = 161

Endeavour: Intel Server D50DNP1SBB (Xeon Max 9480)

SPEChpc 2021_tny_peak = 162

hpc2021 License: 13


Test Date: Jun-2024

Test Sponsor: Intel

Hardware Availability: Jan-2023

Tested by: Intel

Software Availability: Mar-2024



Results Table

Benchmark	Base								Peak									
	Model	Ranks	Thrds/Rnk	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Model	Ranks	Thrds/Rnk	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
505.lbm_t	OMP	256	14	9.61	234	8.93	252	9.04	249	OMP	256	14	9.61	234	8.93	252	9.04	249
513.soma_t	OMP	256	14	22.4	165	22.2	166	22.3	166	OMP	256	14	22.4	165	22.2	166	22.3	166
518.tealeaf_t	OMP	256	14	6.76	244	7.02	235	7.67	215	OMP	256	14	6.76	244	7.02	235	7.67	215
519.civleaf_t	OMP	256	14	6.65	248	6.77	244	6.71	246	OMP	512	7	6.56	252	6.56	252	6.56	252
521.miniswp_t	OMP	256	14	25.0	63.9	25.0	64.0	25.1	63.8	OMP	256	14	25.0	63.9	25.0	64.0	25.1	63.8
528.pot3d_t	OMP	256	14	7.13	298	7.17	296	7.14	298	OMP	256	14	7.13	298	7.17	296	7.14	298
532.sph_exa_t	OMP	256	14	17.8	110	17.8	110	17.9	109	OMP	256	14	17.8	110	17.8	110	17.9	109
534.hpgmgfv_t	OMP	256	14	19.5	60.3	19.5	60.4	19.5	60.2	OMP	256	14	19.5	60.3	19.5	60.4	19.5	60.2
535.weather_t	OMP	256	14	13.1	246	13.2	244	13.2	244	OMP	256	14	13.1	246	13.2	244	13.2	244

SPEChpc 2021_tny_base = 161

SPEChpc 2021_tny_peak = 162

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.



SPEChpc™ 2021 Tiny Result

Copyright 2021-2024 Standard Performance Evaluation Corporation

Intel

SPEChpc 2021_tny_base = 161

Endeavour: Intel Server D50DNP1SBB (Xeon Max 9480)

SPEChpc 2021_tny_peak = 162

hpc2021 License: 13
Test Sponsor: Intel
Tested by: Intel

Test Date: Jun-2024
Hardware Availability: Jan-2023
Software Availability: Mar-2024

Hardware Summary

Type of System: Homogenous Cluster
Compute Node: Intel Server D50DNP1SBB (Xeon Max 9480)
Interconnect: Mellanox HDR
Compute Nodes Used: 32
Total Chips: 64
Total Cores: 3584
Total Threads: 7168
Total Memory: 20 TB
Max. Peak Threads: 14

Software Summary

Compiler: Intel oneAPI Compiler 2024.1.0
MPI Library: Intel MPI Library 2021.12 for Linux OS
Other MPI Info: None
Other Software: None
Base Parallel Model: OMP
Base Ranks Run: 256
Base Threads Run: 14
Peak Parallel Models: OMP
Minimum Peak Ranks: 256
Maximum Peak Ranks: 512
Max. Peak Threads: 14
Min. Peak Threads: 7

Node Description: Intel Server D50DNP1SBB (Xeon Max 9480)

Hardware

Number of nodes: 32
Uses of the node: Compute
Vendor: Intel
Model: Intel Server D50DNP1SBB (Xeon Max 9480)
CPU Name: Intel Xeon Max 9480
CPU(s) orderable: 1, 2 chips
Chips enabled: 2
Cores enabled: 112
Cores per chip: 56
Threads per core: 2
CPU Characteristics: Turbo Boost Technology up to 3.5 GHz
CPU MHz: 1900
Primary Cache: 32 KB I + 48 KB D on chip per core
Secondary Cache: 2 MB I+D on chip per core
L3 Cache: 112.5 MB I+D on chip per chip
Other Cache: None
Memory: 640 GB (16 x 32GB 2Rx8 PC5-4800B-R + 8 x 16GB HBM2 3200 MT/s)
Disk Subsystem: 1 x 1 TB NVMe U.2 2.5" SSD
Other Hardware: None
Accel Count: None
Accel Model: None
Accel Vendor: None
Accel Type: None
Accel Connection: None
Accel ECC enabled: None
Accel Description: None
Adapter: Mellanox ConnectX-6 HDR
Number of Adapters: 1
Slot Type: PCI-Express 4.0 x16
Data Rate: 200Gbit/s
Ports Used: 1

Software

Accelerator Driver: None
Adapter: Mellanox ConnectX-6 HDR
Adapter Driver: 23.04-0.5.3
Adapter Firmware: 20.37.1014
Operating System: Rocky Linux 8.8 (Green Obsidian) 4.18.0-477.15.1.el8_8.x86_64
Local File System: xfs
Shared File System: PANASAS FS
System State: Run level 5
Other Software: None

(Continued on next page)



SPEChpc™ 2021 Tiny Result

Copyright 2021-2024 Standard Performance Evaluation Corporation

Intel

SPEChpc 2021_tny_base = 161

Endeavour: Intel Server D50DNP1SBB (Xeon Max 9480)

SPEChpc 2021_tny_peak = 162

hpc2021 License: 13
Test Sponsor: Intel
Tested by: Intel

Test Date: Jun-2024
Hardware Availability: Jan-2023
Software Availability: Mar-2024

Node Description: Intel Server D50DNP1SBB (Xeon Max 9480)

Hardware (Continued)

Interconnect Type: Mellanox HDR

Interconnect Description: Mellanox HDR

Hardware

Vendor: Mellanox
Model: Mellanox HDR
Switch Model: Mellanox MQM8790-HS2F Quantum HDR InfiniBand Switch
Number of Switches: 18
Number of Ports: 40
Data Rate: 200 Gbit/s
Firmware: 20.36.1010
Topology: Fat-tree
Primary Use: MPI Traffic

Software

: --

Submit Notes

The config file option 'submit' was used.

General Notes

The PANASAS filesystem as described on this result page was formerly generally available. At the time of this publication, it may not be shipping, and/or may not be supported, and/or may fail to meet other tests of General Availability described in the SPEC HPG Policy document, <http://www.spec.org/hpg/policy.html>

HBM is configured as HBM cache mode.

Compiler Version Notes

=====
CXXC 532.sph_exa_t(base, peak)

Intel(R) oneAPI DPC++/C++ Compiler 2024.1.0 (2024.1.0.20240308)
Target: x86_64-unknown-linux-gnu
Thread model: posix
InstalledDir:
/global/panfs05/admin5/opt/intel/oneAPI/2024.1.0/compiler/2024.1/bin/compiler
Configuration file:
/global/panfs05/admin5/opt/intel/oneAPI/2024.1.0/compiler/2024.1/bin/compiler/./icpx.cfg

(Continued on next page)



SPEChpc™ 2021 Tiny Result

Copyright 2021-2024 Standard Performance Evaluation Corporation

Intel

SPEChpc 2021_tny_base = 161

Endeavour: Intel Server D50DNP1SBB (Xeon Max 9480)

SPEChpc 2021_tny_peak = 162

hpc2021 License: 13
Test Sponsor: Intel
Tested by: Intel

Test Date: Jun-2024
Hardware Availability: Jan-2023
Software Availability: Mar-2024

Compiler Version Notes (Continued)

=====
CC 505.lbm_t(base, peak) 513.soma_t(base, peak) 518.tealeaf_t(base, peak)
521.miniswp_t(base, peak) 534.hpgmgfv_t(base, peak)
=====

Intel(R) oneAPI DPC++/C++ Compiler 2024.1.0 (2024.1.0.20240308)

Target: x86_64-unknown-linux-gnu

Thread model: posix

InstalledDir:

/global/panfs05/admin5/opt/intel/oneAPI/2024.1.0/compiler/2024.1/bin/compiler

Configuration file:

/global/panfs05/admin5/opt/intel/oneAPI/2024.1.0/compiler/2024.1/bin/compiler/./icx.cfg
=====

=====
FC 519.clvleaf_t(base, peak) 528.pot3d_t(base, peak) 535.weather_t(base,
peak)
=====

ifx (IFX) 2024.1.0 20240308

Copyright (C) 1985-2024 Intel Corporation. All rights reserved.
=====

Base Compiler Invocation

C benchmarks:

mpiicc -cc=icx

C++ benchmarks:

mpicpc -cxx=icpx

Fortran benchmarks:

mpiifort -fc=ifx

Base Portability Flags

505.lbm_t: -lstdc++ -std=c++14
513.soma_t: -lstdc++ -std=c++14
518.tealeaf_t: -lstdc++ -std=c++14
521.miniswp_t: -lstdc++ -std=c++14
534.hpgmgfv_t: -lstdc++ -std=c++14



SPEChpc™ 2021 Tiny Result

Copyright 2021-2024 Standard Performance Evaluation Corporation

Intel

SPEChpc 2021_tny_base = 161

Endeavour: Intel Server D50DNP1SBB (Xeon Max 9480)

SPEChpc 2021_tny_peak = 162

hpc2021 License: 13
Test Sponsor: Intel
Tested by: Intel

Test Date: Jun-2024
Hardware Availability: Jan-2023
Software Availability: Mar-2024

Base Optimization Flags

C benchmarks:

```
-O3 -Ofast -xCORE-AVX512 -mprefer-vector-width=512  
-qopt-multiple-gather-scatter-by-shuffles -fiopenmp -ffast-math -flto  
-funroll-loops
```

C++ benchmarks:

```
-O3 -Ofast -xCORE-AVX512 -mprefer-vector-width=512  
-qopt-multiple-gather-scatter-by-shuffles -fiopenmp -ffast-math -flto  
-funroll-loops
```

Fortran benchmarks:

```
-O3 -Ofast -xCORE-AVX512 -mprefer-vector-width=512  
-qopt-multiple-gather-scatter-by-shuffles -fiopenmp -ffast-math -flto  
-funroll-loops -nostandard-realloc-lhs -align array64byte
```

Base Other Flags

C benchmarks:

```
-Wno-incompatible-function-pointer-types
```

Peak Compiler Invocation

C benchmarks:

```
mpiicc -cc=icx
```

C++ benchmarks:

```
mpiicpc -cxx=icpx
```

Fortran benchmarks:

```
mpiifort -fc=ifx
```

Peak Portability Flags

```
505.lbm_t: -lstdc++ -std=c++14  
513.soma_t: -lstdc++ -std=c++14  
518.tealeaf_t: -lstdc++ -std=c++14  
521.miniswp_t: -lstdc++ -std=c++14  
534.hpgmgfv_t: -lstdc++ -std=c++14
```



SPEChpc™ 2021 Tiny Result

Copyright 2021-2024 Standard Performance Evaluation Corporation

Intel

SPEChpc 2021_tny_base = 161

Endeavour: Intel Server D50DNP1SBB (Xeon Max 9480)

SPEChpc 2021_tny_peak = 162

hpc2021 License: 13
Test Sponsor: Intel
Tested by: Intel

Test Date: Jun-2024
Hardware Availability: Jan-2023
Software Availability: Mar-2024

Peak Optimization Flags

C benchmarks:

505.lbm_t: basepeak = yes
513.soma_t: basepeak = yes
518.tealeaf_t: basepeak = yes
521.miniswp_t: basepeak = yes
534.hpgmgfv_t: basepeak = yes

C++ benchmarks:

532.sph_exa_t: basepeak = yes

Fortran benchmarks:

519.clvleaf_t: -O3 -Ofast -xCORE-AVX512 -mprefer-vector-width=512
-qopt-multiple-gather-scatter-by-shuffles -fiopenmp
-ffast-math -flto -funroll-loops -nostandard-realloc-lhs
-align array64byte
528.pot3d_t: basepeak = yes
535.weather_t: basepeak = yes

Peak Other Flags

C benchmarks:

-Wno-incompatible-function-pointer-types

The flags files that were used to format this result can be browsed at

<http://www.spec.org/hpc2021/flags/HBM.html>
http://www.spec.org/hpc2021/flags/Intel_compiler_flags.2024-12-11.html

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/hpc2021/flags/HBM.xml>
http://www.spec.org/hpc2021/flags/Intel_compiler_flags.2024-12-11.xml



SPEChpc™ 2021 Tiny Result

Copyright 2021-2024 Standard Performance Evaluation Corporation

Intel

SPEChpc 2021_tny_base = 161

Endeavour: Intel Server D50DNP1SBB (Xeon Max 9480)

SPEChpc 2021_tny_peak = 162

hpc2021 License: 13
Test Sponsor: Intel
Tested by: Intel

Test Date: Jun-2024
Hardware Availability: Jan-2023
Software Availability: Mar-2024

SPEChpc is a trademark of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester. For other inquiries, please contact info@spec.org.

Tested with SPEChpc2021 v1.1.8 on 2024-06-10 07:34:23-0400.
Report generated on 2024-12-31 10:30:38 by hpc2021 PDF formatter v1.0.3.
Originally published on 2024-12-25.