



# OMPM2001 Result

Copyright ©1999-2002, Standard Performance Evaluation Corporation

Fujitsu Limited  
PRIMEPOWER HPC2500 (1.3GHz)

SPECompMpeak2001 = --  
SPECompMbase2001 = 22280

SPEC license #HPG0003 | Tested by: Fujitsu Limited | Test site: Numazu, Japan | Test date: May-2003 | Hardware Avail: Jul-2003 | Software Avail: May-2003

Benchmark	Reference Time	Base Runtime	Base Ratio	Peak Runtime	Peak Ratio	
310.wupwise_m	6000	275	21786			
312.swim_m	6000	147	40693			
314.mgrid_m	7300	194	37686			
316.applu_m	4000	71.4	56024			
318.galgel_m	5100	342	14908			
320.earthquake_m	2600	171	15194			
324.apsi_m	3400	120	28306			
326.gafort_m	8700	346	25139			
328.fma3d_m	4600	280	16424			
330.art_m	6400	378	16940			
332.ammp_m	7000	875	8001			

### Hardware

CPU: SPARC64 V  
 CPU MHz: 1299  
 FPU: Integrated  
 CPU(s) enabled: 128  
 CPU(s) orderable: 8 to 128  
 Primary Cache: 128KBI+128KBD on chip  
 Secondary Cache: 2MB(I+D) on chip, per CPU  
 L3 Cache: None  
 Other Cache: None  
 Memory: 512GB  
 Disk Subsystem: 1 x 36 GB Ultra SCSI  
 Other Hardware: None

### Software

OpenMP Threads: 32  
 Parallel: OpenMP  
 Operating System: Solaris 8  
 Fujitsu Parallelnavi 2.2 (NQS etc)  
 Compiler: Fujitsu Parallelnavi 2.2 (C & F90)  
 File System: ufs  
 System State: Multi-user

## Notes/Tuning Information

### Baseline flags:

C: -KOMP,fast\_GP2=2,V9,largepage=2,hardbarrier -x-  
 F90: -KOMP,fast\_GP2=2,V9,largepage=2,hardbarrier,prefetch\_line=4 -Nautoobjstack

### Portability Flags:

318.galgel\_m: -Am -Fixed -w  
 328.fma3d\_m: -Am

### Extra Flags:

330.art\_m: -DINTS\_PER\_CACHELINE=16 -DDBLS\_PER\_CACHELINE=8

### System tunables:

```
/etc/system:
set shmsys:shminfo_shmmax=268435456
set shmsys:shminfo_shmmni=2048
set shmsys:shminfo_shmseg=2048
set autoup=4800
set memscrub_period_sec=345600
/etc/opt/FJSVpnm/lpg.conf:
JOB=408G,SHMSEGSIZE=256M
/etc/opt/FJSVpnm/cpursc.conf:
CPU_USE=0-3:0-3
```



# OMPM2001 Result

Copyright ©1999-2002, Standard Performance Evaluation Corporation

Fujitsu Limited  
PRIMEPOWER HPC2500 (1.3GHz)

SPECompMpeak2001 = --  
SPECompMbase2001 = 22280

SPEC license #HPG0003 | Tested by: Fujitsu Limited | Test site: Numazu, Japan | Test date: May-2003 | Hardware Avail: Jul-2003 | Software Avail: May-2003

## Notes/Tuning Information (Continued)

NQS:

```
Per-process data size limit = UNLIMITED
Per-process permanent file size limit = UNLIMITED
Per-process memory size limit = 40 gigabytes
Per-request memory size limit = 32 gigabytes
Per-process number of cpus limit = 124
Per-process stack size limit = 4 gigabytes
Per-process CPU time limit = 2147483646.000
Execution mode = SIMplex
Jobclass = 0
```

Submitting the runspec to NQS:

Run the qsub command with the following sh script.

```
cd /spec/omp2001
. ./shrc
OMP_NUM_THREADS=32
export OMP_NUM_THREADS
runspec --config=Fujitsu --reportable medium
```