



OMPM2001 Result

Copyright 1999-2008, Standard Performance Evaluation Corporation

Supermicro Corporation
Supermicro H8QM8

SPECompMpeak2001 = 34415
SPECompMbase2001 = 33086

SPEC license #HPG0017 | Tested by: Advanced Micro Devices | Test site: Austin TX | Test date: Oct-2008 | Hardware Avail: Nov-2008 | Software Avail: Nov-2007

Benchmark	Reference Time	Base Runtime	Base Ratio	Peak Runtime	Peak Ratio	
310.wupwise_m	6000	124	48291	114	52530	
312.swim_m	6000	209	28774	171	35108	
314.mgrid_m	7300	175	41804	175	41804	
316.applu_m	4000	203	19744	203	19744	
318.galgel_m	5100	195	26212	195	26212	
320.quake_m	2600	86.0	30244	74.0	35136	
324.apsi_m	3400	78.8	43121	78.8	43121	
326.gafort_m	8700	267	32531	267	32531	
328.fma3d_m	4600	237	19432	237	19432	
330.art_m	6400	67.3	95069	67.3	95069	
332.ammp_m	7000	317	22077	317	22077	

Hardware

CPU: Quad-Core AMD Opteron(tm) Processor 8384
 CPU MHz: 2700
 FPU: Integrated
 CPU(s) enabled: 16 cores, 4 chips, 4 cores/chip
 CPU(s) orderable: 1-4
 Primary Cache: 64 KB I + 64 KB D on chip per core
 Secondary Cache: 512 KB I+D on chip per core
 L3 Cache: 6 MB I+D on chip per chip
 Other Cache: None
 Memory: 32GB (16x2GB, PC2-6400, CL5 dual-rank)
 Disk Subsystem: 160GB 7200 RPM SATA
 Other Hardware: None

Software

OpenMP Threads: 16
 Parallel: OpenMP
 Operating System: SUSE Linux Enterprise Server 10 (x86_64) SP1 2.6.16.46-0.12-mp
 Compiler: PathScale Compiler Suite ver. 3.1
 File System: Linux/Ext3
 System State: Multi-User

Notes/Tuning Information

Extra art Base Flags

330.art_m (extra): -DINTS_PER_CACHELINE=16 -DDBLS_PER_CACHELINE=8

Alternate Sources:

314.mgrid_m (base): intel

310.wupwise_m (peak), 312.swim_m (peak), 320.quake_m (peak): omp1.32

Base tuning:

C : pathcc -gnu3 -mp -Ofast -mcpu=barcelona -mcmmodel=medium

Fortran : pathf90 -mp -Ofast -mcpu=barcelona -OPT:early_mp=on -mcmmodel=medium

ONESTEP=yes

Peak Tuning:

310.wupwise_m: -mp -Ofast -msse3 -LNO:prefetch Ahead=5:prefetch=3

-OPT:unroll_times_max=8:unroll_size=128:IEEE_NaN_Inf=off:ro=3

-IPA:linear=on:plimit=50000:callee_limit=5000 -INLINE:aggressive=on

312.swim_m: -mp -O3 -OPT:Ofast -m3dnow -mcmmodel=medium -LNO:simd=0

314.mgrid_m: basepeak=yes

316.applu_m: basepeak=yes

318.galgel_m: basepeak=yes

320.quake_m: -Ofast -mp -OPT:alias=disjoint

324.apsi_m: basepeak=yes

326.gafort_m: basepeak=yes

328.fma3d_m: basepeak=yes

330.art_m: basepeak=yes

Standard Performance Evaluation Corporation

info@spec.org

http://www.spec.org



OMPM2001 Result

Copyright 1999-2008, Standard Performance Evaluation Corporation

Supermicro Corporation
Supermicro H8QM8

SPECompMpeak2001 = 34415
SPECompMbase2001 = 33086

SPEC license #HPG0017 | Tested by: Advanced Micro Devices | Test site: Austin TX | Test date: Oct-2008 | Hardware Avail: Nov-2008 | Software Avail: Nov-2007

Notes/Tuning Information (Continued)

332.amp_m: basepeak=yes
ONESTEP=yes for all peak tests.

Portability flags:

318.galgel_m : -fixedform -col80

Base and Peak User Environment (bash):

```
export OMP_NUM_THREADS=16
export OMP_DYNAMIC=FALSE
export PSC_OMP_AFFINITY=TRUE
export PSC_OMP_STATIC_FAIR=TRUE
export PSC_OMP_THREAD_SPIN=1000000000
ulimit -s unlimited
```

For flag descriptions, see file AMD-Jul2008-psc31_flags.txt
Default BIOS settings used, except PowerNow! disabled in Bios