



# CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

**SGI**  
**SGI 2800 128X 400MHz R12k**

SPECfp\_rate2000 = **407**  
SPECfp\_rate\_base2000 = **375**

SPEC license #: 4 | Tested by: SGI | Test date: May-2000 | Hardware Avail: Jun-2000 | Software Avail: Apr-2000

2000 1500 1000 500				Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
				168.wupwise	128	663	358	128	577	412
				171.swim	128	1823	252	128	1822	253
				172.mgrid	128	1162	230	128	1105	242
				173.applu	128	1104	282	128	1010	309
				177.mesa	128	505	412	128	472	441
				178.galgel	128	301	1433	128	261	1651
				179.art	128	260	1484	128	260	1485
				183.equake	128	797	242	128	783	247
				187.facerec	128	544	518	128	537	526
				188.amp	128	583	560	128	578	565
				189.lucas	128	1217	244	128	1206	246
				191.fma3d	128	1566	199	128	1318	237
				200.sixtrack	128	798	205	128	787	208
				301.apsi	128	1274	303	128	849	455

**Hardware**

CPU: R12000  
CPU MHz: 400  
FPU: Integrated  
CPU(s) enabled: 128 cores, 128 chips, 1 core/chip  
CPU(s) orderable: 64-512  
Parallel: No  
Primary Cache: 32KBI + 32KBD on chip  
Secondary Cache: 8MB(I+D) off chip  
L3 Cache: N/A  
Other Cache: N/A  
Memory: 128GB  
Disk Subsystem: 1 x 9 GB SCSI, 16 x 18 GB FC (striped)  
Other Hardware: None

**Software**

Operating System: IRIX 6.5.8f  
Compiler: MIPSpro 7.3.1m C, C++, Fortran90  
SCSL 1.2 Math Library  
File System: xfs  
System State: Single-user

## Notes/Tuning Information

Baseline optimization flags (for C benchmarks):  
PASS1 : -Ofast=ip27 -IPA:use\_intrinsic -fb\_create /tmp/SPEC2000/FBDIR\_base/\$(EXEBASE)  
PASS2 : -Ofast=ip27 -IPA:use\_intrinsic -fb\_opt /tmp/SPEC2000/FBDIR\_base/\$(EXEBASE)  
Baseline optimization flags (for Fortran benchmarks): -Ofast=ip27 -LNO:fusion=2  
Portability Flags:  
178.galgel: -fixedform  
Peak optimization flags:  
note: all occurrences of (FEEDBACK) below means compiled with a two-step process:  
PASS1 = -fb\_create /tmp/SPEC2000/FBDIR\_peak/\$(EXEBASE)  
PASS2 = -fb\_opt /tmp/SPEC2000/FBDIR\_peak/\$(EXEBASE)  
168.wupwise: -Ofast=ip27 -IPA:space=1000:linear=on:plimit=10000:callee\_limit=5000 -INLINE:aggressive=on  
-OPT:Olimit=0 -LNO:fusion=2:prefetch Ahead=5  
171.swim: -Ofast=ip27 -LNO:cs2=8m  
172.mgrid: -Ofast=ip27 -LNO:cs2=8m:fission=2:ou=2  
173.applu: -Ofast=ip27 -LNO:ou\_max=5:ou\_prod\_max=10:prefetch=0:fusion=2  
177.mesa: -Ofast=ip27 -OPT:goto=off -LNO:opt=0 (FEEDBACK)  
178.galgel: -Ofast=ip27 -LNO:ou\_max=7 -lscs (FEEDBACK)



# CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

SGI  
SGI 2800 128X 400MHz R12k

SPECfp\_rate2000 = 407  
SPECfp\_rate\_base2000 = 375

SPEC license #: 4 | Tested by: SGI | Test date: May-2000 | Hardware Avail: Jun-2000 | Software Avail: Apr-2000

## Notes/Tuning Information (Continued)

```
.
  RM_SOURCES = lapak.f90
179.art: -Ofast=ip27 -bigp_off -LNO:prefetch=0 -IPA:min_hot=15 (FEEDBACK)
183.quake: -Ofast=ip27 -LNO:prefetch=0 -TENV:X=4 -CG:ld_latency=7 -IPA:space=500 (FEEDBACK)
187.facerec: -Ofast=ip27 -fb_opt /tmp/SPEC2000/FBDIR_peak/$(EXEBASE) -LNO:fusion=2 (FEEDBACK)
188.ammp: -Ofast=ip27 -OPT:goto=off -IPA:space=500:plimit=900 (FEEDBACK)
189.lucas: -Ofast=ip27 -LNO:fusion=2:blocking=off -CG:ld_latency=4 -IPA:min_hot=8 (FEEDBACK)
191.fma3d: -Ofast=ip27 -bigp_off -LNO:prefetch=0 -OPT:goto=off:unroll_size=160:unroll_times_max=4
  -CG:ld_latency=2 (FEEDBACK)
200.sixtrack:= -Ofast=ip27 -IPA:maxdepth=2 -LNO:prefetch=0 (FEEDBACK)
301.apsi: -Ofast=ip27 -TENV:X=4 -LNO:prefetch=0:blocking=off -IPA:linear=on:use_intrinsic
The following O/S parameters were set:
  setenv PAGESIZE_DATA 4096
  setenv PAGESIZE_TEXT 4096
  setenv PAGESIZE_STACK 4096
  systune -i ; percent_totalmem_4m_pages = 50 ; nlpages_4m = 128
  limit stacksize 500000
The following is done before building each benchmark that requires (FEEDBACK):
rm -rf /tmp/SPEC2000/FBDIR_peak/$baseexe ; mkdir -p /tmp/SPEC2000/FBDIR_peak/$baseexe
or
rm -rf /tmp/SPEC2000/FBDIR_base/$baseexe ; mkdir -p /tmp/SPEC2000/FBDIR_base/$baseexe
```