



# CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

**Fujitsu Limited**  
**PRIMEPOWER800/1000/2000 (675MHz)**

SPECfp2000 = **456**  
SPECfp\_base2000 = **332**

SPEC license #: 19 | Tested by: Fujitsu Limited | Test date: Aug-2001 | Hardware Avail: Sep-2001 | Software Avail: Sep-2001

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	1000 2000 3000 4000			
168.wupwise	1600	500	320	339	472	[Bar chart showing ratio 472]			
171.swim	3100	941	329	852	364	[Bar chart showing ratio 364]			
172.mgrid	1800	765	235	583	309	[Bar chart showing ratio 309]			
173.applu	2100	1108	190	528	398	[Bar chart showing ratio 398]			
177.mesa	1400	395	354	372	376	[Bar chart showing ratio 376]			
178.galgel	2900	266	1089	228	1269	[Bar chart showing ratio 1269]			
179.art	2600	544	478	105	2472	[Bar chart showing ratio 2472]			
183.earthquake	1300	742	175	389	334	[Bar chart showing ratio 334]			
187.facerec	1900	382	497	305	623	[Bar chart showing ratio 623]			
188.amp	2200	535	411	509	432	[Bar chart showing ratio 432]			
189.lucas	2000	768	260	755	265	[Bar chart showing ratio 265]			
191.fma3d	2100	854	246	838	251	[Bar chart showing ratio 251]			
200.sixtrack	1100	394	279	348	316	[Bar chart showing ratio 316]			
301.apsi	2600	744	350	731	356	[Bar chart showing ratio 356]			

### Hardware

CPU: SPARC64 GP  
CPU MHz: 675  
FPU: Integrated  
CPU(s) enabled: 1 core, 1 chip, 1 core/chip  
CPU(s) orderable: 4 to 16/4 to 32/8 to 128  
Parallel: None  
Primary Cache: 128KBI+128KBD on chip  
Secondary Cache: 8MB(I+D) off chip, per CPU  
L3 Cache: None  
Other Cache: None  
Memory: 8192MB  
Disk Subsystem: 1 x 18.2GB SCSI (10025rpm)  
Other Hardware: Ethernet

### Software

Operating System: Solaris 8 4/01  
Compiler: Fujitsu Parallelnavi 1.0.2  
Sun Forte Developer 6 update 2  
File System: ufs  
System State: single user

## Notes/Tuning Information

```
FDO: (Parallelnavi 1.0.2)
fdo_pre0=rm -rf `pwd`/*.*.d
PASS1=-Kpg PASS2=-Kpu
FDO: (Forte Developer 6 update 2)
fdo_pre0=rm -rf `pwd`/../feedback.profile
PASS1=-xprofile=collect:`pwd`/../feedback
PASS2=-xprofile=use:`pwd`/../feedback
Baseline :
(using Fortran compiler of Parallelnavi 1.0.2)
-Kfast_GP=2,largepage -O4 -fs FDO

(using C compiler of Parallelnavi 1.0.2)
-Kfast_GP=2,largepage FDO

Peak:
(using Fortran compiler of Parallelnavi 1.0.2)
168.wupwise: -Kfast_GP=2,prefetch=4,nounroll -x dir=`pwd`/../../src -fs
```



# CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

**Fujitsu Limited**  
**PRIMEPOWER800/1000/2000 (675MHz)**

**SPECfp2000 = 456**  
**SPECfp\_base2000 = 332**

SPEC license #: 19 | Tested by: Fujitsu Limited | Test date: Aug-2001 | Hardware Avail: Sep-2001 | Software Avail: Sep-2001

## Notes/Tuning Information (Continued)

FDO ONESTEP=yes

171.swim: -Kfast\_GP=2,GREG,preex,ilfunc,prefetch=3,largepage,commonpad=152,prefetch\_iteration=3,unroll=2,nogs,frecipro  
-O4 -fs

172.mgrid: -Kfast\_GP=2,preex,GREG,commonpad=144,unroll=3,largepage,prefetch=3  
-O4 -fs

178.galgel: -Kfast\_GP=2,GREG,largepage,preex,unroll=2,prefetch\_iteration=2,commonpad=24  
-O4 -lssl2mtfma -fs FDO

RM\_SOURCES=lapak.f90

189.lucas: -Kfast\_GP=2,GREG,preex,largepage,nounroll -O4 -fs FDO

191.fma3d: -Kfast\_GP=2,preex,GREG,nounroll,prefetch=4,largepage -O4 -fs FDO

200.sixtrack: -Kfast\_GP=2,GREG,noprefetch,unroll=4,largepage,frecipro -fs

301.apsi: -Kfast\_GP=2,GREG,preex,largepage,unroll=2 -O4 -fs FDO

(using C compiler of Parallelnavi 1.0.2)

188.ammp: -Kfast\_GP=2,GREG,popt,prefetch=4,preex,preload,largepage,fuse,unroll=3 -x-

(using FORTRAN77 compiler of Forte Developer 6 update 2)

173.applu: -fast -Qoption iropt -whole,-Adata\_access,-Mt6000,-Mm12000,-Mr40000,-Ma400 -xarch=v8plus -dn  
ONESTEP=yes

(using FORTRAN90 compiler of Forte Developer 6 update 2)

187.facerec: -fast -xarch=v9 FDO ONESTEP=yes

(using C compiler of Forte Developer 6 update 2)

177.mesa: -fast -xcrossfile -xrestrict -xalias\_level=std -xregs=syst -Wc,-Qgsched-trace\_late=1,-Qgsched-trace\_spec\_load=1  
-xarch=v8plus -W2,-Amemopt -dn

FDO ONESTEP=yes

179.art: -fast -xalias\_level=strong -xdepend -xregs=syst -W2,-whole,-Amemopt  
-xarch=v8plus -lmopt -lm -dn FDO ONESTEP=yes

183.quake: -fast -xalias\_level=strong -xdepend -W2,-whole,-Amemopt  
-xarch=v8plus -lmopt -lm FDO ONESTEP=yes

### Portability:

(for Parallelnavi 1.0.2)

178.galgel: -Am -Fixed

187.facerec: -Am

191.fma3d: -Am

### Note:

System Tunables: (for /etc/system)

consistent\_coloring=1, tune\_t\_fsflushr=86400, autoup=86400,

shmsys:shminfo\_shmmax=8589934592, shmsys:shminfo\_shmmni=1024, shmsys:shminfo\_shmseg=1024

(for /etc/opt/FJSVpnm/lpg.conf)

TSS=512M, SHMSEGSIZE=256M

Feedback directed optimization was used for all baseline benchmarks and peak benchmarks except following peak benchmarks: 171.swim, 172.mgrid, 173.applu, 188.ammp, 200.sixtrack.

System board used with only one CPU present.