



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers
PRIMEPOWER800/1000/2000 (675MHz)

SPECfp_rate2000 = 78.6
SPECfp_rate_base2000 = 56.9

SPEC license #: 22 Tested by: Fujitsu Limited Test date: Sep-2001 Hardware Avail: Nov-2001 Software Avail: Dec-2001

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	16	544	54.6	16	372	79.8
171.swim	16	1190	48.4	16	1049	54.8
172.mgrid	16	883	37.8	16	691	48.3
173.applu	16	1275	30.6	16	560	69.5
177.mesa	16	399	65.1	16	375	69.2
178.galgel	16	270	200	16	232	232
179.art	16	557	86.7	16	106	453
183.equake	16	835	28.9	16	436	55.3
187.facerec	16	393	89.7	16	310	114
188.amp	16	534	76.5	16	506	80.7
189.lucas	16	883	42.0	16	869	42.7
191.fma3d	16	953	40.9	16	946	41.2
200.sixtrack	16	399	51.2	16	354	57.7
301.apsi	16	786	61.4	16	774	62.4

Hardware

CPU: SPARC64 GP
CPU MHz: 675
FPU: Integrated
CPU(s) enabled: 16 cores, 16 chips, 1 core/chip
CPU(s) orderable: 4 to 16/4 to 32/8 to 128
Parallel: None
Primary Cache: 128KBI+128KBD on chip
Secondary Cache: 8MB(I+D) off chip, per CPU
L3 Cache: None
Other Cache: None
Memory: 16GB
Disk Subsystem: 1 x 36GB, 1 x 18GB SCSI (10000rpm)
Other Hardware: None

Software

Operating System: Solaris 8 7/01
Compiler: Fujitsu Parallelnavi 1.0.2
with patch 911403-01
Sun Forte Developer 6 update 2
File System: ufs
System State: multi user

Notes/Tuning Information

```
FDO: (Parallelnavi 1.0.2)
fdo_pre0=rm -rf `pwd`/*.*.d
PASS1=-Kpg PASS2=-Kpu
FDO: (Forte Developer 6 update 2)
fdo_pre0=rm -rf `pwd`/../feedback.profile
PASS1=-xprofile=collect:`pwd`/../feedback
PASS2=-xprofile=use:`pwd`/../feedback
Baseline :
(using Fortran compiler of Parallelnavi 1.0.2)
-Kfast_GP=2,largepage -O4 -fs FDO

(using C compiler of Parallelnavi 1.0.2)
-Kfast_GP=2,largepage FDO

Peak:
(using Fortran compiler of Parallelnavi 1.0.2)
168.wupwise: -Kfast_GP=2,prefetch=4,nounroll -x dir=`pwd`/../../src -fs
```



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers
PRIMEPOWER800/1000/2000 (675MHz)

SPECfp_rate2000 = 78.6
SPECfp_rate_base2000 = 56.9

SPEC license #: 22 | Tested by: Fujitsu Limited | Test date: Sep-2001 | Hardware Avail: Nov-2001 | Software Avail: Dec-2001

Notes/Tuning Information (Continued)

FDO ONESTEP=yes

171.swim: -Kfast_GP=2,GREG,preex,ilfunc,prefetch=3,commonpad=152,prefetch_iteration=3,unroll=2,nogs,frecipro
-O4 -fs -dn

172.mgrid: -Kfast_GP=2,preex,GREG,commonpad=144,unroll=3,prefetch=3
-O4 -fs -dn

178.galgel: -Kfast_GP=2,GREG,largepage,preex,unroll=2,prefetch_iteration=2,commonpad=24
-O4 -lssl2mtfma -fs FDO

RM_SOURCES=lapak.f90

189.lucas: -Kfast_GP=2,GREG,preex,largepage,nounroll -O4 -fs FDO

191.fma3d: -Kfast_GP=2,preex,GREG,nounroll,prefetch=4,largepage -O4 -fs FDO

200.sixtrack: -Kfast_GP=2,GREG,noprefetch,unroll=4,frecipro -fs -dn

301.apsi: -Kfast_GP=2,GREG,preex,largepage,unroll=2 -O4 -fs FDO

(using C compiler of Parallelnavi 1.0.2)

188.ammp: -Kfast_GP=2,GREG,popt,prefetch=4,preex,preload,largepage,fuse,unroll=3 -x-

(using FORTRAN77 compiler of Forte Developer 6 update 2)

173.applu: -fast -Qoption iropt -whole,-Adata_access,-Mt6000,-Mm12000,-Mr40000,-Ma400 -xarch=v8plus -dn
ONESTEP=yes

(using FORTRAN90 compiler of Forte Developer 6 update 2)

187.facerec: -fast -xarch=v9 FDO ONESTEP=yes

(using C compiler of Forte Developer 6 update 2)

177.mesa: -fast -xcrossfile -xrestrict -xalias_level=std -xregs=syst -Wc,-Qgsched-trace_late=1,-Qgsched-trace_spec_load=1
-xarch=v8plus -W2,-Amemopt -dn

FDO ONESTEP=yes

179.art: -fast -xalias_level=strong -xdepend -xregs=syst -W2,-whole,-Amemopt
-xarch=v8plus -lmopt -lm -dn FDO ONESTEP=yes

183.quake: -fast -xalias_level=strong -xdepend -W2,-whole,-Amemopt
-xarch=v8plus -lmopt -lm FDO ONESTEP=yes

Portability:

(for Parallelnavi 1.0.2)

178.galgel: -Am -Fixed

187.facerec: -Am

191.fma3d: -Am

Note:

System Tunables: (for /etc/system)

consistent_coloring=1, tune_t_fsflushr=86400, autoup=86400,

shmsys:shminfo_shmmax=8589934592, shmsys:shminfo_shmmni=1024, shmsys:shminfo_shmseg=1024

(for /etc/opt/FJSVpnm/lpg.conf)

TSS=512M, SHMSEGSIZE=256M

Feedback directed optimization was used for all baseline benchmarks and peak benchmarks except following peak benchmarks: 171.swim, 172.mgrid, 173.applu, 188.ammp, 200.sixtrack.