



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Fujitsu Limited
PRIMEPOWER2000 (675MHz)

SPECint_rate2000 = 319
SPECint_rate_base2000 = 299

SPEC license #: 19 Tested by: Fujitsu Limited Test date: Sep-2001 Hardware Avail: Sep-2001 Software Avail: Dec-2001

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	64	371	280	64	364	285
175.vpr	64	369	282	64	353	294
176.gcc	64	484	169	64	394	207
181.mcf	64	439	305	64	382	350
186.crafty	64	223	332	64	198	376
197.parser	64	416	321	64	402	332
252.eon	64	280	345	64	263	367
253.perlbnk	64	376	355	64	369	362
254.gap	64	494	165	64	485	168
255.vortex	64	290	486	64	283	498
256.bzip2	64	341	326	64	342	326
300.twolf	64	597	373	64	558	399

Hardware

CPU: SPARC64 GP
CPU MHz: 675
FPU: Integrated
CPU(s) enabled: 64 cores, 64 chips, 1 core/chip
CPU(s) orderable: 8 to 128
Parallel: None
Primary Cache: 128KBI+128KBD on chip
Secondary Cache: 8MB(I+D) off chip, per CPU
L3 Cache: None
Other Cache: None
Memory: 128GB
Disk Subsystem: 1 x 36GB, 1 x 18GB SCSI (10000rpm)
Other Hardware: None

Software

Operating System: Solaris 8 7/01
Compiler: Fujitsu Parallelnavi 1.0.2 with patch 911403-01
Sun Forte Developer 6 update 2
File System: ufs
System State: multi user

Notes/Tuning Information

Baseline (except 252.eon, for Parallelnavi 1.0.2): -Kfast_GP=3,largepage
fdo_pre0=rm -rf `pwd`/*.fbk
PASS1=-Kpg
PASS2=-Kpu=\$(EXEBASE).fbk
(252.eon, for Forte Developer 6 update 2): -fast -xcrossfile -xarch=v8plus
fdo_pre0=rm -rf `pwd`/../feedback.profile `pwd`/SunWS_cache
PASS1=-xprofile=collect:`pwd`/../feedback
PASS2=-xprofile=use:`pwd`/../feedback

Peak (for Parallelnavi 1.0.2):
fdo_pre0=rm -rf `pwd`/*.fbk
PASS1=-Kpg
PASS2=-Kpu=\$(EXEBASE).fbk
164.gzip: -Kfast_GP=4,largepage
175.vpr: -Kfast_GP=4,staticclump,memalias,switchopt,cond,GREG,nounroll,largepage,onefile,NOFLTLTD=3,xi=30
181.mcf: -Kfast_GP=2,nounroll,memalias,restp,prefetch=2,largepage -x-
197.parser: -Kfast_GP=4,switchopt,cond,staticclump,use_rodata,largepage
253.perlbnk: -Kfast_GP=4,memalias,switchopt,largepage,bcopy
254.gap: -Kfast_GP=3,largepage,memalias,unroll=4
256.bzip2: -Kfast_GP=3,largepage



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Fujitsu Limited
PRIMEPOWER2000 (675MHz)

SPECint_rate2000 = 319
SPECint_rate_base2000 = 299

SPEC license #: 19 | Tested by: Fujitsu Limited | Test date: Sep-2001 | Hardware Avail: Sep-2001 | Software Avail: Dec-2001

Notes/Tuning Information (Continued)

```

300.twolf: -Kfast_GP=5,GREG,memalias,cfunc,staticclump,use_rodata,xi=10,largepage,nounroll,bcopy
(for Forte Developer 6 update 2)
fdo_pre0=rm -rf `pwd`/../../feedback.profile `pwd`/SunWS_cache
PASS1=-xprofile=collect:`pwd`/../../feedback
PASS2=-xprofile=use:`pwd`/../../feedback
176.gcc: -fast -xcrossfile -W2,-whole -Wc,-Qgsched-trace_late=1,-Qgsched-T4,-Qiselect-funcalign=64
-xarch=v8plus -xprefetch
186.crafty: -fast -xcrossfile -Wc,-Qgsched-trace_late=1,-Qgsched-T4 -xalias_level=strong
-xregs=syst -xchip=ultra2 -xarch=v8plus -W2,-Amemopt
252.eon: -fast -xcrossfile -xsafe=mem -Qoption iropt -Mt500,-restrict_g,-restrict
-Qoption cg -Qgsched-trace_late=1,-Qgsched-T4 -xarch=v8plus
255.vortex: -fast -xsafe=mem -xcrossfile -W2,-Aheap,-reroll=1,-Aunroll,-Ms1,-Mt500,-Mr6000,-crit
-Wc,-Qdepgraph-early_cross_call=1 -Wc,-Qiselect-funcalign=32 -Wc,-Qpeep-Sh0
-xrestrict -xdepend -Wc,-Qgsched-trace_late=1,-Qgsched-T4 -xarch=v8plus -W2,-Amemopt

```

Portability:

```

176.gcc: -Dalloca=__builtin_alloca -DHOST_WORDS_BIG_ENDIAN
186.crafty: -DSUN
252.eon: -library=iostream
253.perlbmk: -DSPEC_CPU2000_SOLARIS
254.gap: -DSYS_IS_USG -DSYS_HAS_TIME_PROTO -DSYS_HAS_SIGNAL_PROTO -DSYS_HAS_CALLOC_PROTO

```

Note:

```

System Tunables: (for /etc/system)
consistent_coloring=1, tune_t_fsflushr=86400, autoup=86400,
shmsys:shminfo_shmmax=8589934592, shmsys:shminfo_shmmni=1024, shmsys:shminfo_shmseg=1024
(for /etc/opt/FJSPvnm/lpg.conf)
TSS=512M, SHMSEGSIZE=256M
ONESTEP=yes was set for all baseline and peak benchmarks.
Feedback directed optimization was used for all baseline and peak benchmarks.

```