



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Advanced Micro Devices

Gigabyte GA-7DX Motherboard, AMD Athlon (TM) XP 1600+

SPECfp2000 = 547

SPECfp_base2000 = 504

SPEC license #: 49 Tested by: AMD Austin TX Test date: Sep-2001 Hardware Avail: Oct-2001 Software Avail: Sep-2001

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio
168.wupwise	1600	217	738	217	738
171.swim	3100	389	798	389	798
172.mgrid	1800	371	485	371	485
173.applu	2100	454	462	449	468
177.mesa	1400	190	738	183	767
178.galgel	2900	628	462	356	815
179.art	2600	704	369	668	389
183.quake	1300	294	443	242	538
187.facerec	1900	332	573	327	581
188.amp	2200	588	374	548	401
189.lucas	2000	369	541	367	545
191.fma3d	2100	377	557	377	557
200.sixtrack	1100	311	354	302	364
301.apsi	2600	634	410	546	476

Hardware

CPU: AMD Athlon (TM) XP 1600+
 CPU MHz: 1400
 FPU: Integrated
 CPU(s) enabled: 1 core, 1 chip, 1 core/chip
 CPU(s) orderable: 1
 Parallel: No
 Primary Cache: 64KBI + 64KBD on chip
 Secondary Cache: 256KB(I+D) on chip
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 2x128MB PC2100 DDR SDRAM CL2 Micron
 Disk Subsystem: IBM DPTA-372020
 Other Hardware: None

Software

Operating System: Windows 2000 SP2
 Compiler: Compaq Visual Fortran 6.6
 Intel C/C++ 5.0.1 build 010525Z and
 Intel Fortran 5.0.1 build 010525Z
 Microsoft Visual Studio 6.0 SP5 (libraries)
 MicroQuill Smartheap Library 5.0
 File System: FAT32
 System State: Default

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
icl and ifl are the Intel C/C++ and Fortran compilers
f90 is the Compaq Fortran compiler
shlw32M.lib is the SmartHeap library V5.0 from MicroQuill www.microquill.com
Portability:
178.galgel: -FI -Fe$@ -link -stack:32000000
Baseline: C icl -QxK -Qipo +FDO shlw32M.lib
Baseline: Fortran ifl -O3 -QxK -Qipo +FDO
Peak tuning:
168.wupwise: ifl -O3 -QxK -Qwp_ipo +FDO
171.swim: ifl -O3 -QxK -Qwp_ipo +FDO
172.mgrid: ifl -O3 -QxK -Qwp_ipo +FDO
173.applu: ifl -O3 -QxK -Qwp_ipo -Qscalar_rep- -Qauto +FDO
177.mesa: icl -O3 -QxK -Qwp_ipo -Oa -Qunroll10 +FDO shlw32M.lib
178.galgel: f90 -Optimize:5 -fast
179.art: icl -O3 -QxK -QaxW -Qwp_ipo -Oa +FDO shlw32M.lib
183.quake: icl -O3 -QxK -Qwp_ipo -Qrcd -Oa +FDO shlw32M.lib
```



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Advanced Micro Devices
Gigabyte GA-7DX Motherboard, AMD Athlon (TM) XP 1600+

SPECfp2000 = 547
SPECfp_base2000 = 504

SPEC license #: 49 | Tested by: AMD Austin TX | Test date: Sep-2001 | Hardware Avail: Oct-2001 | Software Avail: Sep-2001

Notes/Tuning Information (Continued)

```
187.facerec: f90 -Optimize:5 -fast
188.ammf: icl -O3 -QxK -Qwp_ipo -Oa +FDO
189.lucas: ifl -O3 -QxK -Qwp_ipo +FDO shlw32M.lib
191.fma3d: ifl -O3 -QxK -Qwp_ipo +FDO
200.sixtrack: ifl -QxK -QaxW -Qwp_ipo -Qprefetch +FDO
301.apsi: f90 -Optimize:5 -fast
```

Library ordering for 189.lucas (to include SmartHeap correctly with default libs):

```
LIBS=libIEPCF90.lib libintrins.lib libF90.lib
libqwind.lib libm.lib shlw32M.lib LIBC.lib libirc.lib OLDNAMES.lib
```

ONESTEP is used for all base and peak runs

The tested system can be assembled using an ATX case such as the Antec KS-282, a 300W power supply such as the Sparkle FSP300-60GT, and a PCI or AGP video card. The System bus runs at 266MHz