



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

IBM Corporation
IBM IntelliStation POWER Model 265

SPECfp_rate2000 = 8.19
SPECfp_rate_base2000 = 8.10

SPEC license #: 11 | Tested by: IBM Corp. | Test date: Jan-2002 | Hardware Avail: Mar-2002 | Software Avail: Dec-2001

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	314	11.8	2	314	11.8
171.swim	2	1123	6.40	2	1123	6.40
172.mgrid	2	645	6.47	2	645	6.47
173.applu	2	805	6.05	2	797	6.11
177.mesa	2	444	7.31	2	442	7.35
178.galgel	2	334	20.1	2	334	20.1
179.art	2	382	15.8	2	382	15.8
183.quake	2	359	8.40	2	346	8.72
187.facerec	2	490	9.00	2	490	9.00
188.amp	2	692	7.38	2	675	7.56
189.lucas	2	814	5.70	2	789	5.88
191.fma3d	2	713	6.83	2	689	7.07
200.sixtrack	2	521	4.89	2	521	4.89
301.apsi	2	839	7.19	2	839	7.19

Hardware

CPU: POWER3-II
CPU MHz: 450
FPU: Integrated
CPU(s) enabled: 2 cores, 2 chips, 1 core/chip
CPU(s) orderable: 1,2
Parallel: No
Primary Cache: 32KBI+64KBD (on chip)
Secondary Cache: 4MB unified (off chip)
L3 Cache: None
Other Cache: None
Memory: 2GB
Disk Subsystem: 2x18GB 10000RPM
Other Hardware: None

Software

Operating System: AIX 5L V5.1
Compiler: Fortran 77 and 90: IBM xl Fortran 7.1.1.0 invoked as xlf90 for Fortran 90 and as xlf for Fortran 77
C: IBM VAC++ 5.0.2.0 invoked as xlc
File System: AIX/JFS
System State: Multi-user

Notes/Tuning Information

Portability Flags
-qfixed used in: wupwise, swim, mgrid, applu, galgel, sixtrack, apsi
-qsuffix=f=f90 used in: galgel, facerec, lucas, fma3d

Base Optimization Flags:
Fortran: -O5 -lmass
C: -O5 -lmass

Peak Optimization Flags
168.wupwise: (basepeak=1)
171.swim: (basepeak=1)
172.mgrid: (basepeak=1)
173.applu: -O5 -lmass -qipa=partition=large
177.mesa: -O5 -lmass -qipa=partition=large, fdpr -v -R3
178.galgel: (basepeak=1)
179.art: (basepeak=1)
183.quake: -O5 -lmass -lhmu -qinline
187.facerec: (basepeak=1)
188.amp: -O3 -qarch=pwr3



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

IBM Corporation
IBM IntelliStation POWER Model 265

SPECfp_rate2000 = 8.19
SPECfp_rate_base2000 = 8.10

SPEC license #: 11 | Tested by: IBM Corp. | Test date: Jan-2002 | Hardware Avail: Mar-2002 | Software Avail: Dec-2001

Notes/Tuning Information (Continued)

```
189.lucas: -qpdf1/pdf2 -O3 -lhm -lmas
           -qipa=partition=large, fdpr -v -R3
191.fma3d: -O4 -lmas -qipa=partition=large
200.sixtrack: (basepeak=1)
301.apsi: (basepeak=1)
fpdr: Feedback directed program restructuring tool
/usr/spec2000 filesystem mounted with no JFS log file I/O
APAR IY22854 was applied to AIX 5L V5.1 to enable new hardware support
```