



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company
hp AlphaServer ES45 68/1250

SPECint2000 = NC
SPECint_base2000 = NC

SPEC license #: 2 | Tested by: HP NH | Test date: Jul-2002 | Hardware Avail: Aug-2002 | Software Avail: Nov-2002

SPEC has determined that this result was not in compliance with the SPEC CPU2000 run and reporting rules. Specifically, the submitter has reported that the 3 month availability requirement in the SPEC CPU2000 run rules will not be met due to a change in availability date for the operating system.

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	1	2	3	4	5
164.gzip	1400	NC	NC	NC	NC					
175.vpr	1400	NC	NC	NC	NC					
176.gcc	1100	NC	NC	NC	NC					
181.mcf	1800	NC	NC	NC	NC					
186.crafty	1000	NC	NC	NC	NC					
197.parser	1800	NC	NC	NC	NC					
252.eon	1300	NC	NC	NC	NC					
253.perlbmk	1800	NC	NC	NC	NC					
254.gap	1100	NC	NC	NC	NC					
255.vortex	1900	NC	NC	NC	NC					
256.bzip2	1500	NC	NC	NC	NC					
300.twolf	3000	NC	NC	NC	NC					

Hardware

CPU: Alpha 21264C
 CPU MHz: 1250
 FPU: Integrated
 CPU(s) enabled: 1 core, 1 chip, 1 core/chip
 CPU(s) orderable: 1 to 4
 Parallel: No
 Primary Cache: 64KB(I)+64KB(D) on chip
 Secondary Cache: 16MB off chip per CPU
 L3 Cache: None
 Other Cache: None
 Memory: 16GB
 Disk Subsystem: 9 GB SCSI
 Other Hardware: None

Software

Operating System: Tru64 UNIX V5.1B
 Compiler: Compaq C V6.5-011-48C5K
 Spike V5.2 (506 48C5K)
 Compaq C++ V6.3-010
 File System: ufs
 System State: Multi-user

Notes/Tuning Information

Baseline C : cc -arch ev6 -fast +CFB ONESTEP
 C++: cxx -arch ev6 -O2 ONESTEP

Peak:

All but 252.eon: cc -g3 -arch ev6 ONESTEP
 164.gzip: -fast -O4 -non_shared +CFB
 175.vpr: -fast -O4 -assume_restricted_pointers +CFB
 176.gcc: -fast -O4 -xtaso_short -all -ldensemalloc -none
 +CFB +IFB



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company
hp AlphaServer ES45 68/1250

SPECint2000 = NC
SPECint_base2000 = NC

SPEC license #: 2 | Tested by: HP NH | Test date: Jul-2002 | Hardware Avail: Aug-2002 | Software Avail: Nov-2002

SPEC has determined that this result was not in compliance with the SPEC CPU2000 run and reporting rules. Specifically, the submitter has reported that the 3 month availability requirement in the SPEC CPU2000 run rules will not be met due to a change in availability date for the operating system.

Notes/Tuning Information (Continued)

```

181.mcf: -fast -xtaso_short +CFB +IFB +PFB
186.crafty: same as base
197.parser: -fast -O4 -xtaso_short -non_shared +CFB
252.eon: cxx -arch ev6 -O2 -all -ldensemalloc -none
253.perlbnk: -fast -non_shared +CFB +IFB
254.gap: -fast -O4 -non_shared +CFB +IFB +PFB
255.vortex: -fast -non_shared +CFB +IFB
256.bzip2: -fast -O4 -non_shared +CFB
300.twolf: -fast -O4
          -ldensemalloc -non_shared +CFB +IFB

```

Most benchmarks are built using one or more types of profile-driven feedback. The types used are designated by abbreviations in the notes:

+CFB: Code generation is optimized by the compiler, using feedback from a training run. These commands are done before the first compile (in phase "fdo_pre0"):

```

mkdir /tmp/pp
rm -f /tmp/pp/${baseexe}*

```

and these flags are added to the first and second compiles:

```

PASS1_CFLAGS = -prof_gen_noopt -prof_dir /tmp/pp
PASS2_CFLAGS = -prof_use -prof_dir /tmp/pp

```

(Peak builds use /tmp/pp above; base builds use /tmp/pb.)

+IFB: Icache usage is improved by the post-link-time optimizer Spike, using feedback from a training run. These commands are used (in phase "fdo_postN"):

```

mv ${baseexe} oldexe
spike oldexe -feedback oldexe -o ${baseexe}

```

+PFB: Prefetches are improved by the post-link-time optimizer Spike, using feedback from a training run. These commands are used (in phase "fdo_post_makeN"):

```

rm -f *Counts*
mv ${baseexe} oldexe
pixie -stats dstride oldexe 1>pixie.out 2>pixie.err
mv oldexe.pixie ${baseexe}

```



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company
hp AlphaServer ES45 68/1250

SPECint2000 = NC
SPECint_base2000 = NC

SPEC license #: 2 | Tested by: HP NH | Test date: Jul-2002 | Hardware Avail: Aug-2002 | Software Avail: Nov-2002

SPEC has determined that this result was not in compliance with the SPEC CPU2000 run and reporting rules. Specifically, the submitter has reported that the 3 month availability requirement in the SPEC CPU2000 run rules will not be met due to a change in availability date for the operating system.

Notes/Tuning Information (Continued)

A training run is carried out (in phase "fdo_runN"), and then this command (in phase "fdo_postN"):

```
spike oldexe -fb oldexe -stride_prefetch -o ${baseexe}
```

When Spike is used for both Icache and Prefetch improvements, only one spike command is actually issued, with the Icache options followed by the Prefetch options.

vm:

```
vm_bigpg_enabled = 1  
vm_bigpg_thresh=16  
vm_swap_eager = 0
```

proc:

```
max_per_proc_address_space = 0x4000000000  
max_per_proc_data_size = 0x4000000000  
max_per_proc_stack_size = 0x4000000000  
max_proc_per_user = 2048  
max_threads_per_user = 0  
maxusers = 16384  
per_proc_address_space = 0x4000000000  
per_proc_data_size = 0x4000000000  
per_proc_stack_size = 0x4000000000
```

```
Portability: gcc: -Dalloca=__builtin_alloca; crafty: -DALPHA  
perlbnk: -DSPEC_CPU2000_DUNIX; vortex: -DSPEC_CPU2000_LP64  
gap: -DSYS_HAS_CALLOC_PROTO -DSYS_IS_BSD -DSYS_HAS_IOCTL_PROTO  
-DSPEC_CPU2000_LP64
```

Submitted_by: "Craig, Steve" <Steve.Craig@hp.com>
Submitted: Thu Aug 1 16:03:57 2002
Submission: cpu2000-20020801-01512.sub